ZER001_A1

Material Safety Data Sheet INTERPLATE ZERO GREY POWDER PART B

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: ZER001
MSDS Revision Date: 01/07/2010
MSDS Revision Number: A1-4



1. Identification of the preparation and company

Product Identity INTERPLATE ZERO GREY POWDER PART B

Bulk Sales Reference No. ZER001

Company Name International Paint LLC 6001 Antoine Drive

Houston, Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 527–3887

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product



Warning

GHS Classification;

Item	Category	Hazard	
Flammability	Not classified	Not applicable	
Acute Toxicity (mouth)	Not classified	Not applicable	
Acute Toxicity (skin)	Not classified	Not applicable	
Acute Toxicity (inhalation)	Not classified	Not applicable	
Acute Toxicity (ingestion)	Not classified	Not applicable	
Skin corrosion/irritation	Not classified	Not applicable	
Eye damage/irritation	Not classified	Not applicable	
Sensitization (respiratory)	Not classified	Not applicable	
Sensitization (skin)	Not classified	Not applicable	
Germ toxicity	Not classified	Not applicable	
Specific target organ systemic toxicity (single exposure)	1	systemic toxicity	
	2	Not applicable	
	3	Not applicable	
Specific target organ systemic Toxicity (repeated exposure)	1	lung	
	2	Not applicable	
Aspiration hazard	Not classified	Not applicable	
Harmfulness to aquatic Environment (acute)	1	Very Toxic to aquatic life.	
Harmfulness to aquatic Environment (long term effect)	1	Very Toxic to aquatic life with long lasting effects	

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects

HMIS Rating Health: 1 Flammability: 0 Reactivity: 0 PPE: X

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Carbonic acid, calcium salt (1:1)	0000471-34-1	1.0 – 10
Zinc oxide	0001314-13-2	1.0 – 10
Kaolin	0001332-58-7	1.0 – 10
Zinc	0007440-66-6	75 – 100

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

Ingestion If swallowed, immediately contact Poison Control Center at

1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious

person.

5. Fire-fighting measures

Flash Point F: No Established Limit

C: No Established Limit

Lower Explosive Limit

No Established Limit (%vol in air) at Normal Atmospheric Temp and Pressure

(LEL)

ERG Guide No. 170

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined

areas. Use non–sparking equipment to collect spilled material and transfer to containers for later disposal. DO NOT GET WATER INSIDE CONTAINERS.

Public Safety

CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep

unauthorized personnel away. Stay upwind.

ERG Guide No. 170

7. Handling and storage

Storage Temperature

Store between 40-100F (4-38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Finely divided powders are potentially explosive when suspended in air. Isolate from heat, sparks, electrical equipment and open flame. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Do not breathe dust. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

CAS No.	Ingredient	Source	Value		
0000471-34-1	Carbonic acid, calcium salt	OSHA	No Established Limit		
	(1:1)	ACGIH	No Established Limit		
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)		
		Supplier	No Established Limit		
		OHSA, CAN	10 mg/m3 TWAEV (containing no asbestos and less than 1% crystalline silica)		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
0001314–13–2	Zinc oxide	OSHA	5 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)10 mg/m3 STEL (fume)		
		ACGIH	2 mg/m3 TWA (respirable fraction)10 mg/m3 STEL (respirable fraction)		
		NIOSH	5 mg/m3 TWA (dust and fume)10 mg/m3 STEL (fume)15 mg/m3 Ceiling (dust)500 mg/m3 IDLH		
		Supplier	No Established Limit		
		OHSA, CAN	2 mg/m3 TWAEV (respirable)10 mg/m3 STEV (respirable)		
		Mexico	5 mg/m3 TWA (fume); 10 mg/m3 TWA (dust)10 mg/m3 STEL (fume)		
		Brazil	No Established Limit		
0001332–58–7 Kaolin		OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)		
		ACGIH	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and		
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)		
		Supplier	No Established Limit		
		OHSA, CAN	2 mg/m3 TWAEV (respirable, containing no asbestos and less than 1% crystalline silica)		
		Mexico	10 mg/m3 TWA20 mg/m3 STEL		
		Brazil	No Established Limit		
0007440-66-6	0007440-66-6 Zinc		No Established Limit		
		ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		

Health Data

CAS No.	Ingredient	Source	Value
0000471-34-1	Carbonic acid, calcium salt (1:1)	NIOSH	No Established Limit
0001314-13-2	Zinc oxide	NIOSH	Metal fume fever
0001332–58–7	Kaolin	NIOSH Skin and mucous membrane injury respiratory effects	
0007440-66-6	Zinc	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value	
0000471-34-1	Carbonic acid, calcium	OSHA	Select Carcinogen: No	
	salt (1:1)	NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0001314-13-2	Zinc oxide	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0001332-58-7	Kaolin	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0007440-66-6	007440–66–6 Zinc		Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

Respiratory Avoid breathing dust. Use a NIOSH approved respirator in accordance with

29CFR 1910.134 to remove particulates (and vapors if there is overexposure to vapors generated during the processing of this product). FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not

endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes Avoid contact with eyes. Protective equipment should be selected to

provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded

after each use.

Skin Protective equipment should be selected to provide protection from

exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment

must be thoroughly cleaned, or discarded after each use.

Engineering Controls Depending on the site-specific conditions of use, provide adequate

ventilation.

Other Work Practices Emergency eye wash fountains and safety showers should be available in

the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. Avoid contact with the property of the p

eyes and clothing. Avoid prolonged or repeated contact with skin.

9. Physical and chemical properties

Physical State Solid Coloured pH No Established Limit

Specific Gravity 5.81

Boiling Point F No Established Limit
Vapor Density Not Applicable

VOC % Refer to the Technical Data Sheet for this product

Evaporation Rate Not Applicable

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous May produce hazardous fumes when heated to decomposition as in welding. Fumes

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Carbonic acid, calcium salt (1:1) – (0000471–34–1)	6,450.00, Rat – Category: NA		
Zinc oxide – (0001314–13–2)	5,000.00, Rat – Category: 5		5.70, rat – Category: 3
Kaolin - (0001332-58-7)			
Zinc - (0007440-66-6)			

General No additional information provided for this product. See Sections 8 and 11 for

chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)
DOT Proper Shipping ZINC DUST (NOT IMDG Proper Shipping ZINC DUST

Name

Name HAZARDOUS BY

TESTING IN

TESTING IN ACCORDANCE WITH UN MANUAL OF TESTS AND CRITERIA)

DOT Hazard Class NR IMDG Hazard Class 4.3 – Dangerous when

wet materials

UN / NA Number Not Regulated UN / NA Number UN 1436

DOT Packing Group Not Regulated IMDG Packing Group III

CERCLA/DOT RQ 25 gal. / 1214 lbs. System Reference 12

Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification No Established Limit

```
DOT Marine Pollutants (10%):
      (No Product Ingredients Listed)
DOT Severe Marine Pollutants (1%):
     (No Product Ingredients Listed)
EPCRA 311/312 Chemicals and RQs (>.1%):
             Zinc (1000 lb final RQ (no release reporting if the pieces are larger than 100 µm); 454 kg)
EPCRA 302 Extremely Hazardous (>.1%):
      (No Product Ingredients Listed)
EPCRA 313 Toxic Chemicals (>.1%):
             Zinc
Mass RTK Substances (>1%):
            Kaolin
             Zinc
             Zinc oxide
Mass Extraordinarily Haz Sub (>.01%):
     (No Product Ingredients Listed)
Penn RTK Substances (>1%):
             Kaolin
             Zinc
             Zinc oxide
Penn Special Hazardous Substances (>.01%):
      (No Product Ingredients Listed)
Rhode Island Hazardous Substances (>.1%):
            Kaolin
             Zinc
             Zinc oxide
RCRA Status (%):
N.J. RTK Substances (>1%):
             Zinc
             Zinc oxide
N.J. Special Hazardous Substances (>.01%):
      (No Product Ingredients Listed)
N.J. Env. Hazardous Substances (>.1%):
            Zinc
Proposition 65 - Carcinogens (>0%):
             Cadmium
             Lead
Proposition 65 - Female Repro Toxins (>0%):
Proposition 65 - Male Repro Toxins (>0%):
            Cadmium
            Lead
Proposition 65 – Developmental Toxins (>0%):
             Cadmium
             Lead
```

Risk Phrases:

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.