

## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

1. Product and company identification
---------------------------------------

Hazardous according to criteria of the Australian Safety and Compensation Council.

This product is not a Dangerous Good for transport.

Product Name	INTERZINC 225 L-S PART A
Product Code	TQA425
Intended use	This product is intended for use in the marine and protective coatings markets. Refer Technical Data Sheet. For professional use only.
Application Method	Apply by brush and roller for small areas. Airless spray for large areas. Refer Technical Data Sheet.
Company Name	Akzo Nobel Protective Coatings 115 Hyde Road Yeronga Queensland Australia
Telephone No.	(07) 3892 8888
Fax No.	(07) 3892 4287
24 hour Emergency Telephone No.	1800 680 071
For Poisons Advice telephone	131 126 For Advice to Doctors & Hospitals only

2. Hazard Identification
--------------------------

R36/38 - Irritating to eyes and skin.

S23 - Do not breathe vapour/spray.

S25 - Avoid contact with eyes.

S51 - Use only in well-ventilated areas.

Poison Schedule: none assigned

**HSNO Number:** Not Applicable

Further information is given in section 11.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

### 3. Composition / information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations. Users are referred to the Australian Safety and Compensation Council (ASCC) website [www.ascc.gov.au](http://www.ascc.gov.au) for more information.

Ingredient	CAS Number	Concentration Range%	Symbol (s)	Risk phrases (*)
Silicic acid, potassium salt	0001312-76-1	25 - 50	Xn	R36/38

Other ingredients in this product have been determined not to be hazardous

\* The full text of the above phrases are shown in section 16.

### 4. First aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

#### Eye Contact

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

#### Skin Contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

#### Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

**5. Fire-fighting measures**

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Do not use - water jet.

Note; Fire will produce dense black smoke. Decomposition products may be hazardous to health. Avoid exposure and use breathing apparatus as appropriate.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

**6. Accidental release measures**

Ventilate the area to avoid breathing vapours. Take the personal protective measures listed in Section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to relevant State and Federal regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the relevant Environment Protection Agency.

Empty containers may contain product residues, including flammable or explosive vapours. Do not cut, puncture or weld on or near containers. All label warnings must be observed until the containers have been cleaned or reconditioned.

Ventilate the area to avoid breathing vapours. Take the personal protective measures listed in Section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to relevant State and Federal regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the relevant Environment Protection Agency.

Empty containers may contain product residues, including flammable or explosive vapours. Do not cut, puncture or weld on or near containers. All label warnings must be observed until the containers have been cleaned or reconditioned.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

7. Handling and storage
-------------------------

## Handling

## In Storage

Handle containers carefully to prevent damage and spillage.

## In Use

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Observe label precautions. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty a container; containers are not pressure vessels.

## Storage

Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same material.

Prevent unauthorised access.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

8. Exposure controls and personal protection
--

## Engineering Measures

## Exposure Limits

From the ASCC "Exposure Standards for Atmospheric Contaminants in the Occupational Environment". For detailed information refer to the ASCC web site ([www.ascc.gov.au](http://www.ascc.gov.au)).

Material	Short term (15 min. ave)		Long term (8hr time weighted average)	
	ppm	mg/M3	ppm	mg/M3

Chemicals classified as hazardous by the ASCC may have a notification alongside the exposure standard. If such a notification is necessary, it will appear in the far right hand column. The legend is as follows:

- (P) Peak exposure limit
- (R) Suppliers Recommended Limit
- (Sk) There is a risk of absorption through unbroken skin
- (Sen) Sensitiser
- (Cat1) Category 1 - established human carcinogen
- (Cat2) Category 2 - probable human carcinogen
- (Cat3) Category 3 - substances suspected of having carcinogenic potential.

There is no biological limit allocated.

## Personal Protection

## Respiratory Protection

When concentrations exceed the exposure limits shown above workers must wear appropriate respirators approved in accordance AS/NZS1716. Provision of other controls such as exhaust ventilation should be considered if practical.

## Eye Protection

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should comply with AS/NZS1337.

Wear a full face shield if mixing or pouring operations pose a risk of splashes.

An eye wash station is suggested as a good work place practice.

## Hand Protection

Gloves of an appropriate material should be worn during mixing and application. Nitrile or PVC gloves are generally recommended for products containing solvents.

## Skin Protection

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help to protect areas which are difficult to cover such as the face and neck. They should

however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

### 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Colour</b>	Light Coloured
<b>Flash Point (deg C closed cup)</b>	n/a
<b>Autoignition temperature</b>	---
<b>Viscosity (cSt)</b>	N/A
<b>Specific Gravity</b>	1.127
<b>Solvent Weight %</b>	Not Applicable
<b>Vapour Density</b>	Heavier than air.
<b>pH</b>	Not Applicable
<b>Lower Explosive Limit (%v/v air)</b>	Not Applicable
<b>Solubility in Water</b>	Immiscible
<b>R.A.Q. to ventilate to 10% of the LEL (M3/l)</b>	-
<b>Odour</b>	Smell of Solvent

### 10. Stability and reactivity

**Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**Conditions to avoid**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.

**Incompatible materials**

Strong acids, bases, oxidising agents.

**Hazardous decomposition products**

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

**Hazardous reactions**

None.

### 11. Toxicological information

There are no data available on the product itself.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

12. Ecological information
----------------------------

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

13. Disposal considerations
-----------------------------

Do not allow into drains or water courses. Wastes and empty containers should be disposed of in accordance with State and Federal regulations.

Using information provided in this data sheet advice should be obtained from the local Waste Regulation Authority as to whether special waste regulations apply.

14. Transport information
---------------------------

Transport only in accordance with the following regulations:

Road and Rail  
Transport Non Hazardous

IMDG reference :	Class/Div.	Subsidiary Class
	Proper Shipping Name	Non Hazardous
	UN No.	MFAG
	EMS	
	Packaging Group	
	Marine pollutant	No

ICAO/IATA	Shipping Name
	Class
	UN No.
	Packaging Group



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

15. Regulatory information
----------------------------

The following information is provided in accordance with ASCC guidelines for the labelling of Hazardous Substances.

Symbol(s)

Irritant

Contains;

R. Phrases;

R36/38 - Irritating to eyes and skin.

S. Phrases;

S23 - Do not breathe vapour/spray.

S25 - Avoid contact with eyes.

S51 - Use only in well-ventilated areas.

P. Phrases;



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TQA425

INTERZINC 225 L-S PART A

Version Number 5 Revision Date 07/04/11

16. Other information
-----------------------

Contact point:

Industrial Coatings HSE Department - Health and Safety Advisor  
+61 (0)3 9313 4555

Marine & Protective Coatings Regulatory Affairs Manager  
+61 (0)3 8336 8487

The information on this MSDS is based upon the present state of our knowledge and on current State and Federal laws.

The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Material Safety Data Sheet is required according to State and Federal legislation and following ASCC guidance (as amended).

The full text of the R phrases appearing in section 3 is:

R36 - Irritating to eyes.

R38 - Irritating to skin.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.