

# ECA066\_A5

## Material Safety Data Sheet INTERGARD 740 RED BASE

Sales  
Order: {SalesOrd}  
ECA066  
05/13/2011  
A5-3

Bulk Sales Reference No.:  
MSDS Revision Date:  
MSDS Revision Number:



### 1. Identification of the preparation and company

Product Identity INTERGARD 740 RED BASE  
Bulk Sales Reference No. ECA066  
Company Name International Paint LLC  
6001 Antoine Drive  
Houston Texas 77091

Emergency  
CHEMTREC (USA) (800) 424-9300  
International Paint (713) 682-1711  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

### 2. Hazard identification of the product



#### GHS Classification;

Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	central nerve system, kidneys, liver, respiratory system
	2	central nerve system
	3	narcotic effects
Specific target organ systemic Toxicity (repeated exposure)	1	central nerve system, respiratory system
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects
Carcinogenicity	Not classified	Not applicable

## ECA066\_A5

Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

## Safety Phrases:

S36/37: Wear suitable protective clothing and gloves.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.			
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.			
Eyes	Causes severe eye irritation. Avoid contact with eyes.			
Skin	Causes skin irritation. May be harmful if absorbed through the skin.			
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.			
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.			
HMIS Rating	Health: 2*	Flammability: 3	Reactivity: 0	PPE: X

## 3. Composition/information on ingredients

Ingredient	CAS No.	Percent
1,2,4-Trimethyl benzene	0000095-63-6	1.0 – 10
Benzene, ethyl-	0000100-41-4	1.0 – 10
Propylene glycol monomethyl ether	0000107-98-2	1.0 – 10
Xylenes (o-, m-, p- isomers)	0001330-20-7	10 – 25
Kaolin	0001332-58-7	1.0 – 10
Barium sulfate	0007727-43-7	25 – 50
Polymer of epoxy resin and bisphenol A	0025036-25-3	10 – 25
Petroleum naphtha, light aromatic	0064742-95-6	1.0 – 10

## 4. First aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

## 5. Fire-fighting measures

Flash Point	F: 81 C: 27
-------------	----------------

Lower Explosive Limit (LEL) 1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No.

128

## 6. Accidental release measures

Spill Response  
Procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

## Public Safety

CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No.

128

## 7. Handling and storage

## Storage Temperature

Store between 32 and 120 F

Handling and Storage  
Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

## 8. Exposure controls and personal protection

## Exposure

CAS No.	Ingredient	Source	Value
0000095–63–6	1,2,4–Trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000100–41–4	Benzene, ethyl–	OSHA	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		ACGIH	100 ppm TWA125 ppm STEL
		NIOSH	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA125 ppm STEL
		Mexico	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		Brazil	78 ppm TWA; 340 mg/m3 TWA
0000107–98–2	Propylene glycol monomethyl ether	OSHA	150 ppm STEL; 540 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	100 ppm TWA; 360 mg/m3 TWA150 ppm STEL; 540 mg/m3 STEL
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	No Established Limit
		Brazil	No Established Limit

ECA066\_A5

0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		Brazil	78 ppm TWA; 340 mg/m3 TWA
0001332-58-7	Kaolin	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	10 mg/m3 TWA20 mg/m3 STEL
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0025036-25-3	Polymer of epoxy resin and bisphenol A	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-95-6	Petroleum naphtha, light aromatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	NIOSH	No Established Limit
0000100-41-4	Benzene, ethyl-	NIOSH	Eye skin
0000107-98-2	Propylene glycol monomethyl ether	NIOSH	Eye nose
0001330-20-7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant; respiratory and eye irritation
0001332-58-7	Kaolin	NIOSH	Skin and mucous membrane injury respiratory effects
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0025036-25-3	Polymer of epoxy resin and bisphenol A	NIOSH	No Established Limit

## ECA066\_A5

0064742-95-6	Petroleum naphtha, light aromatic	NIOSH	No Established Limit
--------------	-----------------------------------	-------	----------------------

## Carcinogen Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000100-41-4	Benzene, ethyl-	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000107-98-2	Propylene glycol monomethyl ether	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylenes (o-, m-, p-isomers)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001332-58-7	Kaolin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025036-25-3	Polymer of epoxy resin and bisphenol A	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha, light aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices.

## ECA066\_A5

Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

### 9. Physical and chemical properties

Physical State	Liquid Coloured
pH	No Established Limit
Specific Gravity	1.46
Boiling Point F	210
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether

### 10. Stability and reactivity

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

### 11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
1,2,4-Trimethyl benzene – (0000095-63-6)	3,400.00, Rat – Category: 5	3,160.00, Rabbit – Category: 5	-----
Benzene, ethyl- – (0000100-41-4)	3,500.00, Rat – Category: 5	15,354.00, Rabbit – Category: NA	17.20, Rat – Category: 4
Propylene glycol monomethyl ether – (0000107-98-2)	5,200.00, Rat – Category: NA	13,000.00, Rabbit – Category: NA	54.60, Rat – Category: NA
Xylenes (o-, m-, p- isomers) – (0001330-20-7)	4,300.00, Rat – Category: 5	1,700.00, Rabbit – Category: 4	29.08, rat – Category: NA
Kaolin – (0001332-58-7)	-----	-----	-----
Barium sulfate – (0007727-43-7)	-----	-----	-----
Polymer of epoxy resin and bisphenol A – (0025036-25-3)	-----	-----	-----
Petroleum naphtha, light aromatic – (0064742-95-6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit – Category: 4	5.20, Rat – Category: 3

General	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.
---------	---

### 12. Ecological information

Not Defined  
No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

### 13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

### 14. Transport information

DOT (Domestic Surface Transportation)

IMO / IMDG (Ocean Transportation)

## ECA066\_A5

DOT Proper Shipping Name PAINT  
 DOT Hazard Class 3  
 UN / NA Number UN 1263  
 DOT Packing Group III  
 CERCLA/DOT RQ 59 gal. / 714 lbs.

IMDG Proper Shipping Name PAINT  
 IMDG Hazard Class 3 – Flammable and Combustible liquid  
 UN / NA Number UN 1263  
 IMDG Packing Group III  
 System Reference Code 2

15. Regulatory information
----------------------------

**Regulatory Overview**      The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

**WHMIS Classification**      B2:D2B

**DOT Marine Pollutants (10%):**  
 (No Product Ingredients Listed)

**DOT Severe Marine Pollutants (1%):**  
 (No Product Ingredients Listed)

**EPCRA 311/312 Chemicals and RQs (>.1%) :**  
 Cumene (5000 lb final RQ; 2270 kg final RQ)  
 Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)  
 Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

**EPCRA 302 Extremely Hazardous (>.1%) :**  
 (No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals (>.1%) :**  
 1,2,4-Trimethyl benzene  
 Cumene  
 Benzene, ethyl-  
 Xylenes (o-, m-, p- isomers)

**Mass RTK Substances (>1%) :**  
 1,2,4-Trimethyl benzene  
 Barium sulfate  
 Benzene, ethyl-  
 Kaolin  
 Propylene glycol monomethyl ether  
 Xylenes (o-, m-, p- isomers)

**Mass Extraordinarily Haz Sub (>.01%) :**  
 Quartz

**Penn RTK Substances (>1%) :**  
 1,2,4-Trimethyl benzene  
 Barium sulfate  
 Benzene, ethyl-  
 Kaolin  
 Propylene glycol monomethyl ether  
 Xylenes (o-, m-, p- isomers)

**Penn Special Hazardous Substances (>.01%) :**  
 (No Product Ingredients Listed)

**Rhode Island Hazardous Substances (>.1%) :**  
 Cumene  
 Diisobutylketone  
 Benzene, ethyl-  
 Kaolin  
 Propylene glycol monomethyl ether  
 Xylenes (o-, m-, p- isomers)

**RCRA Status:**  
 (No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

1,2,4-Trimethyl benzene  
Barium sulfate  
Benzene, ethyl-  
Kaolin  
Propylene glycol monomethyl ether  
Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%) :

Cumene  
Benzene, ethyl-  
Isobutyl alcohol  
Propylene glycol monomethyl ether  
Quartz  
Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-Trimethyl benzene  
Cumene  
Benzene, ethyl-  
Xylenes (o-, m-, p- isomers)

Proposition 65 – Carcinogens (>0%):

Cumene  
Benzene, ethyl-  
Formaldehyde  
Quartz

Proposition 65 – Female Repro Toxins (>0%):  
(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):  
(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):  
(No Product Ingredients Listed)

Risk Phrases:

R20/21: Harmful by inhalation and in contact with skin.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.