

**BXA739 INTERSLEEK 737 PART C**

1

09/07/13

**1.****1.1.**

INTERSLEEK 737 PART C

BXA739

**1.2.****1.3.**

International Paint Singapore Pte Ltd  
3 Neythal Road  
Jurong Town  
Singapore 628570

+65 6261 5033

+65 6264 4612

**1.4.**

+65 6261 5033

**2.****2.1.**

3; H226

- 4;H312

- 4;H332

/

2;H315

1;H317

**2.2.**

11 , 12



H226

H312

H315

H317

H332

[ ]:

P210 / / /

P261 / /가 / / /

P264

P271 가

P272

P273

P280 / / /

[ ]:

P302+352 :

P303+361+353 ( ) :

P304+312 : /

P321 ( ).

P322 ( ).

P333+313 /

P340 가

P362

P363

P370 :

P378 , , ,

[ ]:

P403+233 가

[ ]:

P501 ( )

2.3. PBT ( , ) vPvB ( , )

3.

/	%	GHS	
<b>xylene</b> CAS No: 0001330-20-7	80-90	3; H226 - 4;H332 - 4;H312 / 2;H315	[1][2]
<b>(Trimethoxysilylpropyl)ethylenediamine</b> CAS No: 0001760-24-3	1-2.5	/ 2;H315 / 2;H319 1;H317 - 3;H412	[1]
<b>Dibutyltin dilaurate</b> CAS No: 0000077-58-7	<1	- 4;H302 - 4;H312 / 2;H315 / 2;H319 - 3;H301 - 3;H373 - 1;H410 1;H360 1;H360 2;H341	[1]

1)

- 2)
- 3) PBT

가  
vPvB  
16

가 , 가  
가 .

**4.**

**4.1.**

가 .

가 , .

10 , .

**4.2.** 가 /

**4.3.**

**5.** ,

**5.1.**

; , , , .

Note; 가 .

가 .

**5.2.**

가 . :  
, , , .

**5.3.**

가  
가 .

6.

6.1.

가 가 가 , 가

6.2.

가 .

6.3.

.8

, , 가 . (13 .)

가 .

가 .

, 가 , 가 . ,

7.

7.1.

가 .  
, 가 (LEL) (OEL)

가 .

가 .  
, 가 (LEL) (OEL)

7.2. ( )

: , , .  
,8

가 , 가 .

가 , 61  
1

7.3. Specific end use(s)

가 .

Hot surfaces, Sparks,

가 ( 60% , )

8.

8.1.

(OEL)

(ACGIH)

(ACGIH)

ppm

mg/m<sup>3</sup>

ppm

mg/m<sup>3</sup>

Dibutyltin dilaurate

-

0.2

-

0.1

xylene

150

651

100

434

(P) (Peak exposure limit)

(R)

(Sk)

(Sen)

(Cat 1)

(Cat 2) 가

(Cat 3)

**DNEL/PNEC**

8.2.

가

가

(visor)

(overall)

가

가

.가

가

9.

pH

/ (°C)

(°C)

65

25

( = 1)

( , )

/

: 1.1 ( xylene )

: 6.6 ( xylene )

(Pa)

0.89

n-

/

(Log Kow)

9.2.

10.

10.1.

10.2.

.(Section 7 )

가

10.3.

가

10.4.

10.5.

.(7 .)

10.6.

가

11.

(OEL)

가

가

가

2

	LD50, mg/kg	LD50, mg/kg	LD50, mg/L/4hr	/ LD50, mg/L/4hr
(Trimethoxysilylpropyl)ethylenediamine - (1760-24-3)	7,684.00,			
Dibutyltin dilaurate - (77-58-7)	2,000.00,			
xylene - (1330-20-7)	4,299.00,	1,548.00,		20.00,

( )		
( )	4	
( )	4	
/	2	
/		
	1	
(1 )		
( )		

12.

12.1.

Dangerous Preparations Directive 1999/45/EC

가  
.( 3 )

가

	96 hr LC50 mg/l	49 hr EC50 mg/l	ErC50 mg/l
xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
(Trimethoxysilylpropyl)ethylenediamine - (1760-24-3)	597.00, Danio rerio	81.00, Daphnia magna	126.00 (72 hr), Scenedesmus subspicatus
Dibutyltin dilaurate - (77-58-7)	2.00, Leuciscus idus	0.66, Daphnia magna	

12.2.

가

12.3.

12.4.

12.5. , 가  
PBT ( ) vPvB ( )

12.6.

13.

13.1.

가

14.

14.1. 1263

14.2.

14.3.

1263, , 3, III, 3[Y]

IMDG Class/Div. 3

EmS F-E,S-E

ICAO/IATA 3

14.4. III

14.5.



IMDG :

14.6. 가

가

14.7. MARPOL73/78 Annex II IBC Code .

15.

None noted.

16.

This product complies with IMO Antifouling Systems Convention (AFS 2001).  
Foul Release Coating Type - Biocide-free.

SDS

Section 3 Phrases

H226

H312

H315

H319

H332

H336

H372

**This SDS is valid for 5 years from the revised date on page 1.**



Akzo Nobel

가