Safety Data Sheet INTERLAC 665 YELLOW Bulk Sales Reference No.: SDS Revision Date: SDS Revision Number:

CLB134 08/26/2015 A6

# X.International.

1. Identification of the preparation and company						
1.1. Product identifier						
Product Identity	INTERLAC 665 YELLOW					
Bulk Sales Reference Number CLB134						
1.2. Relevant identified uses of the substance or mixture and uses advised against						
Intended Use	See Technical Data Sheet.					
Application Method	See Technical Data Sheet.					
1.3. Details of the supplier of the safety data sheet						
Company Name	International Paint Ltda					
	ARGENTINA:					
	Ruta Panamericana Km 37,5					
	Garin, Buenos Aires PO Box: B1606DQE					
	AKZONOBEL CHILE:					
	Calle Limache 3363 Local 3, El Salto					
	Viña del Mar, Chile					
	C.P. 2520642 - Rut 76.048140-8					
	BRAZIL: Avenida Paiva, 999 - Neves					
	Sao Goncalo, RJ					
	24426-148 Brazil					
Emergency						
Suatrans Cotec	0800 7071 767 or 0800 7077 022 or 0800 172020 or					
	55*2*7500 (24 hr)					
International Paint	ARGENTINA:					
	+54 3327 44 7777					
	CHILE: +56 32 267 1174					
	BRAZIL:					
	+55 21 2199-7100					
Poison Control Center (Brazil)	0800-0148110 or +55 11 3069-8800					
Medical Service (Argentina)	+54 3327 44 7144 or +54 3327 44 7282					
Firefighter/HSE (Argentina)	+54 3327 44 7123					
Customer Service	ARGENTINA: +54 3327 44 7777 Fax: +54 3327 44 7738					
	CHILE: +56 32 267 1174 Fax: +56 32 263 1496					
	BRAZIL:					
	+55 21 2199-7100 Fax: +55 21 2199-7124					
2. Hazard identif	ication of the product					
2.1. Classification of the substance or mixture						

2.1. Classification of the substance or mixture Flam. Liq. 3;H226 Skin Irrit. 2;H315 Eye Dam. 1;H318 Skin Sens. 1;H317 Resp. Sens. 1;H334 Carc. 2;H351 Aquatic Chronic 3;H412

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled.

H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapours / spray.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %
Solvent naphtha (petroleum), medium aliphatic CAS Number: 0064742-88-7	25 - 50
Limestone CAS Number: 0001317-65-3	10 - 25
Isobenzofurandione CAS Number: 0000085-44-9	1.0 - 10
Pentaerythritol CAS Number: 0000115-77-5	1.0 - 10
Petroleum naphtha CAS Number: 0064742-95-6	1.0 - 10
Trimethyl benzene CAS Number: 0025551-13-7	1.0 - 10
	1.0 - 10

Titanium dioxide CAS Number: 0013463-67-7	
Distillates, petroleum CAS Number: 0068410-16-2	1.0 - 10
Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7	1.0 - 10
Methyl ethyl ketoxime CAS Number: 0000096-29-7	0.10 - 1.0

4. First aid measures					
4.1. Description of first aid measures					
General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.				
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.				
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.				
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.				
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.				
4.2. Most important syn	nptoms and effects, both acute and delayed				
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. May cause allergic respiratory reaction.				
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.				
Eyes	Causes severe eye irritation. Avoid contact with eyes.				
Skin	Causes skin irritation. May be harmful if absorbed through the skin.				
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.				
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.				
	5. Fire-fighting measures				
5.1. Extinguishing medi					
Appropriate Extinguishing Methods	Water in form of fog, Co2, foam or dry chemical dust.				
Inappropriate Extinguishing Methods	Direct water spray into fire				
Specific Hazards	Can liberate toxic fumes or gases during the burning. For decomposition see section 10.				
5.2. Special hazards ar	ising from the substance or mixture				
Special Methods	Evacuate the area and to fight the fire at a safe distance upwind. Use water in fog to cool containers near the fire. Keep runoff from entering sewer. Extinguishing water must be disposed according to local legislation.				
5.3. Advice for fire-fight					
Firefighter Protection	In fire case, to use personal respiratory device and suits for protection.				
	6. Accidental release measures				
6.1. Personal precautio	ns, protective equipment and emergency procedures				
Personal precautions	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material.				
Public Safety	Call Suatrans Cotec 0800 7071 767 or 0800 7077 022 or 0800 17 2020 or 55*2*7500 (24 hr) for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters. Stop leak if you can do so without risk. Prayant entry into watenyaye, sowers, basements or confined areas A				

without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry

#### CLB134 A6

earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

ւց սբ

Clean Up Method	Cover with sand or other non-cumbustible material. Transfer absorbed material with a non-sparking tool.
	7. Handling and storage

7.1. Precautions for safe handling

Handle the packages with care in order to avoid damage and spillage.

Be aware of the precautions referred to on the label.

Avoid contact with the eyes and the skin. Avoid swallowing of vapor and the pulverizations. Be aware of the precautions referred to on the label. Use personal protection equipment according to the section 8. No smoking, drinking or eating in the application areas.

All the ignition sources (hot surfaces, sparks, unprotected flames, etc.) must be excluded from the areas of manufacturing and application. The storage areas, the preparation and the application must be well ventilated. The product can be carried electrostatically. Always use grounding cables when transferring solvents or product. The operators must use adequate outfits which shall not develop static current. (at least 60% of natural fiber) and anti-static shoes.

Solvents based products: The solvent vapors are heavier than the air and can concentrate on the floor and explosive mixtures may be formed with the air .

Water based products: It does not require special cares for not being inflammable or explosive. Use only the indicated personal protection equipments.

7.2. Conditions for safe storage, including any incompatibilities Store between 40-100F (4-38C).

	8. Exposure controls and personal protection					
8.1. Control parameters						
	Exposure					
CAS No.	Ingredient	Source	Value			
0000085-44-9	Isobenzofurandione	ACGIH	1 ppm TWA			
		Brazil				
0000096-29-7	Methyl ethyl ketoxime	ACGIH				
		Brazil				
0000115-77-5	Pentaerythritol	ACGIH	10 mg/m3 TWA			
		Brazil				
0001317-65-3	Limestone	ACGIH				
		Brazil				
0001330-20-7	Xylenes (o-, m-, p- isomers)	ACGIH	100 ppm TWA150 ppm STEL			
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT			
0013463-67-7	Titanium dioxide	ACGIH	10 mg/m3 TWA			
		Brazil				
0025551-13-7	Trimethyl benzene	ACGIH	25 ppm TWA			
		Brazil				
0064742-88-7	Solvent naphtha (petroleum),	ACGIH				
	medium aliphatic	Brazil				
0064742-95-6	Petroleum naphtha	ACGIH				
		Brazil				
0068410-16-2	Distillates, petroleum	ACGIH				
		Brazil				

Health Data					
CAS No.	Ingredient	Source	Value		
0000085-44-9	Isobenzofurandione		Skin and respiratory irritation and sensitization eye irritation		
0000096-29-7	Methyl ethyl ketoxime	NIOSH			
0000115-77-5	Pentaerythritol	NIOSH	Physical irritation		

0001317-65-3	Limestone	NIOSH	Eye and skin irritation Physical irritation
0001330-20-7	Xylenes (o-, m-, p- isomers)		Central nervous system depressant; respiratory and eye irritation
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0025551-13-7	Trimethyl benzene	NIOSH	Skin irritation CNS depression
	Solvent naphtha (petroleum), medium aliphatic	NIOSH	
0064742-95-6	Petroleum naphtha	NIOSH	
0068410-16-2	Distillates, petroleum	NIOSH	

		1	urcinogen Data
CAS No.	Ingredient	Source	
0000085-44-9	Isobenzofurandione	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000096-29-7	Methyl ethyl ketoxime	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000115-77-5	Pentaerythritol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001317-65-3	Limestone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylenes (o-, m-, p-	OSHA	Select Carcinogen: No
	isomers)	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0025551-13-7	Trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-88-7	Solvent naphtha (petroleum), medium aliphatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068410-16-2	Distillates, petroleum	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory Protection Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's

	dia attana famina	Sector and a sector secto				
	directions for resp					
Eye and face protection		eyes. Protective equipment should be selected to provide posure to the chemicals listed in Section 8 of this document.				
	Depending on the site-specific conditions of use, safety glasses, chemical goggles,					
	ace protection may be required to prevent contact. The equipment					
Chip and hady	•	ly cleaned, or discarded after each use.				
Skin and body protection		nent should be selected to provide protection from exposure to the n Section 8 of this document. Depending on the site-specific				
P	conditions of use,	protective gloves, apron, boots, head and face protection may be				
		nt contact. The equipment must be thoroughly cleaned, or discarded				
	after each use.	· · · · · · · · · · · ·				
Engineering Controls	cross-ventilation.	of vapors by opening all windows and doors to achieve				
Special Precations	0,,,	ash fountains and safety showers should be available in the				
		r of any potential exposure. Use good personal hygiene practices. re eating, drinking, using toilet facilities, etc. Promptly remove soiled				
		to clothing thoroughly before reuse. Shower after work using plenty of				
	soap and water.	5 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5,				
	9. Pł	nysical and chemical properties				
Appearance		Yellow Liquid				
Odour threshold		Not Measured				
рН		No Established Limit				
Melting point / freezing		Not Measured				
Initial boiling point and	boiling range	142 (°C) 287.6 (°F)				
Flash Point		39 (°C) 102.2 (°F)				
Evaporation rate (Ethe	,	Not Measured				
Flammability (solid, gas		Not Applicable				
Upper/lower flammabil	ity or explosive limit	s Lower Explosive Limit: .7				
Vanaur prosoura (Pa)		Upper Explosive Limit: No Established Limit Not Measured				
Vapour pressure (Pa) Vapor Density		Heavier than air				
Specific Gravity		1.06				
Solubility in Water		Not Measured				
Partition coefficient n-octanol/water /l.o.g						
Kow)		Not Measured				
Auto-ignition temperatu	ure	Not Measured				
Decomposition temper	ature	Not Measured				
Viscosity (cSt)		No Established Limit Not Measured				
VOC %		Refer to the Technical Data Sheet or label where information is				
		available.				
		10. Stability and reactivity				
10.1. Reactivity		To: Orability and Podolivity				
•	ne or strong strong	acid to prevent probable exothermal reactions.				
10.2. Chemical stability	0 0					
This product is stable						
10.3. Possibility of hazardous reactions						
Dangerous Polymerization will not occur. Heat and vapors in excess can be generated when inproperly used.						
10.4. Conditions to avoid						
	Keep away from alkaline or strong strong acid to prevent probable exothermal reactions. Strong oxidizing agents					
10.5. Incompatible mat						
Strong oxidizing agents						
10.6 Hazardaus decomposition products						

10.6. Hazardous decomposition products

Can liberate toxic vapors in the welding process. The vapors can produce Dioxide and Monoxide of Carbon.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling

the contents may be harmful or fatal. No additional information provided for this product. See Sections 3 and 8 for chemical specific data.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	6,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available	
Limestone - (1317-65-3)	No data available	No data available	No data available	No data available	
Isobenzofurandione - (85-44-9)	1,530.00, Rat - Category: 4	10,000.00, Rabbit - Category: NA	No data available	No data available	
Pentaerythritol - (115-77-5)	19,500.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	No data available	
Petroleum naphtha - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available	
Trimethyl benzene - (25551-13-7)	No data available	No data available	No data available	No data available	
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA	
Distillates, petroleum - (68410-16-2)	No data available	No data available	No data available	No data available	
Xylenes (o-, m-, p- isomers) - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available	
Methyl ethyl ketoxime - (96-29-7)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available	

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.
Reproductive Toxicity		Not Applicable
Specific target organ systemic toxicity (single exposure)		Not Applicable
Specific target organ systemic Toxicity (repeated exposure)		Not Applicable
Aspiration hazard	Not Classified	Not Applicable

#### 12. Ecological information

#### 12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 199/45/CE and is classified according to the same as for the environment. For details, see sections 8 and 11. There are no data available on the product. Avoid contamination of drains or watercourses

Aquatic Ecotoxicity

Ingredient

	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	800.00, Pimephales promelas	100.00, Daphnia magna	450.00 (96 hr), Selenastrum capricornutum
Limestone - (1317-65-3)	Not Available	Not Available	Not Available
lsobenzofurandione - (85-44-9)	313.00, Leuciscus idus	Not Available	41.40 (96 hr), Pseudokirchneriella subcapitata
Pentaerythritol - (115-77-5)	5,000.00, Leuciscus idus	33,600.00, Daphnia magna	Not Available
Petroleum naphtha - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Trimethyl benzene - (25551-13-7)	Not Available	5.60, Palaemonetes pugio	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
Distillates, petroleum - (68410-16-2)	Not Available	Not Available	0.00 ( hr),
Xylenes (o-, m-, p- isomers) - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Methyl ethyl ketoxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus

12.2. Persistence and degradability No data available 12.3. Bioaccumulative potential Not Measured 12.4. Mobility in soil No data available 12.5. Results of PBT and vPvB assessment This product contains no PBT/vPvB chemicals. 12.6. Other adverse effects No data available 13. Disposal 13.1. Waste treatment methods

13. Disposal considerations

General	Note: Disposal must be in accordance with the federal, state and local regulations.
Method of treatment and disposal	Product: The treatment and the disposal of the product must in accordance the local legislation.
·	Remaining portions of the product: Residues that will not be used must be discarded in accordance the local legislation. Used packing: Do not reuse the packing. Recycle if appropriate or discard in accordance the local legislation.
	14. Transport information

14.1. UN number

UN 1263 CONSUMER COMMODITY, ORM-D

14.2. UN proper shipping name 14.3. Transport hazard class(es)

Domestic Surface Transportation		IMO / IMDG (Ocean Transportation)	
Proper Shipping Name	CONSUMER COMMODITY, ORM-D	IMDG Proper Shipping Name	Paint
Hazard Class	NR	IMDG Hazard Class	Flammable Liquid, 3
UN / NA Number	UN 1263	UN / NA Number	UN 1263
Packaging Group	Not Regulated	IMDG Packing Group III	
CERCLA/DOT RQ	NA gal. / NA lbs.	System Reference Code	181

Risk Numbe	er 30	EMS Marine Pollutant No
Air Transport (IC)	AO-ITI / IATA-DGR)	
Proper Ship Name	ping CONSUMER COMMODITY, ORM-D	
Hazard Clas	ss NR	
UN / NA Nu	mber UN 1263	
Packaging (	Group Not Regulated	
14.4. Packing group	Ш	
14.5. Environmental ha	zards	
IMDG Marine	e Pollutant: No	
14.6. Special precautio	ns for user	
Not Ap	oplicable	
14.7. Transport in bulk	according to Annex II of MA	ARPOL73/78 and the IBC Code
Not Ap	oplicable	
	15. Regi	ulatory information
Regulatory Overview	Products at Work. Act # 96.044 of 18/05/88. Decreto 1.797, of 25/01/19 Resolution ANTT # 420, o of Road Transport of Haza Decreto 3214 of MTE NBR 7500: Identification f storage of products. NBR 7501: Terminology NBR 7503: Road transpor Features, dimensions and NBR 9735: Set of equipm Products Procedures.	for the road transport, the handling, the moving and the Transport of Hazardous Products. rt of hazardous products emergency form and envelope
WHMIS Classification	B3 D2A E	

16. Other information

The information contained in this Material Safety Data Sheet (MSDS) has the purpose of being a description of the product safety requirements, which were obtained from the literature and current legislation specific about raw materials/ingredients. Thus, the accuracy of the data contained herein is not, expressly or implicitly, assured by the Manufacturer. The product shall not be used for purposes other than the ones specified by the Manufacturer. The user is always liable for taking all required measures to comply with the provisions in this MSDS, as well as with the requirements expressed in the regulations and effective legislation.

Bibliographic references:

- Council Directive 67/548/EEC of June 27, 1967.

- Work and Job department clause # 3.214 of June 08, 1978.

- ABNT NBR 14725 (parts I,II,III and IV) Chemical products Information on safety, health and environment.

Specific use: product meant only for professional use, check the product data sheet.

CAS: Chemical Abstract Service register number It s a register number indicated by the American Chemical Society, which identifies only a specific chemical component.

CLB134\_A6

End of Document



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : www.yachtpaint.com , www.international-marine.com, www.international-pc.com