

SAFETY DATA SHEET

INTERFINE 878 ULTRA DEEP BASE

Section 1. Identification

INTERFINE 878 ULTRA DEEP BASE : GHS product identifier
SZA100 : Product code

Identified uses	
Professional application of coatings and inks	
Uses advised against	Reason
All Other Uses	

International Farg AB : **Supplier's details**
 Holmedalen 3
 Aspereds Industriområde
 SE-424 22 Angered
 Sweden

Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530

+46 8 33 12 31 : **Emergency telephone number (with hours of operation)**

+966 55 388 0087 : **National advisory body/ Poison Centre (For use only by licensed medical professionals.)**

sdsfellinguk@akzonobel.com : **e-mail address of person responsible for this SDS**

Section 2. Hazards identification

FLAMMABLE LIQUIDS - Category 3 : **Classification of the substance or mixture**
 SKIN CORROSION/IRRITATION - Category 2
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
 SKIN SENSITIZATION - Category 1

GHS label elements



: **Hazard pictograms**

Warning : **Signal word**
 Flammable liquid and vapour. : **Hazard statements**
 Causes serious eye irritation.
 Causes skin irritation.
 May cause an allergic skin reaction.

Precautionary statements

Section 2. Hazards identification

Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Avoid breathing vapour. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. : **Prevention**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. : **Response**

Store in a well-ventilated place. Keep cool. : **Storage**

Dispose of contents and container in accordance with all local, regional, national and international regulations. : **Disposal**

Wear appropriate respirator when ventilation is inadequate. : **Supplemental label elements**

None known. : **Other hazards which do not result in classification**

Section 3. Composition/information on ingredients

Mixture : **Substance/mixture**

Classification	CAS number	% by weight	Ingredient name
Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	13048-33-4	≥10 - ≤22	hexamethylene diacrylate
Flam. Liq. 2, H225 Acute Tox. 5, H303 Skin Irrit. 3, H316 Eye Irrit. 2A, H319 STOT SE 3, H336	67-63-0	≤5	Isopropyl alcohol
Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304	1330-20-7	≤5	xylene
Flam. Liq. 3, H226 Acute Tox. 5, H313	108-65-6	≤3	2-methoxy-1-methylethyl acetate
Skin Sens. 1, H317 Aquatic Chronic 4, H413	911674-82-3	≤2.7	Amides, castor-oil, hydrogenated, N,N'-[1,3-phenylene-bis(methylene)] bis-

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. : **Eye contact**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. : **Inhalation**

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. : **Skin contact**

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. : **Ingestion**

Most important symptoms/effects, acute and delayed

Potential acute health effects

Causes serious eye irritation. : **Eye contact**

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. : **Inhalation**

Causes skin irritation. May cause an allergic skin reaction. : **Skin contact**

Irritating to mouth, throat and stomach. : **Ingestion**

Over-exposure signs/symptoms

Adverse symptoms may include the following:
pain or irritation
watering
redness : **Eye contact**

Adverse symptoms may include the following:
headache
drowsiness/fatigue
dizziness/vertigo
muscle weakness
unconsciousness : **Inhalation**

Adverse symptoms may include the following:
irritation
redness : **Skin contact**

No specific data. : **Ingestion**

Indication of immediate medical attention and special treatment needed, if necessary

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. : **Notes to physician**

No specific treatment. : **Specific treatments**

Section 4. First aid measures

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. **: Protection of first-aiders**

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Use dry chemical, CO₂, water spray (fog) or foam. **: Suitable extinguishing media**

Do not use water jet. **: Unsuitable extinguishing media**

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. **: Specific hazards arising from the chemical**

Decomposition products may include the following materials: **: Hazardous thermal decomposition products**
 carbon dioxide
 carbon monoxide
 nitrogen oxides
 sulfur oxides
 metal oxide/oxides

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. **: Special protective actions for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. **: Special protective equipment for fire-fighters**

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. **: For non-emergency personnel**

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". **: For emergency responders**

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). **: Environmental precautions**

Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. **: Small spill**

Section 6. Accidental release measures

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

: Large spill

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

: Protective measures

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

: Advice on general occupational hygiene

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

: Conditions for safe storage, including any incompatibilities

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Exposure limits	Ingredient name
ACGIH TLV (United States, 3/2015). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.	Isopropyl alcohol
ACGIH TLV (United States, 3/2015). STEL: 651 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 434 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.	xylene

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

: Appropriate engineering controls

Section 8. Exposure controls/personal protection

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. : **Environmental exposure controls**

Individual protection measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. : **Hygiene measures**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. : **Eye/face protection**

Skin protection

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. : **Hand protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. : **Body protection**

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. : **Other skin protection**

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. : **Respiratory protection**

Section 9. Physical and chemical properties

Appearance

Liquid.	: Physical state
Various	: Colour
Solvent.	: Odour
Not available.	: Odour threshold
Not applicable.	: pH
Not available.	: Melting point
Not available.	: Boiling point
Closed cup: 35°C (95°F)	: Flash point

Section 9. Physical and chemical properties

Not available.	: Evaporation rate
Not available.	: Flammability (solid, gas)
Not available.	: Lower and upper explosive (flammable) limits
Not available.	: Vapour pressure
Not available.	: Vapour density
1.44	: Relative density
Insoluble in the following materials: cold water.	: Solubility
Not available.	: Partition coefficient: n-octanol/water
Not available.	: Auto-ignition temperature
Not available.	: Decomposition temperature
Kinematic (room temperature): 121 mm ² /s (121 cSt)	: Viscosity

Section 10. Stability and reactivity

No specific test data related to reactivity available for this product or its ingredients.	: Reactivity
The product is stable.	: Chemical stability
Under normal conditions of storage and use, hazardous reactions will not occur.	: Possibility of hazardous reactions
Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.	: Conditions to avoid
Reactive or incompatible with the following materials: oxidizing materials	: Incompatible materials
Under normal conditions of storage and use, hazardous decomposition products should not be produced.	: Hazardous decomposition products

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Exposure	Dose	Species	Result	Product/ingredient name
-	5 g/kg	Rat	LD50 Oral	hexamethylene diacrylate
-	12800 mg/kg	Rabbit	LD50 Dermal	Isopropyl alcohol
-	5000 mg/kg	Rat	LD50 Oral	xylene 2-methoxy-1-methylethyl acetate
-	4300 mg/kg	Rat	LD50 Oral	
-	5000 mg/kg	Rabbit	LD50 Dermal	
-	8532 mg/kg	Rat	LD50 Oral	

Irritation/Corrosion

Section 11. Toxicological information

Observation	Exposure	Score	Species	Result	Product/ingredient name
-	24 hours 500 milligrams	-	Rabbit	Skin - Severe irritant	hexamethylene diacrylate
-	24 hours 100 milligrams	-	Rabbit	Eyes - Moderate irritant	Isopropyl alcohol
-	10 milligrams	-	Rabbit	Eyes - Moderate irritant	
-	100 milligrams	-	Rabbit	Eyes - Severe irritant	
-	500 milligrams	-	Rabbit	Skin - Mild irritant	

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Target organs	Route of exposure	Category	Name
Narcotic effects	Not applicable.	Category 3	Isopropyl alcohol
Respiratory tract irritation	Not applicable.	Category 3	xylene

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Result	Name
ASPIRATION HAZARD - Category 1	xylene

Not available.

: Information on likely routes of exposure

Potential acute health effects

Causes serious eye irritation.

: Eye contact

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

: Inhalation

Causes skin irritation. May cause an allergic skin reaction.

: Skin contact

Irritating to mouth, throat and stomach.

: Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Adverse symptoms may include the following:

: Eye contact

pain or irritation

watering

redness

Section 11. Toxicological information

Adverse symptoms may include the following:

headache
drowsiness/fatigue
dizziness/vertigo
muscle weakness
unconsciousness

: Inhalation

Adverse symptoms may include the following:

irritation
redness

: Skin contact

No specific data.

: Ingestion

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Not available.

: Potential immediate effects

Not available.

: Potential delayed effects

Long term exposure

Not available.

: Potential immediate effects

Not available.

: Potential delayed effects

Potential chronic health effects

Not available.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

: General

No known significant effects or critical hazards.

: Carcinogenicity

No known significant effects or critical hazards.

: Mutagenicity

No known significant effects or critical hazards.

: Teratogenicity

No known significant effects or critical hazards.

: Developmental effects

No known significant effects or critical hazards.

: Fertility effects

Numerical measures of toxicity

Acute toxicity estimates

ATE value	Route
120453.6 mg/kg	Oral
27314.6 mg/kg	Dermal
305.3 mg/l	Inhalation (vapours)

Section 12. Ecological information

Toxicity

Exposure	Species	Result	Product/ingredient name
48 hours	Crustaceans - Crangon crangon	Acute LC50 1400000 to 1950000 µg/l Marine water	Isopropyl alcohol
96 hours	Fish - Gambusia affinis	Acute LC50 1400000 µg/l	xylene
48 hours	Crustaceans - Palaemonetes pugio	Acute LC50 8500 µg/l Marine water	
96 hours	Fish - Pimephales promelas	Acute LC50 13400 µg/l Fresh water	2-methoxy-1-methylethyl acetate
96 hours	Fish	Acute LC50 134 mg/l Fresh water	

Section 12. Ecological information

Persistence and degradability

Not available.

Bioaccumulative potential

Potential	BCF	LogP _{ow}	Product/ingredient name
low	-	2.81	hexamethylene diacrylate
low	-	0.05	Isopropyl alcohol
low	8.1 to 25.9	3.12	xylene
low	-	1.2	2-methoxy-1-methylethyl acetate

Mobility in soil

Not available.

: Soil/water partition coefficient (K_{oc})

No known significant effects or critical hazards.

: Other adverse effects

Section 13. Disposal considerations

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

: Disposal methods

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

IATA	IMDG	UN	
UN1263	UN1263	UN1263	UN number
PAINT	PAINT	PAINT	UN proper shipping name
3 	3 	3 	Transport hazard class(es)
III	III	III	Packing group
No.	No.	No.	Environmental hazards
-	-	-	Additional information

Not applicable.

: IMDG Code Segregation group

Section 14. Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. : **Special precautions for user**

Not available. : **Transport in bulk according to Annex II of Marpol and the IBC Code**

Section 15. Regulatory information

No known specific national and/or regional regulations applicable to this product (including its ingredients). : **Safety, health and environmental regulations specific for the product**

Section 16. Other information

Justification

Justification	Classification
On basis of test data	Flam. Liq. 3, H226
Calculation method	Skin Irrit. 2, H315
Calculation method	Eye Irrit. 2A, H319
Calculation method	Skin Sens. 1, H317

History

30/05/2017 : **Date of printing**
 30/05/2017 : **Date of issue/Date of revision**
 16/06/2016 : **Date of previous issue**
 3 : **Version**
 : **Key to abbreviations**

ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 UN = United Nations

Not available. : **References**

Indicates information that has changed from previously issued version.

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out

Section 16. Other information

of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel