

KRA852_A1

Material Safety Data Sheet INTERBOND 808 CINZA

Sales
Order: {SalesOrd}
KRA852
17/12/2010
A1-2

Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:



1. Identification of the preparation and company

Product Identity INTERBOND 808 CINZA
Bulk Sales Reference No. KRA852
Company Name International Paint LLC
6001 Antoine Drive
Houston, Texas 77091

Emergency
CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product



Warning

GHS Classification:

Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	2	Causes skin irritation
Eye damage/irritation	2A	Causes serious eye irritation
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	central nerve system, kidneys, liver, respiratory system
	2	central nerve system
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	central nerve system, lung, respiratory system, systemic toxicity
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects

KRA852_A1

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

- S1: Keep locked up.
- S23: Do not breathe vapor/spray.
- S24: Avoid contact with skin.
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S27: Take off immediately all contaminated clothing.
- S28: After contact with skin, wash immediately with plenty of soap and water.
- S37: Wear suitable gloves.
- S39: Wear eye/face protection.
- S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- S51: Use only in well-ventilated areas.
- S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.
- S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.
HMIS Rating	Health: 3* Flammability: 3 Reactivity: 0 PPE: X

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Benzene, ethyl-	0000100-41-4	1.0 - 10
Methylisobutyl ketone	0000108-10-1	1.0 - 10
Xylenes (o-, m-, p- isomers)	0001330-20-7	1.0 - 10
Glycidoxypropyltrimethoxysilane	0002530-83-8	1.0 - 10
Barium sulfate	0007727-43-7	25 - 50
Titanium dioxide	0013463-67-7	1.0 - 10
Bisphenol A - Epichlorohydrin polymer	0025068-38-6	10 - 25
Aromatic hydrocarbon resin	0068410-16-2	1.0 - 10
Talc (*non-asbestiform)	14807-96-6*	10 - 25

4. First aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

KRA852_A1

Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Flash Point	F: 90 C: 32
Lower Explosive Limit (LEL)	1 (%vol in air) at Normal Atmospheric Temp and Pressure
ERG Guide No.	127

6. Accidental release measures

Spill Response Procedures	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.
Public Safety	CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).
ERG Guide No.	127

7. Handling and storage

Storage Temperature	Store between 32 and 120 F
Handling and Storage Precautions	Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection
--

CAS No.	Ingredient	Exposure	
		Source	Value
0000100-41-4	Benzene, ethyl-	OSHA	100 ppm TWA; 435 mg/m ³ TWA125 ppm STEL; 545 mg/m ³ STEL
		ACGIH	100 ppm TWA125 ppm STEL
		NIOSH	100 ppm TWA; 435 mg/m ³ TWA125 ppm STEL; 545 mg/m ³ STEL800 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWAEV; 435 mg/m ³ TWAEV125 ppm STEV; 540 mg/m ³ STEV
		Mexico	100 ppm TWA; 435 mg/m ³ TWA125 ppm STEL; 545 mg/m ³ STEL
		Brazil	78 ppm TWA; 340 mg/m ³ TWA
0000108-10-1	Methylisobutyl ketone	OSHA	100 ppm TWA; 410 mg/m ³ TWA75 ppm STEL; 300 mg/m ³ STEL
		ACGIH	50 ppm TWA75 ppm STEL

KRA852_A1

		NIOSH	50 ppm TWA; 205 mg/m3 TWA75 ppm STEL; 300 mg/m3 STEL500 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	50 ppm TWAEV; 205 mg/m3 TWAEV75 ppm STEV
		Mexico	50 ppm TWA; 205 mg/m3 TWA75 ppm STEL; 307 mg/m3 STEL
		Brazil	No Established Limit
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWAEV; 435 mg/m3 TWAEV150 ppm STEV; 650 mg/m3 STEV
		Mexico	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		Brazil	78 ppm TWA; 340 mg/m3 TWA
0002530-83-8	Glycidoxypropyltrimethoxysilane	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWAEV (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWAEV (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
0025068-38-6	Bisphenol A – Epichlorohydrin polymer	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0068410-16-2	Aromatic hydrocarbon resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit

KRA852_A1

14807-96-6*	Talc (*non-asbestiform)	Brazil	No Established Limit
		OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000100-41-4	Benzene, ethyl-	NIOSH	Eye skin
0000108-10-1	Methylisobutyl ketone	NIOSH	Irritation liver
0001330-20-7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant; respiratory and eye irritation
0002530-83-8	Glycidoxypropyltrimethoxysilane	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0025068-38-6	Bisphenol A - Epichlorohydrin polymer	NIOSH	No Established Limit
0068410-16-2	Aromatic hydrocarbon resin	NIOSH	No Established Limit
14807-96-6*	Talc (*non-asbestiform)	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000100-41-4	Benzene, ethyl-	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000108-10-1	Methylisobutyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0002530-83-8	Glycidoxypropyltrimethoxysilane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0025068-38-6	Bisphenol A - Epichlorohydrin polymer	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068410-16-2	Aromatic hydrocarbon resin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
14807-96-6*	Talc (*non-asbestiform)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

KRA852_A1

		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
--	--	------	--

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State	Liquid Coloured
pH	Not Determined
Specific Gravity	1.77
Boiling Point F	175
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether

10. Stability and reactivity

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Benzene, ethyl- - (0000100-41-4)	3,500.00, Rat - Category: 5	15,354.00, Rabbit - Category: NA	17.20, Rat - Category: 4
Methylisobutyl ketone - (0000108-10-1)	2,080.00, Rat - Category: 5	16,000.00, Rabbit - Category: NA	8.20, Rat - Category: 3
Xylenes (o-, m-, p- isomers) - (0001330-20-7)			

KRA852_A1

	4,300.00, Rat – Category: 5	1,700.00, Rabbit – Category: 4	29.08, rat – Category: NA
Glycidoxypropyltrimethoxysilane – (0002530–83–8)	-----	-----	-----
Barium sulfate – (0007727–43–7)	-----	-----	-----
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA
Bisphenol A – Epichlorohydrin polymer – (0025068–38–6)	11,400.00, Rat – Category: NA	-----	-----
Aromatic hydrocarbon resin – (0068410–16–2)	-----	-----	-----
Talc (*non-asbestiform) – (14807–96–6*)	-----	-----	-----

General NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined
No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3	IMDG Hazard Class	3 – Flammable and Combustible liquid
UN / NA Number	UN 1263	UN / NA Number	UN 1263
DOT Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	82 gal. / 1207 lbs.	System Reference Code	1

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2; D1B; D2B

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

- Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)
- Methylisobutyl ketone (5000 lb final RQ; 2270 kg final RQ)
- Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

- Benzene, ethyl-
- Methylisobutyl ketone
- Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

Barium sulfate
Benzene, ethyl-
Methylisobutyl ketone
Titanium dioxide
Xylenes (o-, m-, p- isomers)

Mass Extraordinarily Haz Sub (>.01%) :
(No Product Ingredients Listed)

Penn RTK Substances (>1%) :

Barium sulfate
Benzene, ethyl-
Methylisobutyl ketone
Titanium dioxide
Xylenes (o-, m-, p- isomers)

Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%) :

Benzene, ethyl-
Methylisobutyl ketone
Titanium dioxide
Xylenes (o-, m-, p- isomers)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Benzene, ethyl-
Methylisobutyl ketone
Titanium dioxide
Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%) :

Benzene, ethyl-
Methylisobutyl ketone
Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

Benzene, ethyl-
Methylisobutyl ketone
Xylenes (o-, m-, p- isomers)

Proposition 65 – Carcinogens (>0%):

Benzene, ethyl-
Naphthalene
Nickel

Proposition 65 – Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):

(No Product Ingredients Listed)

Risk Phrases:

R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be

KRA852_A1

caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.