In accordance with the Standard for Classification and Labelling of Chemical Substance and Material Safety Data Sheet, Article 10 Paragraph

SAFETY DATA SHEET

INTERFINE 878 PART B

Section 1. Chemical product and company identification

A. Product name : INTERFINE 878 PART B

Product code : SZA076

B. <u>Relevant identified uses of the substance or mixture and uses advised against</u>

Identified uses		
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

C. Manufacturer	: International Farg AB Holmedalen 3 Aspereds Industriomrade SE-424 22 Angered Sweden
	Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530
Emergency telephone number (with hours of operation)	: +46 8 33 12 31
e-mail address of person responsible for this SDS	: sdsfellinguk@akzonobel.com

Section 2. Hazards identification

- A. Hazard classification : FLAMMABLE LIQUIDS Category 3 SKIN CORROSION/IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
- B. <u>GHS label elements, including precautionary statements</u> Symbol :



Signal word	: Danger
Hazard statements	: Flammable liquid and vapour. Causes severe skin burns and eye damage.
Drace ution on a statements	

Precautionary statements

Prevention

: Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all materialhandling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wash hands thoroughly after handling.



Section 2. Hazards identification

Response	 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Wear appropriate respirator when ventilation is inadequate.
C. Other hazards which do	: None known.

C. Other hazards which do : None known not result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	Common name	CAS number	%	Classification
3-aminopropyltriethoxysilane	3-aminopropyltriethoxysilane	919-30-2	≥70 - <80	Acute Tox. 4, H302 Skin Corr. 1, H314 Eye Dam. 1, H318
3-(trimethoxysilyl)propylamine	1-Propanamine, 3- (trimethoxysilyl)-	13822-56-5	≥20 - <30	Skin Irrit. 2, H315 Eye Dam. 1, H318
dioctyltin di(acetate)	STANNANE, BIS (ACETYLOXY)DIOCTYL-	17586-94-6	≥1 - <5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 2, H371 (immune system) (oral)

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Α.	Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
в.	Skin contact	: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

2/11

:



X.International.

Section 4. First aid measures

C.	Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
D.	Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Е.	Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
	Specific treatments	:	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures A. Extinguishing media Suitable extinguishing : Use dry chemical, CO₂, water spray (fog) or foam. media Unsuitable : Do not use water jet. extinguishing media B. Specific hazards arising : Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur from the chemical and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Hazardous thermal : Decomposition products may include the following materials: decomposition products carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides C. Special protective : Fire-fighters should wear appropriate protective equipment and self-contained equipment for firebreathing apparatus (SCBA) with a full face-piece operated in positive pressure fighters mode.

1



Section 5. Firefighting measures

Special precautions for	: Promptly isolate the scene by removing all persons from the vicinity of the incident if
fire-fighters	there is a fire. No action shall be taken involving any personal risk or without
	suitable training. Move containers from fire area if this can be done without risk.
	Use water spray to keep fire-exposed containers cool.

Section 6. Accidental release measures

Α.	Personal precautions,	:	No action shall be taken involving any personal risk or without suitable training.
	protective equipment		Evacuate surrounding areas. Keep unnecessary and unprotected personnel from
	and emergency		entering. Do not touch or walk through spilt material. Shut off all ignition sources.
	procedures		No flares, smoking or flames in hazard area. Do not breathe vapour or mist.
	•		Provide adequate ventilation. Wear appropriate respirator when ventilation is
			inadequate. Put on appropriate personal protective equipment.

B. Environmental precautions
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

C. Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an
	appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

A. Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

:

Section 7. Handling and storage

В.	Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
----	--	---	--

Section 8. Exposure controls/personal protection

A. <u>Control parameters</u>

Occupational exposure limits

Ingredient name	Exposure limits
	Ministry of Labor (Republic of Korea, 8/2013). Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours.

B. Appropriate engineering controls
 Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
 Environmental
 Emissions from ventilation or work process equipment should be checked to ensure

exposure controls Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Hand protection	: Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

•



K.International.

Section 8. Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

Α.	<u>Appearance</u>		
	Physical state	:	Liquid.
	Colour	:	Colourless.
В.	Odour	:	Odourless.
C.	Odour threshold	:	Not available.
D.	рН	:	Not applicable.
Ε.	Melting/freezing point	:	Not available.
F.	Boiling point/boiling range	:	Lowest known value: 194°C (381.2°F) (3-(trimethoxysilyl)propylamine).
G.	Flash point	:	Closed cup: 57°C (134.6°F)
	Fire point	1	Not available.
Н.	Evaporation rate	:	Not available.
I.	Flammability (solid, gas)	:	Not available.
J.	Lower and upper explosive (flammable) limits	:	Not available.
K.	Vapour pressure	:	Not available.
L.	Solubility	:	Insoluble in the following materials: cold water.
М.	Vapour density	:	Not available.
N.	Relative density	:	0.97
0.	Partition coefficient: n- octanol/water	:	Not available.
Ρ.	Auto-ignition temperature	:	Not available.
Q.	Decomposition temperature	:	Not available.
R.	Viscosity	:	Kinematic (room temperature): 10 mm ² /s (10 cSt)
S.	Molecular weight	:	Not applicable.

Section 10. Stability and reactivity

Α.	Chemical stability	:	The product is stable.
	Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
_			

B. Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

:



X.International.

Section 10. Stability and reactivity

- **C. Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials
- D. Hazardous decomposition products
 C. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

A. Information on likely : Not available.

routes of exposure

Potential acute health effects

Inhalation	: May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	: May cause burns to mouth, throat and stomach.
Skin contact	: Causes severe burns.

Eye contact : Causes serious eye damage.

Over-exposure signs/symptoms

Inhalation	: No specific data.
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-aminopropyltriethoxysilane	LD50 Dermal	Rabbit	4.29 g/kg	-
	LD50 Oral	Rat	1.57 g/kg	-
dioctyltin di(acetate)	LD50 Oral	Rat	154 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
3-aminopropyltriethoxysilane	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 750	-
	Skin - Severe irritant	Rabbit	-	Micrograms 24 hours 5 milligrams	-

Sensitisation

Not available.

CMR - ISHA Article 42 Public Notice No 2013-38 Occupational Exposure Limits

Not available.

Mutagenicity

:

Not available.

Section 11. Toxicological information

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
dioctyltin di(acetate)	Category 2	Oral	immune system

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

Chronic toxicity

Not available.

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

ATE value

Route	Result
Oral	2238.2 mg/kg
Dermal	6115.9 mg/kg

Section 12. Ecological information

A. Ecotoxicity

Not available.

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminopropyltriethoxysilane 3-(trimethoxysilyl) propylamine	1.7 0.2		low low

D. Mobility in soil

:

K.International.

Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Α.	Disposal methods	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
В.	Disposal precautions	:	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the

soil, waterways, drains and sewers.

container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
A. UN number	UN3470	UN3470	UN3470
B. UN proper shipping name	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE
C. Transport hazard class(es)	8 (3)	8 (3)	8 (3)
D. Packing group	II	II	II
E. Environmental hazards	No.	No.	No.
F. Additional information	-	-	-

IMDG Code Segregation : Not applicable. group

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

:

Section 15. Regulatory information

Α.	Regulation according to I	SH			
	ISHA article 37 (Harmful substances prohibited from manufacture)	:	None of the components are listed.		
	ISHA article 38 (Harmful substances requiring permission)	:	None of the components are listed.		
	Article 2 of Youth Protection Act on Substances Hazardous to Youth	:	Not applicable.		
	Exposure Limits of Chem	ica	al Substances and Physical Factors		
	The following components have an OEL: Dioctyltin di(acetate)				
	ISHA Enforcement Regs Annex 11-3 (Exposure standards established for harmful factors)	:	None of the components are listed.		
	Annex 11-4 (Harmful factors subject to Work Environment Measurement)		The following components are listed: Organic compounds of tin		
	ISHA Enforcement Regs Annex 12-2 (Harmful Factors Subject to Special Health Check- up)	:	The following components are listed: Tin and compounds		
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	The following components are listed: Tin and its compounds		
В.	Regulation according to (Ch	emicals Control Act		
	K-Reach Article 20 (Toxic chemicals)	:	Not applicable		
	K-Reach Article 27 (Prohibited)	:	None of the components are listed.		
	K-Reach Article 27 (Restricted)	:	None of the components are listed.		
	CSCA Article 11 (TRI)	:	The following components are listed: Tin and its compounds		
	Korea inventory	:	Not determined.		
	CSCA Article 39 (Accident Precaution Chemicals)	:	None of the components are listed.		
C.	Dangerous Materials Safety Management Act	:	Class: Class 4 - Flammable Liquid Item: 4. Class 2 petroleums - Water-insoluble liquid Threshold: 1000 L Danger category: III Signal word: Contact with sources of ignition prohibited		
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.		

:





Section 15. Regulatory information

Ε.	. <u>Regulation according to other foreign laws</u>		
	Europe inventory	:	All components are listed or exempted.
	United States inventory (TSCA 8b)	:	All components are listed or exempted.
	Japan inventory	:	Japan inventory (ENCS): All components are listed or exempted. Japan inventory (ISHL): Not determined.

Section 16. Other information

Α.	References	:	Not available.
В.	Date of issue/Date of revision	:	30/05/2017
C.	Version	:	3
	Date of printing	:	30/05/2017

D. Other

V Indicates information that has changed from previously issued version.

Key to abbreviations	: ATE = Acute Toxicity Estimate
-	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	UN = United Nations

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel