

# KRA855\_A1

## Safety Data Sheet INTERBOND 808 PART B

Sales  
Order: {SalesOrd}  
KRA855  
01/13/2017  
A1-3

Bulk Sales Reference No.:  
SDS Revision Date:  
SDS Revision Number:



### 1. Identification of the preparation and company

#### 1.1. Product identifier

Product Identity INTERBOND 808 PART B  
Bulk Sales Reference No. KRA855

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.  
Application Method See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC  
6001 Antoine Drive  
Houston, Texas 77091

#### Emergency

CHEMTREC (USA) (800) 424-9300  
International Paint (713) 682-1711  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Acute Tox. 5;H303	May be harmful if swallowed.
Acute Tox. 5;H313	May be harmful in contact with skin.
Acute Tox. 4;H332	Harmful if inhaled.
Skin Corr. 1B;H314	Causes severe skin burns and eye damage.
Eye Dam. 1;H318	Causes serious eye damage.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Aquatic Acute 1;H400	Very toxic to aquatic life.
Aquatic Chronic 3;H412	Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.  
H303 May be harmful if swallowed.

H313 May be harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H332 Harmful if inhaled.  
 H400 Very toxic to aquatic life.  
 H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.  
 P235 Keep cool.  
 P240 Ground / bond container and receiving equipment.  
 P241 Use explosion-proof electrical / ventilating / light / equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe mist / vapors / spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves / eye protection / face protection.  
 P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P302+352 IF ON SKIN: Wash with soap and water.  
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
 P310 Immediately call a POISON CENTER or doctor / physician.  
 P312 Call a POISON CENTER or doctor / physician if you feel unwell.  
 P333+313 If skin irritation or a rash occurs: Get medical advice/attention.  
 P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P363 Wash contaminated clothing before reuse.  
 P370 In case of fire: Use water spray, fog, or regular foam..  
 P391 Collect spillage.  
 P403+233 Store in a well ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating            Health: 3            Flammability: 2            Reactivity: 0

3. Composition/information on ingredients
---

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Benzyl alcohol CAS Number: 0000100-51-6	10 - 25	Acute Tox. 4;H332 Acute Tox. 4;H302	[1]
Isophorone diamine CAS Number: 0002855-13-2	10 - 25	Acute Tox. 4;H312 Acute Tox. 4;H302 Skin Corr. 1B;H314 Skin Sens. 1;H317 Aquatic Chronic 3;H412	[1]
Amines, N-tallow alkyltrimethylenedi-, oleates CAS Number: 0061791-53-5	10 - 25	Aquatic Acute 1;H400	[1]
m-Xylene-alpha, alpha'-diamine CAS Number: 0001477-55-0	10 - 25	Acute Tox. 4;H302 Acute Tox. 3;H331 Skin Corr. 1;H314 Skin Sens. 1;H317 Aquatic Chronic	[1][2]

## KRA855\_A1

		3;H412	
Methylisobutyl ketone CAS Number: 0000108-10-1	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335	[1][2]
2,4,6-Tri(dimethylaminomethyl)phenol CAS Number: 0000090-72-2	1.0 - 10	Acute Tox. 4;H302 Eye Irrit. 2;H319 Skin Irrit. 2;H315	[1]
Bis(dimethylamino)methylphenol CAS Number: 0071074-89-0	1.0 - 10	Skin Corr. 1;H314	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

#### 4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

#### 5.2. Special hazards arising from the substance or mixture

FLAMMABLE/COMBUSTIBLE MATERIALS: May be ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 127

## 6. Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. Fully Encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.

## 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

## 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 100 meters (330 feet).

## 7. Handling and storage

## 7.1. Precautions for safe handling

## Handling

Vapors may cause flash fire or ignite explosively.

## In Storage

Keep away from heat, sparks and flame.

## 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

## 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

## 8. Exposure controls and personal protection

## 8.1. Control parameters

## Exposure

CAS No.	Ingredient	Source	Value
0000090-72-2	2,4,6-Tri(dimethylaminomethyl)phenol	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0000100-51-6	Benzyl alcohol	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	

KRA855\_A1

0000108-10-1	Methylisobutyl ketone	OSHA	100 ppm TWA; 410 mg/m3 TWA75 ppm STEL; 300 mg/m3 STEL
		ACGIH	20 ppm TWA75 ppm STEL
		NIOSH	50 ppm TWA; 205 mg/m3 TWA75 ppm STEL; 300 mg/m3 STEL500 ppm IDLH
		Supplier	
		OHSA, CAN	20 ppm TWA75 ppm STEL
		Mexico	50 ppm TWA LMPE-PPT; 205 mg/m3 TWA LMPE-PPT75 ppm STEL [LMPE-CT]; 307 mg/m3 STEL [LMPE-CT]
		Brazil	
0001477-55-0	m-Xylene-alpha, alpha'-diamine	OSHA	0.1 mg/m3 Ceiling
		ACGIH	0.1 mg/m3 Ceiling
		NIOSH	0.1 mg/m3 Ceiling
		Supplier	
		OHSA, CAN	0.1 mg/m3 Ceiling
		Mexico	
		Brazil	
0002855-13-2	Isophorone diamine	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0061791-53-5	Amines, N-tallow alkyltrimethylenedi-, oleates	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0071074-89-0	Bis[(dimethylamino)methyl]phenol	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	

Health Data

CAS No.	Ingredient	Source	Value
0000090-72-2	2,4,6-Tri(dimethylaminomethyl)phenol	NIOSH	
0000100-51-6	Benzyl alcohol	NIOSH	
0000108-10-1	Methylisobutyl ketone	NIOSH	Irritation liver
0001477-55-0	m-Xylene-alpha, alpha'-diamine	NIOSH	Skin irritation systemic effects
0002855-13-2	Isophorone diamine	NIOSH	
0061791-53-5	Amines, N-tallow alkyltrimethylenedi-, oleates	NIOSH	
0071074-89-0	Bis[(dimethylamino)methyl]phenol	NIOSH	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000090-72-2	2,4,6-Tri(dimethylaminomethyl)phenol	OSHA	Select Carcinogen: No

## KRA855\_A1

		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000100-51-6	Benzyl alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-10-1	Methylisobutyl ketone	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0001477-55-0	m-Xylene-alpha, alpha'-diamine	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0002855-13-2	Isophorone diamine	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0061791-53-5	Amines, N-tallow alkyltrimethylenedi-, oleates	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0071074-89-0	Bis[(dimethylamino)methyl]phenol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

### 8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

### 9. Physical and chemical properties

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured

## KRA855\_A1

Initial boiling point and boiling range	79 (°C) 175 (°F)
Flash Point	58 (°C) 136 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.3 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	0.99
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.
VOHAP content (gm/litre of paint)	137.63 (as supplied)
VOHAP content (gm/litre of Solid Coating)	98.36 (as supplied)

10. Stability and reactivity
------------------------------

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

### 10.3. Possibility of hazardous reactions

No data available

### 10.4. Conditions to avoid

No data available

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

**FLAMMABLE/COMBUSTIBLE MATERIALS:** May be ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.

11. Toxicological information
-------------------------------

### Acute toxicity

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Benzyl alcohol - (100-51-6)	1,230.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	No data available	4.178, Rat - Category: 4
Isophorone diamine - (2855-13-2)	1,030.00, Rat - Category: 4	2,001.00, Rat - Category: 5	No data available	5.02, Rat - Category: NA
Amines, N-tallow alkyltrimethylenedi-, oleates - (61791-53-5)	5,000.00, Rat - Category: 5	No data available	No data available	No data available

## KRA855\_A1

m-Xylene-alpha, alpha'-diamine - (1477-55-0)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	2.40, Rat - Category: 3	No data available
Methylisobutyl ketone - (108-10-1)	2,080.00, Rat - Category: 5	16,000.00, Rabbit - Category: NA	12.30, Rat - Category: 4	No data available
2,4,6-Tri(dimethylaminomethyl)phenol - (90-72-2)	1,200.00, Rat - Category: 4	1,280.00, Rat - Category: 4	No data available	No data available
Bis[(dimethylamino)methyl]phenol - (71074-89-0)	No data available	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	5	May be harmful if swallowed.
Acute Toxicity (skin)	5	May be harmful in contact with skin.
Acute Toxicity (inhalation)	4	Harmful if inhaled.
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

### 12. Ecological information

#### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Benzyl alcohol - (100-51-6)	10.00, Lepomis macrochirus	55.00, Daphnia magna	700.00 (72 hr), Algae
Isophorone diamine - (2855-13-2)	110.00, Leuciscus idus	17.40, Daphnia magna	37.00 (72 hr), Scenedesmus subspicatus
Amines, N-tallow alkyltrimethylenedi-, oleates - (61791-53-5)	0.10, Fish (Piscis)	0.001, Daphnia magna	0.01 (72 hr), Algae
m-Xylene-alpha, alpha'-diamine - (1477-55-0)	100.00, Oncorhynchus mykiss	16.00, Daphnia magna	Not Available
Methylisobutyl ketone - (108-10-1)	505.00, Pimephales promelas	1,550.00, Daphnia magna	980.00 (48 hr), Scenedesmus subspicatus
2,4,6-Tri(dimethylaminomethyl)phenol - (90-72-2)	Not Available	Not Available	Not Available
Bis[(dimethylamino)methyl]phenol - (71074-89-0)	Not Available	Not Available	Not Available

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

Not Measured



## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

## 12.6. Other adverse effects

No data available

## 13. Disposal considerations

## 13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

## 14. Transport information

- 14.1. UN number UN 3469  
 14.2. UN proper shipping name PAINT, FLAMMABLE LIQUID, CORROSIVE  
 14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT, FLAMMABLE LIQUID, CORROSIVE	IMDG Proper Shipping Name	PAINT, FLAMMABLE LIQUID, CORROSIVE
DOT Hazard Class	3 Flammable and Combustible Liquids, 8 Corrosive Liquids	IMDG Hazard Class Sub Class	3 Flammable and Combustible Liquids, 8 Corrosive Liquids Not applicable
UN / NA Number	UN 3469	IMDG Packing Group	III
DOT Packing Group	III	System Reference Code	206
CERCLA/DOT RQ	6103 gal. / 50292 lbs.		

- 14.4. Packing group III  
 14.5. Environmental hazards  
 IMDG Marine Pollutant: No ( Amines, N-tallow alkyltrimethylenedi-, oleates )  
 14.6. Special precautions for user  
 Not Applicable  
 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code  
 Not Applicable

## 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3 D2B E

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :  
Methylisobutyl ketone (5000 lb final RQ; 2270 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

Methylisobutyl ketone  
 Mass RTK Substances (>1%) :  
 Benzyl alcohol  
 m-Xylene-alpha, alpha'-diamine  
 Methylisobutyl ketone  
 Penn RTK Substances (>1%) :  
 Benzyl alcohol  
 m-Xylene-alpha, alpha'-diamine  
 Methylisobutyl ketone  
 Penn Special Hazardous Substances (>.01%) :  
 (No Product Ingredients Listed)  
 RCRA Status:  
 (No Product Ingredients Listed)  
 N.J. RTK Substances (>1%) :  
 Isophorone diamine  
 m-Xylene-alpha, alpha'-diamine  
 Methylisobutyl ketone  
 N.J. Special Hazardous Substances (>.01%) :  
 Isophorone diamine  
 Methylisobutyl ketone  
 N.J. Env. Hazardous Substances (>.1%) :  
 Methylisobutyl ketone  
 Proposition 65 - Carcinogens (>0%):  
 Methylisobutyl ketone  
 Proposition 65 - Female Repro Toxins (>0%):  
 (No Product Ingredients Listed)  
 Proposition 65 - Male Repro Toxins (>0%):  
 (No Product Ingredients Listed)  
 Proposition 65 - Developmental Toxins (>0%):  
 (No Product Ingredients Listed)

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H400 Very toxic to aquatic life.  
 H412 Harmful to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

SECTION 2: Hazards identification

SECTION 4: First aid measures

SECTION 9: Physical and chemical properties

SECTION 12: Ecological information

SECTION 14: Transport information

End of Document