

## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

1. Product and company identification
---------------------------------------

Hazardous according to criteria of Safework Australia.

Classified as a Dangerous Good for transport according to the ADG code (7th edition).

Product Name	INTERLINE 850 GREY PART A
Product Code	TLA851
Intended use	This product is intended for use in the Marine and Protective Coatings markets. Refer Technical Data Sheet. For professional use only.
Application Method	Apply by brush and roller for small areas. Airless spray for large areas. Refer Technical Data Sheet.
Company Name	Akzo Nobel Protective Coatings 115 Hyde Road Yeronga Queensland Australia
Telephone No.	(07) 3892 8888
Fax No.	(07) 3892 4287
24 hour Emergency Telephone No.	1800 680 071
For Poisons Advice telephone	131 126 For Advice to Doctors & Hospitals only

2. Hazard Identification
--------------------------

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10 - Flammable.

R36/38 - Irritating to eyes and skin.

R43 - May cause sensitisation by skin contact.

S53 - Attention - Avoid exposure - obtain special instructions before use.

S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets.

S23 - Do not breathe vapour/spray.

S24 - Avoid contact with skin.

S28 - After contact with skin, wash immediately with plenty of soap and water.

S37/39 - Wear suitable gloves and eye/face protection.

S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51 - Use only in well-ventilated areas.

Poison Schedule: 5

**HSNO Number:HSR002662**

**Group Standard: Surface Coatings and Colorants (Flammable)**

**(HSNO 3.1B or 3.1C Classification)**

Further information is given in section 11.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

### 3. Composition / information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations. Users are referred to the Safework Australia website <http://safeworkaustralia.gov.au> for more information.

Ingredient	CAS Number	Concentration Range%	Symbol (s)	Risk phrases (*)
Epoxy Resin	0025068-38-6	10-25	Xi	R36/38, R43, R51/R53
5-methylhexan-2-one	0000110-12-3	2.5-10	Xn	R20
Bisphenol F epoxy resin	Not Available	2.5-10	Xi,N	R36/38, R43, R51/53
Solvent naphtha (petroleum), light aromatic	0064742-95-6	2.5-10	Xn	R65
Iron(III) oxide	0001317-61-9	1-2.5		

Other ingredients in this product have been determined not to be hazardous

\* The full text of the above phrases are shown in section 16.

\* Cut of levels for labelling Risk and Safety Phrases are shown in section 15.

### 4. First aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

#### Eye Contact

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

#### Skin Contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

#### Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

**5. Fire-fighting measures**

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Do not use - water jet.

Note; Fire will produce dense black smoke. Decomposition products may be hazardous to health. Avoid exposure and use breathing apparatus as appropriate.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

**6. Accidental release measures**

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

Ventilate the area to avoid breathing vapours. Take the personal protective measures listed in Section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to relevant State and Federal regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the relevant Environment Protection Agency.

Empty containers may contain product residues, including flammable or explosive vapours. Do not cut, puncture or weld on or near containers. All label warnings must be observed until the containers have been cleaned or reconditioned.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

7. Handling and storage
-------------------------

### Handling

This product contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

### In Storage

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

### In Use

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Observe label precautions. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty a container; containers are not pressure vessels.

All sources of ignition (hot surfaces, sparks, open flames etc) should be excluded from areas of preparation and application. All electrical equipment (including torches) should be protected (Ex) to the appropriate standard.

The product may charge electrostatically. Always use earthing leads when pouring solvents and transferring product. Operators should wear clothing which does not generate static (at least 60% natural fibre) and antistatic footwear; floors should be of conducting type.

### Storage

Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same material.

Prevent unauthorised access.

The requirements of AS/NZS1940 (Storage and Handling of Flammable and Combustible Liquids) apply to all products with a Flash Point less than 61C. Refer to this standard and to State Dangerous Goods Storage and Handling regulations.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

## 8. Exposure controls and personal protection

**Engineering Measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

**Exposure Limits**

From Safework Australia's Hazardous Substance Information System (HSIS)  
 For detailed information refer to the HSIS web site (<http://hsis.ascc.gov.au>).

Material	Short term (15m ave STEL)		Long term (8hr TWA)	
	ppm	mg/M3	ppm	mg/M3
5-methylhexan-2-one	-	-	50	234

Chemicals classified as hazardous by Safework Australia may have a notification alongside the exposure standard. If such a notification is necessary, it will appear in the far right hand column. The legend is as follows:

- (P) Peak exposure limit
- (R) Suppliers Recommended Limit
- (Sk) There is a risk of absorption through unbroken skin
- (Sen) Sensitiser
- (Cat1) Category 1 - established human carcinogen
- (Cat2) Category 2 - probable human carcinogen
- (Cat3) Category 3 - substances suspected of having carcinogenic potential.

There is no biological limit allocated.

**Personal Protection**
**Respiratory Protection**

Respiratory protection is required in insufficiently ventilated working areas and during spraying. When concentrations exceed the exposure limits shown above workers must wear appropriate properly fitted, air-purifying or air-fed respirators approved in accordance AS/NZS1716. Provision of other controls such as exhaust ventilation should be considered if practical.

**Eye Protection**

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should comply with AS/NZS1337.

Wear a full face shield if mixing or pouring operations pose a risk of splashes.

An eye wash station is suggested as a good work place practice.

**Hand Protection**

Gloves of an appropriate material should be worn during mixing and application. Nitrile or PVC gloves are generally recommended for products containing solvents.

### Skin Protection

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help to protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

### 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Colour</b>	Grey
<b>Flash Point (deg C closed cup)</b>	35
<b>Autoignition temperature</b>	425
<b>Viscosity (cSt)</b>	N/A
<b>Specific Gravity</b>	1.722
<b>Solvent Weight %</b>	13.33
<b>Vapour Density</b>	Heavier than air.
<b>pH</b>	Not Applicable
<b>Lower Explosive Limit (%v/v air)</b>	0.8
<b>Solubility in Water</b>	Immiscible
<b>R.A.Q. to ventilate to 10% of the LEL (M3/l)</b>	54.65
<b>Odour</b>	Smell of Solvent

### 10. Stability and reactivity

**Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**Conditions to avoid**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.

**Incompatible materials**

Strong acids, bases, oxidising agents.

**Hazardous decomposition products**

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

**Hazardous reactions**

None.

### 11. Toxicological information

There are no data available on the product itself.

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations this preparation may be an irritant and a skin and respiratory sensitiser. Low molecular weight epoxy constituents are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and sensitisation, possibly with cross-sensitisation to other epoxies.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

12. Ecological information

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

13. Disposal considerations

Do not allow into drains or water courses. Wastes and empty containers should be disposed of in accordance with State and Federal regulations.

Using information provided in this data sheet advice should be obtained from the local Waste Regulation Authority as to whether special waste regulations apply.

14. Transport information

Transport only in accordance with the following regulations:

Road and Rail

Transport UN1263, PAINT, CLASS 3, PGIII, HAZCHEM .3Y (ADG7)

IMDG reference :	Class/Div.	3	Subsidiary Class
	Proper Shipping Name	Paint	
	UN No.	1263	MFAG
	EMS	F-E,S-E	
	Packaging Group	III	
	Marine pollutant	Yes	

ICAO/IATA	Shipping Name	Paint
	Class	3
	UN No.	1263
	Packaging Group	III



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

15. Regulatory information
----------------------------

The following information is provided in accordance with Safework Australia guidelines for the labelling of Hazardous Substances.

Symbol(s)

Irritant

Contains;

Bisphenol F epoxy resin

Epoxy Resin

Risk (R)Phrases;

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10 - Flammable.

R36/38 - Irritating to eyes and skin.

R43 - May cause sensitisation by skin contact.

Safety (S)Phrases;

S53 - Attention - Avoid exposure - obtain special instructions before use.

S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets.

S23 - Do not breathe vapour/spray.

S24 - Avoid contact with skin.

S28 - After contact with skin, wash immediately with plenty of soap and water.

S37/39 - Wear suitable gloves and eye/face protection.

S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51 - Use only in well-ventilated areas.

Precautionary (P)Phrases;

Contains epoxy constituents. See information supplied by the manufacturer.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## Material Safety Data Sheet

TLA851

INTERLINE 850 GREY PART A

Version Number 6 Revision Date 06/26/13

16. Other information
-----------------------

Contact point:

Industrial Coatings HSE Department - Health and Safety Advisor  
+61 (0)3 9313 4555

Marine & Protective Coatings Regulatory Affairs Manager  
+61 (0)3 8336 8487

The information on this MSDS is based upon the present state of our knowledge and on current State and Federal laws.

The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Material Safety Data Sheet is required according to State and Federal legislation and following Safework Australia's guidance (as amended).

The full text of the Risk (R) phrases appearing in section 3 is:

R20 - Harmful by inhalation.

R36/38 - Irritating to eyes and skin.

R43 - May cause sensitisation by skin contact.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 - Harmful: May cause lung damage if swallowed.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.