

# SAFETY DATA SHEET

## Intergard 400 MIO Light Grey Part A

### Section 1. Identification

Intergard 400 MIO Light Grey Part A : GHS product identifier  
 EPA007 : Product code

Identified uses	
Professional application of coatings and inks	
Uses advised against	Reason
All Other Uses	

International Paint Ltd. : **Supplier's details**  
 Stoneygate Lane  
 Felling  
 Gateshead  
 Tyne and Wear  
 NE10 0JY UK  
 Tel: +44 (0)191 469 6111 Fax: +44 (0)191 438 3711

+44 (0)191 469 6111 (24H) : **Emergency telephone number (with hours of operation)**  
 +966 55 388 0087 : **National advisory body/ Poison Centre (For use only by licensed medical professionals.)**  
 sdsfellinguk@akzonobel.com : **e-mail address of person responsible for this SDS**

### Section 2. Hazards identification

FLAMMABLE LIQUIDS - Category 3 : **Classification of the substance or mixture**  
 SKIN CORROSION/IRRITATION - Category 2  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 SKIN SENSITIZATION - Category 1  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS) and hearing organs) - Category 1

#### GHS label elements



: **Hazard pictograms**

Danger : **Signal word**  
 Flammable liquid and vapour. : **Hazard statements**  
 Causes serious eye damage.  
 Causes skin irritation.  
 May cause an allergic skin reaction.  
 May cause respiratory irritation.  
 Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS), hearing organs)

## Section 2. Hazards identification

### Precautionary statements

Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapour. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe gas, vapour or spray. : **Prevention**

Get medical attention if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. : **Response**

Store locked up. Store in a well-ventilated place. Keep cool. : **Storage**

Dispose of contents and container in accordance with all local, regional, national and international regulations. : **Disposal**

Wear appropriate respirator when ventilation is inadequate. : **Supplemental label elements**

None known.

: **Other hazards which do not result in classification**

## Section 3. Composition/information on ingredients

Mixture

: **Substance/mixture**

Classification	CAS number	% by weight	Ingredient name
Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317	25068-38-6	≥10 - ≤25	Reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin, 700 <mol weight < 1000
Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304	1330-20-7	≥10 - <22	xylene
Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	71-36-3	≤10	butan-1-ol
Flam. Liq. 2, H225 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304	100-41-4	≤5	ethylbenzene

## Section 3. Composition/information on ingredients

Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 (central nervous system (CNS)) (inhalation) Asp. Tox. 1, H304 Aquatic Chronic 2, H411	64742-82-1	<2.5	Naphtha (petroleum), hydrodesulfurized heavy
--	------------	------	--

**There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. : **Eye contact**

Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. : **Inhalation**

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. : **Skin contact**

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. : **Ingestion**

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Causes serious eye damage. : **Eye contact**  
May cause respiratory irritation. : **Inhalation**  
Causes skin irritation. May cause an allergic skin reaction. : **Skin contact**  
Irritating to mouth, throat and stomach. : **Ingestion**

#### Over-exposure signs/symptoms

Adverse symptoms may include the following: : **Eye contact**  
pain  
watering  
redness

## Section 4. First aid measures

Adverse symptoms may include the following:

respiratory tract irritation

coughing

headache

drowsiness/fatigue

dizziness/vertigo

muscle weakness

unconsciousness

: Inhalation

Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

: Skin contact

Adverse symptoms may include the following:

stomach pains

: Ingestion

### **Indication of immediate medical attention and special treatment needed, if necessary**

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

: Notes to physician

No specific treatment.

: Specific treatments

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

: Protection of first-aiders

See toxicological information (Section 11)

## Section 5. Firefighting measures

### **Extinguishing media**

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

: Suitable extinguishing media

Do not use water jet.

: Unsuitable extinguishing media

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

: Specific hazards arising from the chemical

Decomposition products may include the following materials:

carbon dioxide

carbon monoxide

metal oxide/oxides

: Hazardous thermal decomposition products

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

: Special protective actions for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Special protective equipment for fire-fighters

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

: **For non-emergency personnel**

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

: **For emergency responders**

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

: **Environmental precautions**

### Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

: **Small spill**

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

: **Large spill**

## Section 7. Handling and storage

### Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

: **Protective measures**

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

: **Advice on general occupational hygiene**

## Section 7. Handling and storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

: **Conditions for safe storage, including any incompatibilities**

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Exposure limits	Ingredient name
<b>ACGIH TLV (United States, 3/2015).</b> STEL: 651 mg/m <sup>3</sup> 15 minutes. STEL: 150 ppm 15 minutes. TWA: 434 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours.	xylene
<b>ACGIH TLV (United States, 3/2015).</b> TWA: 20 ppm 8 hours.	butan-1-ol
<b>ACGIH TLV (United States, 3/2015).</b> TWA: 20 ppm 8 hours.	ethylbenzene

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

: **Appropriate engineering controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

: **Environmental exposure controls**

### Individual protection measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

: **Hygiene measures**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

: **Eye/face protection**

### Skin protection

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE:

: **Hand protection**



## Section 8. Exposure controls/personal protection

The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

: **Body protection**: **Other skin protection**: **Respiratory protection**

## Section 9. Physical and chemical properties

### Appearance

Liquid.

Metallic.

Solvent.

Not available.

Not applicable.

Not available.

Lowest known value: 136.16°C (277.1°F) (xylene).

Closed cup: 23°C (73.4°F)

Not available.

Not available.

Greatest known range: Lower: 1.4% Upper: 11.3% (butan-1-ol)

Not available.

Not available.

1.67

Insoluble in the following materials: cold water.

Not available.

Not available.

Not available.

Kinematic (room temperature): 418 mm<sup>2</sup>/s (418 cSt): **Physical state**: **Colour**: **Odour**: **Odour threshold**: **pH**: **Melting point**: **Boiling point**: **Flash point**: **Evaporation rate**: **Flammability (solid, gas)**: **Lower and upper explosive (flammable) limits**: **Vapour pressure**: **Vapour density**: **Relative density**: **Solubility**: **Partition coefficient: n-octanol/water**: **Auto-ignition temperature**: **Decomposition temperature**: **Viscosity**

## Section 10. Stability and reactivity

No specific test data related to reactivity available for this product or its ingredients.

: **Reactivity**

The product is stable.

: **Chemical stability**

Under normal conditions of storage and use, hazardous reactions will not occur.

: **Possibility of hazardous reactions**

## Section 10. Stability and reactivity

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. : **Conditions to avoid**

Reactive or incompatible with the following materials:  
oxidizing materials : **Incompatible materials**

Under normal conditions of storage and use, hazardous decomposition products should not be produced. : **Hazardous decomposition products**

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Exposure	Dose	Species	Result	Product/ingredient name
-	4300 mg/kg	Rat	LD50 Oral	xylene
4 hours	24 mg/l	Rat	LC50 Inhalation Vapour	butan-1-ol
-	3400 mg/kg	Rabbit	LD50 Dermal	
-	790 mg/kg	Rat	LD50 Oral	
4 hours	4000 ppm	Rabbit	LC50 Inhalation Gas.	ethylbenzene
-	17800 mg/kg	Rabbit	LD50 Dermal	
-	3500 mg/kg	Rat	LD50 Oral	

#### Irritation/Corrosion

Observation	Exposure	Score	Species	Result	Product/ingredient name
-	24 hours 2 milligrams	-	Rabbit	Eyes - Severe irritant	butan-1-ol
-	0.005 Milliliters	-	Rabbit	Eyes - Severe irritant	
-	24 hours 20 milligrams	-	Rabbit	Skin - Moderate irritant	
-	500 milligrams	-	Rabbit	Eyes - Severe irritant	ethylbenzene
-	24 hours 15 milligrams	-	Rabbit	Skin - Mild irritant	

#### Sensitisation

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)



## Section 11. Toxicological information

Target organs	Route of exposure	Category	Name
Respiratory tract irritation	Not applicable.	Category 3	xylene
Respiratory tract irritation and Narcotic effects	Not applicable.	Category 3	butan-1-ol
Respiratory tract irritation	Not applicable.	Category 3	ethylbenzene
Narcotic effects	Not applicable.	Category 3	Naphtha (petroleum), hydrodesulfurized heavy

### Specific target organ toxicity (repeated exposure)

Target organs	Route of exposure	Category	Name
hearing organs central nervous system (CNS)	Not determined Inhalation	Category 2 Category 1	ethylbenzene Naphtha (petroleum), hydrodesulfurized heavy

### Aspiration hazard

Result	Name
ASPIRATION HAZARD - Category 1	xylene
ASPIRATION HAZARD - Category 1	ethylbenzene
ASPIRATION HAZARD - Category 1	Naphtha (petroleum), hydrodesulfurized heavy

Not available.

: Information on likely routes of exposure

### Potential acute health effects

Causes serious eye damage.

: Eye contact

May cause respiratory irritation.

: Inhalation

Causes skin irritation. May cause an allergic skin reaction.

: Skin contact

Irritating to mouth, throat and stomach.

: Ingestion

### Symptoms related to the physical, chemical and toxicological characteristics

Adverse symptoms may include the following:

: Eye contact

pain  
watering  
redness

Adverse symptoms may include the following:

: Inhalation

respiratory tract irritation  
coughing  
headache  
drowsiness/fatigue  
dizziness/vertigo  
muscle weakness  
unconsciousness

Adverse symptoms may include the following:

: Skin contact

pain or irritation  
redness  
blistering may occur

Adverse symptoms may include the following:

: Ingestion

stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

## Section 11. Toxicological information

Not available.	: Potential immediate effects
Not available.	: Potential delayed effects
<b><u>Long term exposure</u></b>	
Not available.	: Potential immediate effects
Not available.	: Potential delayed effects
<b><u>Potential chronic health effects</u></b>	
Not available.	
Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	: General
No known significant effects or critical hazards.	: Carcinogenicity
No known significant effects or critical hazards.	: Mutagenicity
No known significant effects or critical hazards.	: Teratogenicity
No known significant effects or critical hazards.	: Developmental effects
No known significant effects or critical hazards.	: Fertility effects

### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

ATE value	Route
13884 mg/kg	Oral
8351.5 mg/kg	Dermal
67.08 mg/l	Inhalation (vapours)

## Section 12. Ecological information

### **Toxicity**

Exposure	Species	Result	Product/ingredient name
48 hours	Crustaceans - Palaemonetes pugio	Acute LC50 8500 µg/l Marine water	xylene
96 hours	Fish - Pimephales promelas	Acute LC50 13400 µg/l Fresh water	butan-1-ol
48 hours	Daphnia - Daphnia magna	Acute EC50 1983 to 2072 mg/l Fresh water	
96 hours	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	Acute LC50 1910 mg/l Fresh water	ethylbenzene
96 hours	Algae - Pseudokirchneriella subcapitata	Acute EC50 3.6 mg/l Fresh water	
48 hours	Daphnia - Daphnia magna - Neonate	Acute LC50 18.4 to 25.4 mg/l Fresh water	
96 hours	Fish - Menidia menidia	Acute LC50 5.1 to 5.7 mg/l Marine water	

### **Persistence and degradability**

Biodegradability	Photolysis	Aquatic half-life	Product/ingredient name
Readily	-	-	ethylbenzene
Not readily	-	-	Naphtha (petroleum), hydrodesulfurized heavy

## Section 12. Ecological information

### Bioaccumulative potential

Potential	BCF	LogP <sub>ow</sub>	Product/ingredient name
low	8.1 to 25.9	3.12	xylene
low	-	1	butan-1-ol
low	15	3.6	ethylbenzene
high	10 to 2500	-	Naphtha (petroleum), hydrodesulfurized heavy

### Mobility in soil

Not available.

: Soil/water partition coefficient (K<sub>oc</sub>)

No known significant effects or critical hazards.

: Other adverse effects

## Section 13. Disposal considerations




The generation of waste should be avoided or minimised wherever possible.

: Disposal methods

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

IATA	IMDG	UN	
UN1263	UN1263	UN1263	UN number
PAINT	PAINT	PAINT	UN proper shipping name
3 	3 	3 	Transport hazard class(es)
III	III	III	Packing group
No.	No.	No.	Environmental hazards
-	-	-	Additional information

Not applicable.

: IMDG Code Segregation group

## Section 14. Transport information

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. : **Special precautions for user**

Not available.

: **Transport in bulk according to Annex II of Marpol and the IBC Code**

## Section 15. Regulatory information

No known specific national and/or regional regulations applicable to this product (including its ingredients). : **Safety, health and environmental regulations specific for the product**

## Section 16. Other information

### Justification

Justification	Classification
On basis of test data	Flam. Liq. 3, H226
Calculation method	Skin Irrit. 2, H315
Calculation method	Eye Dam. 1, H318
Calculation method	Skin Sens. 1, H317
Calculation method	STOT SE 3, H335
Calculation method	STOT RE 1, H372 (central nervous system (CNS) and hearing organs)

### History

03/05/2017

: **Date of printing**

03/05/2017

: **Date of issue/Date of revision**

14/06/2016

: **Date of previous issue**

3

: **Version**

ATE = Acute Toxicity Estimate

: **Key to abbreviations**

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Not available.

: **References**

**Indicates information that has changed from previously issued version.**

### Notice to reader

**IMPORTANT NOTE:** the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

**Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.**

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the

## Section 16. Other information

handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel