#### Material Safety Data Sheet INTERGARD 292 WHITE PART A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number:

Sales Order: {SalesOrd} NHA200 10/01/2011 A6-5

# X.International.

1. Identit	ication of the preparation and company		
Product Identity	INTERGARD 292 WHITE PART A		
Bulk Sales Reference No.	NHA200		
Company Name	International Paint LLC		
	6001 Antoine Drive		
	Houston, Texas 77091		
Emergency			
CHEMTREC (USA)	(800) 424–9300		
International Paint	(713) 682–1711		
Poison Control Center	(800) 854–6813		
Customer Service			
International Paint	(800) 589–1267		
Fax No.	(800) 631–7481		

2. Hazard identification of the product

### GHS Classification;

and blassification,		
Item	Category	Hazard
Flammability	Not classified	Not applicable
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	blood (circulatory system), central nerve system, kidneys, liver
	2	Not applicable
	3	respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	blood (circulatory system)
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable
Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases: Not Applicable							
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be						
Inhalation	harmful or fatal. Avoid contact with eyes, skin and clothing. Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.						
Eyes		tation. Avoid contact with					
Skin	Causes skin irritation.	May be harmful if absorb	ed through the skin.				
Ingestion	Harmful if swallowed. I drowsiness.	May cause abdominal pa	in, nausea, vomiting,	diarrhea, or			
Chronic effects		d. Contains an ingredient ion 2 and Section 15 for e nd level of exposure.					
HMIS Rating	Health: 2	Flammability: 1	Reactivity: 0	PPE: X			
	3. Compositi	on/information on ingredi	ents				
	•	-					
Ingredient		CAS No.	Percent				
2–Butoxyethanol Ethylene glycol monopi	ronul ether	0000111-76-2 0002807-30-9	1.0 – 10 1.0 – 10				
Titanium dioxide	ropyi etner	0002807-30-9	1.0 – 10 10 – 25				
Wollastonite (Ca(SiO3)	)	0013983-17-0	10 – 23 1.0 – 10				
Talc	)	0013903-17-0	1.0 - 10				
Modified Epoxy Resin		TS-RE2404	10 – 25				
	4.	First aid measures					
General	General Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.   Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If						
Eyes	In case of co	difficult, give oxygen. Get ntact, immediately flush e Get medical attention imm	eyes with plenty of wa	-			
Skin		ntact, immediately flush s	skin with soap and pl	enty of water. Get			
Ingestion	1-800-854-	immediately contact Pois 6813. DO NOT induce vo onnel. Never give anythir	miting unless instruc	ted to do so by			
	5. Fi	re-fighting measures					
Flash Point		F: No Established C: No Established					
Lower Explosive Limit ( ERG Guide No.	LEL) 1 (%vol ir 159	air) at Normal Atmosphe	eric Temp and Press	ure			
	6. Accio	lental release measures					
Spill Response Procedures	immediate area). Do n do so without risk. Pre areas. Absorb or cover transfer to containers.	FION SOURCES (no smo ot touch or walk through vent entry into waterways with dry earth, sand, or LARGE SPILLS: Dike far	spilled material. Stop s, sewers, basements other non-combustib	leak if you can or confined le material and			
Public SafetyCALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep							

unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. 159

ERG Guide No.

7. Handling and storage

Storage TemperatureStore between 40–100F (4–38C).Handling and Storage<br/>PrecautionsKeep away from heat, sparks and flame. Do not smoke. Extinguish all flames and<br/>pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition<br/>during use and until all vapors are gone. Vapors may cause flash fire or ignite<br/>explosively. Prevent build–up of vapors by opening all windows and doors to achieve<br/>cross–ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated<br/>contact with skin. Close container after each use. Wash thoroughly after handling.

<ol><li>Exposure controls and perso</li></ol>	nal protection
---	----------------

CAS No.	Ingredient	Source	Value
0000111-76-2	2-Butoxyethanol	OSHA	50 ppm TWA; 240 mg/m3 TWA
		ACGIH	20 ppm TWA
		NIOSH	5 ppm TWA; 24 mg/m3 TWA700 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWAEV
		Mexico	26 ppm TWA; 120 mg/m3 TWA75 ppm STEL; 360 mg/m3 STEL
		Brazil	39 ppm TWA; 190 mg/m3 TWA
0002807-30-9	Ethylene glycol monopropyl	OSHA	No Established Limit
	ether	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWAEV; 110 mg/m3 TWAEV
		Mexico	No Established Limit
		Brazil	No Established Limit
013463-67-7	7 Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWAEV (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0014807–96–6	Talc	OSHA	No Established Limit
		ACGIH	2 mg/m3 TWA (respirable fraction, particulate matte containing no asbestos and
		NIOSH	2 mg/m3 TWA (respirable dust, containing no asbestos and less than 1% quartz)1000 mg/m3 IDLH (containg no asbestos and
		Supplier	No Established Limit
		OHSA,	2 mg/m3 TWAEV (respirable, containing no

		CAN	asbestos and less than 1% crystalline silica)
		Mexico	2 mg/m3 TWA
		Brazil	No Established Limit
TS-RE2404	Modified Epoxy Resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

	Health Data				
CAS No.	Ingredient	Source	Value		
0000111–76–2	2-Butoxyethanol	NIOSH	Adverse effects on blood and hematopoietic system tissue irritation		
0002807-30-9	Ethylene glycol monopropyl ether	NIOSH	No Established Limit		
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals		
0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	No Established Limit		
0014807–96–6	Talc		(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects		
TS-RE2404	Modified Epoxy Resin	NIOSH	No Established Limit		

	Carcinogen Data					
CAS No.	Ingredient	Source	Value			
0000111-76-2	2–Butoxyethanol	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;			
0002807-30-9	Ethylene glycol	OSHA	Select Carcinogen: No			
	monopropyl ether	NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			
0013463–67–7	Titanium dioxide	OSHA	Select Carcinogen: Yes			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;			
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;			
0014807–96–6	Talc	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;			
TS-RE2404	Modified Epoxy Resin	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other

Eyes	manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles,
	and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties				
Physical State	Liquid Coloured			
рН	No Established Limit			
Specific Gravity	1.39			
Boiling Point F	210			
Vapor Density	Heavier than air			
VOC %	Refer to the Technical Data Sheet or label where information is available.			
Evaporation Rate Slower than ether				
	10. Stability and reactivity			
General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly			

	handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous	May produce hazardous fumes when heated to decomposition as in welding. Fumes
Decompostion	may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information					
Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr		
2-Butoxyethanol - (0000111-76-2)	470.00, Rat – Category: 4	220.00, Rabbit – Category: 3	2.21, Rat – Category: 3		
Ethylene glycol monopropyl ether – (0002807–30–9)	3,089.00, Rat – Category: 5				
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabitt – Category: NA	6,082.00, Rat – Category: NA		
Wollastonite (Ca(SiO3)) – (0013983–17–0)					
Talc – (0014807–96–6)					
Modified Epoxy Resin – (TS–RE2404)					

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

General

### 13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

	14. Transpor	rt information	
DOT (Domestic Su	face Transportation)	IMO / IMDG (Oce	ean Transportation)
DOT Proper Shipping Name	PAINT OR PAINT RELATED MATERIAL, NMFC 149980	IMDG Proper Shipping Name	• •
DOT Hazard Class	NR	IMDG Hazard Class	Not Regulated
UN / NA Number	Not Regulated	UN / NA Number	Not Regulated
DOT Packing Group	Not Regulated	IMDG Packing Group	Not Regulated
CERCLA/DOT RQ	5761 gal. / 66667 lbs.	System Reference Code	9
	15. Regulato	ry information	
Regulatory Overview	selected regulations are	Section 15 is not intended to b e represented. All ingredients bstance Control Act) Inventory entory.	of this product are listed
WHMIS Classification	No Established Limit		
DOT Marine Pollutants (No Product Ingre			
DOT Severe Marine Pol (No Product Ingre			
EPCRA 311/312 Chemi			
Nitrous ac	id, sodium salt (100 lb final F	RQ; 45.4 kg final RQ)	
EPCRA 302 Extremely (No Product Ingre			
EPCRA 313 Toxic Cher	nicals (>.1%) :		
Barium			
	id, sodium salt		
Mass RTK Substances	(>1%):		
2–Butoxye	ethanol		
Talc			
Titanium o	lioxide		
Mass Extraordinarily Ha	z Sub (>.01%) :		
Quartz			
Penn RTK Substances	(>1%):		
2–Butoxye	ethanol		
Talc			
Titanium o	lioxide		
Penn Special Hazardou (No Product Ingre			
Rhode Island Hazardou	s Substances (>.1%) :		
Barium			
2–Butoxye	ethanol		
Diacetone	alcohol		
Mica			
Talc			
Titanium o	lioxide		
RCRA Status (%):			
N.J. RTK Substances (>	.1%) :		
( )			

Titanium dioxide N.J. Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) N.J. Env. Hazardous Substances (>.1%) : Barium Nitrous acid, sodium salt Proposition 65 – Carcinogens (>0%): 1,4-Dioxane Acetaldehyde Benzene, (chloromethyl)-Epichlorohydrin Ethylene oxide Lead Quartz Proposition 65 – Female Repro Toxins (>0%): Ethylene oxide Lead Proposition 65 – Male Repro Toxins (>0%): Epichlorohydrin Lead Proposition 65 – Developmental Toxins (>0%): Lead **Risk Phrases:** Not Applicable

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.