

Safety Data Sheet

LYY999/00/A/TT INTERLAC 639 ????????

Version 1 Revision Date 10/21/13

1. Product and company identification

1.1. Product identifier INTERLAC 639 ????????

Product Code LYY999/00/A/TT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Refer Technical Data Sheet.

Application Method Refer Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Manufacturer International Paint Taiwan

No. 20, Yumin St., Dafa Industrial Park

Daliao District, Kaohsiung City 83162,

Taiwan (R.O.C.)

 Telephone No.
 07-787 3959

 Fax No.
 07-787 3953

 1.4. Emergency telephone number
 07-787 3959

For Poisons Advice telephone For Advice to Doctors & Hospitals only

2. Hazard identification of the product

2.1. Classification of the substance or mixture

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.

[Prevention]: [Response]: [Storage]: [Disposal]:

2.3. Other hazards

3. Composition/information on ingredients

This product contains the following hazardous substances.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1,2,4,-Trimethylbenzene CAS Number: 0000095-63-6		Flam. Liq. 3;H226 Acute Tox. 4;H332	[1][2]

		Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Aquatic Chronic 2;H411	
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	25-50	Asp. Tox. 1;H304	[1]
Zirconium salts = 60 %w/w (Typical). CAS Number: 0072854-21-8	10-25		[1]
Cumene CAS Number: 0000098-82-8	2.5-10	Flam. Liq. 3;H226 Asp. Tox. 1;H304 STOT SE 3;H335 Aquatic Chronic 2;H411	[1][2]
White spirits CAS Number: 0008052-41-3	2.5-10	Asp. Tox. 1;H304	[1][2]

- [1] Substance classified with a health or environmental hazard.
- [2] Substance with a workplace exposure limit.
- [3] PBT-substance or vPvB-substance.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

4. First aid measures

4.1. Description of first aid measures

General

Inhalation

Skin Contact

Eye Contact

Ingestion

- 4.2. Most important symptoms and effects, both acute and delayed
- 4.3. Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

- 5.1. Extinguishing media
- 5.2. Special hazards arising from the substance or mixture
- 5.3. Advice for fire-fighters

6. Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
- 6.2. Environmental precautions
- 6.3. Methods and material for containment and cleaning up

7. Handling and storage

^{*}The full texts of the Hazard (H) phrases are shown in Section 16.

7.1. Precautions for safe handling Handling In Storage 7.2. Conditions for safe storage, including any incompatibilities 7.3. Specific end use(s) 8. Exposure controls and personal protection 8.1. Control parameters Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygenists). Long term (8hr time weighted Comments Short term (15 min. ave) Material average) mg/m³ ppm ppm mg/M3 Cumene 300 885 50 246 White spirits 100 525 Key to notification (P) Peak exposure limit (R) Suppliers Recommended Limit (Sk) There is a risk of absorption through unbroken skin (Sen) Sensitiser (Cat1) Category 1 - established human carcinogen (Cat2) Category 2 - probable human carcinogen (Cat3) Category 3 - substances suspected of having carcinogenic potential **DNEL/PNEC** values 8.2. Exposure controls **Eye Protection Skin Protection** Other **Respiratory Protection** Thermal hazards

9. Physical and chemical properties

Colour

Odour

Odour threshold

pН

Melting point / freezing point (°C)

Initial boiling point and boiling range (°C)

Flash Point (C)

Evaporation rate (Ether = 1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits Lower Explosive

Lower Explosive Limit: No data available Upper Explosive Limit: 7 (Solvent naphtha

(petroleum), light aromatic)

Vapour pressure (Pa)

Vapour Density

Specific Gravity 0.00

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Autoignition temperature ()

Decomposition temperature

Viscosity (cSt)

9.2. Other information

No further information

10. Stability and reactivity

- 10.1. Reactivity
- 10.2. Chemical stability
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid
- 10.5. Incompatible materials
- 10.6. Hazardous decomposition products

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
1,2,4,-Trimethylbenzene - (95-63-6)	3,400.00, Rat	3,160.00, Rabbit	18.00, Rat	Not Available
Cumene - (98-82-8)	1,400.00, Rat	10,627.00, Rabbit	Not Available	Not Available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat	3,400.00, Rabbit	Not Available	Not Available
White spirits - (8052-41-3)	Not Available	Not Available	Not Available	Not Available
Zirconium salts = 60 %w/w (Typical) (72854-21-8)	Not Available	Not Available	Not Available	Not Available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	Not Classified	Not Applicable

Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1,2,4,-Trimethylbenzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	Not Available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Zirconium salts = 60 %w/w (Typical) (72854-21-8)	Not Available	Not Available	Not Available
Cumene - (98-82-8)	2.70, Oncorhynchus mykiss	10.60, Daphnia magna	2.60 (72 hr), Pseudokirchneriella subcapitata
White spirits - (8052-41-3)	Not Available	Not Available	Not Available

- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

14. Transport information

- **14.1. UN number**
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)

Road and Rail Transport

IMDG Class/Div Sub Class

reference:

Ems

ICAO/IATA Class Sub Class

14.4. Packing group

14.5. Environmental hazards

Road and Rail Environmentally Hazardous:

Transport

IMDG Marine Pollutant:

reference:

14.6. Special precautions for user

No further information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

The product and all its components complies with these local regulations: NICNAS - Australia EPA - New Zealand

Labor Health & Safety facility
Lead toxic prevention
Public Traffic safety
Toxic substance management
Hazard substance awarenessLead
Labor permit exposure limit of airborne concentration at work place
Waste treatment method and facility standard

16. Other information

The information on this SDS is based upon the present state of our knowledge and on current law. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Safety Data Sheet is required according to legislation.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

This SDS is valid for 5 years from the revised date on page 1. The revision date is in American format (e.g. MM/DD/YY).

End of document



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.