Material Safety Data Sheet INTERGARD 292 RED PART A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number:

Sales Order: {SalesOrd} NHA217 05/12/2011 A9-6

# X.International.

1. Identification of the preparation and company				
Product Identity	INTERGARD 292 RED PART A			
Bulk Sales Reference No.	NHA217			
Company Name International Paint LLC				
	6001 Antoine Drive			
	Houston, Texas 77091			
Emergency				
CHEMTREC (USA)	(800) 424–9300			
International Paint	(713) 682–1711			
Poison Control Center	(800) 854–6813			
Customer Service				
International Paint	(800) 589–1267			
Fax No.	(800) 631–7481			

2. Hazard identification of the product

### GHS Classification;

and blassification,		
Item	Category	Hazard
Flammability	Not classified	Not applicable
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	blood (circulatory system), central nerve system, kidneys, liver
	2	Not applicable
	3	respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	blood (circulatory system)
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable
Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Cofety Dhreece		Not Applicat	_				
Safety Phrases:		Not Applicat	Die				
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be						
Inhalation	harmful or fatal. Avoid contact with eyes, skin and clothing. Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.						
Eyes		ritation. Avoid contact with					
Skin	-	May be harmful if absorb	-				
Ingestion		May cause abdominal pai	•	diarrhea, or			
Chronic effects	animal data (See Sec	rd. Contains an ingredient tion 2 and Section 15 for e and level of exposure.					
HMIS Rating	Health: 2	Flammability: 1	Reactivity: 0	PPE: X			
	3. Composi	tion/information on ingredi	ents				
Ingredient		CAS No.	Percent				
2-Butoxyethanol		0000111-76-2	1.0 – 10				
Ethylene glycol monopi	ropyl ether	0002807-30-9	1.0 – 10 1.0 – 10				
Barium sulfate		0002807-30-9	1.0 – 10 1.0 – 10				
Titanium dioxide		0013463-67-7	1.0 – 10 1.0 – 10				
Wollastonite (Ca(SiO3)	۱ ۱	0013983-17-0	1.0 – 10 1.0 – 10				
Talc	)	0013983-17-0	1.0 – 10 1.0 – 10				
Modified Epoxy Resin		TS-RE2404	1.0 – 10 10 – 25				
		. First aid measures					
	т						
General		ntaminated clothing and sh y. Wash clothing before reu ed shoes.					
Inhalation		emove to fresh air. If not be difficult, give oxygen. Get					
Eyes		ontact, immediately flush e Get medical attention imn		ater for at least			
Skin		ontact, immediately flush s ention immediately.	skin with soap and ple	enty of water. Get			
Ingestion		d, immediately contact Pois					
		-6813. DO NOT induce vo sonnel. Never give anythir					
	5. F	ire-fighting measures					
Flash Point		F: No Established C: No Established	-				
Lower Explosive Limit ( ERG Guide No.	LEL) 1 (%vol 159	in air) at Normal Atmosphe	eric Temp and Press	ure			
	6 400	idental release measures					
L	0.700						
Spill Response Procedures	immediate area). Do do so without risk. Pro areas. Absorb or cove transfer to containers	ITION SOURCES (no smo not touch or walk through s event entry into waterways er with dry earth, sand, or o . LARGE SPILLS: Dike far I runoff from fire control.	spilled material. Stop s, sewers, basements other non-combustib	leak if you can or confined le material and			
Public Safety							

CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

ERG Guide No.

159

### 7. Handling and storage

Storage TemperatureStore between 40–100F (4–38C).Handling and Storage<br/>PrecautionsKeep away from heat, sparks and flame. Do not smoke. Extinguish all flames and<br/>pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition<br/>during use and until all vapors are gone. Vapors may cause flash fire or ignite<br/>explosively. Prevent build–up of vapors by opening all windows and doors to achieve<br/>cross–ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated<br/>contact with skin. Close container after each use. Wash thoroughly after handling.

#### 8. Exposure controls and personal protection

CAS No.	Ingredient	Source	Value
0000111–76–2	2–Butoxyethanol	OSHA	50 ppm TWA; 240 mg/m3 TWA
		ACGIH	20 ppm TWA
		NIOSH	5 ppm TWA; 24 mg/m3 TWA700 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	26 ppm TWA; 120 mg/m3 TWA75 ppm STEL; 360 mg/m3 STEL
		Brazil	39 ppm TWA; 190 mg/m3 TWA
0002807-30-9	Ethylene glycol monopropyl	OSHA	No Established Limit
	ether	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 110 mg/m3 TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463–67–7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	No Established Limit
	,,	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0014807–96–6	Talc	OSHA	No Established Limit
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	2 mg/m3 TWA (containing no Asbestos and
	Supplier	No Established Limit	
	OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and	
		Mexico	2 mg/m3 TWA (respirable fraction)
		Brazil	No Established Limit
TS-RE2404	Modified Epoxy Resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

	Health Data				
CAS No.	Ingredient	Source	Value		
0000111–76–2	2–Butoxyethanol	NIOSH	Adverse effects on blood and hematopoietic system tissue irritation		
0002807-30-9	Ethylene glycol monopropyl ether	NIOSH	No Established Limit		
0007727-43-7	Barium sulfate	NIOSH	Eye nose		
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals		
0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	No Established Limit		
0014807–96–6	Talc	NIOSH	(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects		
TS-RE2404	Modified Epoxy Resin	NIOSH	No Established Limit		

CAS No.	Ingredient	Source	Value		
0000111-76-2	2–Butoxyethanol	OSHA	Select Carcinogen: No		
		NTP Known: No; Suspected: No			
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;		
0002807–30–9	Ethylene glycol	OSHA	Select Carcinogen: No		
	monopropyl ether	NTP	Known: No; Suspected: No		
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0007727–43–7 Bariu		OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0013463–67–7	Titanium dioxide	OSHA	Select Carcinogen: Yes		
		NTP	Known: No; Suspected: No		
			Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;		
0013983–17–0	Wollastonite (Ca(SiO3))	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;		
0014807–96–6	Talc	OSHA	Select Carcinogen: No		

		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
TS-RE2404	Modified Epoxy Resin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.
	9. Physical and chemical properties

Liquid Coloured
No Established Limit
1.34
210
Heavier than air
Refer to the Technical Data Sheet or label where information is available.
Slower than ether
10. Stability and reactivity

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decompostion	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.
	11 Toxicological information

11. Toxicological information					
Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr		
2-Butoxyethanol - (0000111-76-2)	470.00, Rat – Category: 4	220.00, Rabbit – Category: 3	2.21, Rat – Category: 3		
Ethylene glycol monopropyl ether – (0002807–30–9)					

	3,089.00, Rat – Category: 5		
Barium sulfate – (0007727–43–7)			
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA
Wollastonite (Ca(SiO3)) - (0013983-17-0)			
Talc – (0014807–96–6)			
Modified Epoxy Resin – (TS–RE2404)			

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

#### 12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

#### 13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

### 14. Transport information

DOT (Domestic Surface Transportation)		IMO / IMDG (Oce	IMO / IMDG (Ocean Transportation)		
DOT Proper Shipping Name	PAINT OR PAINT RELATED MATERIAL, NMFC 149980	IMDG Proper Shipping Name	PAINT OR PAINT RELATED MATERIAL, NMFC 149980		
DOT Hazard Class	NR	IMDG Hazard Class	Not Regulated		
UN / NA Number	Not Regulated	UN / NA Number	Not Regulated		
DOT Packing Group	Not Regulated	IMDG Packing Group	Not Regulated		
CERCLA/DOT RQ	5963 gal. / 66667 lbs.	System Reference Code	9		
15. Regulatory information					
Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.					
WHMIS Classification	No Established Limit				
DOT Marine Pollutants (10%): (No Product Ingredients Listed)					
DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed)					
EPCRA 311/312 Chemicals and RQs (>.1%):					
Nitrous acid, sodium salt (100 lb final RQ; 45.4 kg final RQ)					
EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed)					
EPCRA 313 Toxic Chemicals (>.1%):					
Barium					
Nitrous acid, sodium salt					
Mass RTK Substances (>1%):					
Barium sulfate					
2-Butoxyethanol					
Talc					
Titanium dioxide					
Mass Extraordinarily Haz Sub (>.01%) :					

Quartz Penn RTK Substances (>1%) : Barium sulfate 2-Butoxyethanol Talc Titanium dioxide Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%) : Barium 2-Butoxyethanol Diacetone alcohol Kaolin Mica Talc Titanium dioxide RCRA Status (%): N.J. RTK Substances (>1%) : Barium sulfate 2-Butoxyethanol Talc Titanium dioxide N.J. Special Hazardous Substances (>.01%) : Barium 2-Butoxyethanol Propylene glycol monomethyl ether Quartz N.J. Env. Hazardous Substances (>.1%) : Barium Nitrous acid, sodium salt Proposition 65 – Carcinogens (>0%): 1,4-Dioxane Acetaldehyde Benzene, (chloromethyl)-Epichlorohydrin Ethylene oxide Lead Quartz Proposition 65 – Female Repro Toxins (>0%): Ethylene oxide Lead Proposition 65 – Male Repro Toxins (>0%): Epichlorohydrin Ethylene oxide Lead Proposition 65 – Developmental Toxins (>0%): Ethylene oxide Lead

Risk Phrases:

Not Applicable

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be

caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.