

# SAFETY DATA SHEET

### Interlac 843 Olive Green

### Section 1. Identification

Interlac 843 Olive Green : GHS product identifier

**ADA012** : Product code

Professional application of coatings and inks : Identified uses

Industrial application of coatings and inks

### Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

International Paint Ltd. : Supplier's details

Stoneygate Lane

Felling Gateshead Tyne and Wear NE10 0JY UK

+966 55 388 0087

Tel: +44 (0)191 469 6111 Fax: +44 (0)191 438 3711

+44 (0)191 469 6111 (24H) : Emergency telephone

number (with hours of

operation)

: National advisory body/ Poison Centre (For use only

by licensed medical professionals.)

: e-mail address of person sdsfellinguk@akzonobel.com

responsible for this SDS

# Section 2. Hazards identification

FLAMMABLE LIQUIDS - Category 3 : Classification of the LONG-TERM AQUATIC HAZARD - Category 3 substance or mixture

**GHS** label elements

: Hazard pictograms

: Response

Warning : Signal word

Flammable liquid and vapour. : Hazard statements

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, : Prevention open flames and hot surfaces. - No smoking. Use explosion-proof electrical,

ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Avoid release to the environment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

Store in a well-ventilated place. Keep cool. : Storage

Date of issue/Date of revision : 06/08/2014.

Version: 1 1/11



## Section 2. Hazards identification

Dispose of contents and container in accordance with all local, regional, national and international regulations.

: Disposal

None known.

: Other hazards which do not result in classification

# Section 3. Composition/information on ingredients

Mixture : Substance/mixture

Classification	CAS number	% by weight	Ingredient name
STOT SE 3, H336 (Narcotic effects)	64742-82-1	>=15 - <20	Naphtha (petroleum), hydrodesulfurized heavy
Asp. Tox. 1, H304 Aquatic Chronic 2, H411			
Asp. Tox. 1, H304	64742-48-9	>=10 - <20	Naphtha (petroleum), hydrotreated heavy
Acute Tox. 4, H302 Skin Sens. 1, H317	27253-31-2	>=0.1 - <0.25	neodecanoic acid, cobalt salt
Repr. 2, H361 (Fertility) (oral)			
Aquatic Chronic 2, H411			
Acute Tox. 4, H312	96-29-7	>=0.1 - <1	2-butanone oxime
Eye Dam. 1, H318 Skin Sens. 1, H317			
Carc. 2, H351			

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

### **Description of necessary first aid measures**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

: Eye contact

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

: Inhalation

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

: Skin contact

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

: Ingestion

## Most important symptoms/effects, acute and delayed

Potential acute health effects

Date of issue/Date of revision : 06/08/2014.

Version: 1



: Eye contact

: Inhalation : Skin contact

: Ingestion

: Eye contact

: Inhalation

## Section 4. First-aid measures

No known significant effects or critical hazards. No known significant effects or critical hazards.

No known significant effects or critical hazards.

No known significant effects or critical hazards.

Over-exposure signs/symptoms

No specific data.

Adverse symptoms may include the following:

headache

drowsiness/fatigue

dizziness/vertigo

muscle weakness

unconsciousness

No specific data. : Skin contact

No specific data. : Ingestion

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

No specific treatment. : Specific treatments

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

No action shall be taken involving any personal risk or without suitable training. It : Protection of first-aiders

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### Extinguishing media

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

: Suitable extinguishing

: Notes to physician

media

Do not use water jet.

: Unsuitable extinguishing

media

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

: Specific hazards arising from the chemical

Decomposition products may include the following materials:

carbon dioxide carbon monoxide

metal oxide/oxides

: Hazardous thermal decomposition products

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

: Special protective actions for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Special protective equipment for fire-fighters

Date of issue/Date of revision Version: 1

: 06/08/2014.



### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

: For non-emergency personnel

: For emergency responders

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

: Environmental precautions

#### Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and : Small spill explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and : Large spill explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

: Protective measures

: Advice on general occupational hygiene



# Section 7. Handling and storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

: Conditions for safe storage, including any incompatibilities

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

None.

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

: Appropriate engineering controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

: Environmental exposure controls

### **Individual protection measures**

Wash hands, forearms and face thoroughly after handling chemical products, before : Hygiene measures eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

: Eye/face protection

#### **Skin protection**

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

: Hand protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

: Body protection



# Section 8. Exposure controls/personal protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

: Other skin protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

: Respiratory protection

## Section 9. Physical and chemical properties

**Appearance** 

Liquid. : Physical state

Green. : Colour Solvent. : Odour

Not available. : Odour threshold

Not applicable. : pH

Not available. : Melting point

Lowest known value: >142°C (>287.6°F)(Naphtha (petroleum), hydrodesulfurized : **Boiling point** 

heavy).

Closed cup: 36°C (96.8°F) : Flash point

Not available. : Evaporation rate

Not available. : Flammability (solid, gas)

Greatest known range: Lower: 0.7% Upper: 6.5% (Naphtha (petroleum), : Lower and upper explosive

hydrodesulfurized heavy) (flammable) limits

Not available. : Vapour pressure

Not available. : Vapour density

1.26 : Relative density

Insoluble in the following materials: cold water. : Solubility

Not available. : Partition coefficient: n-

octanol/water

Not available. : Auto-ignition temperature

Not available. : Decomposition temperature

Kinematic (room temperature): 504 mm²/s (504 cSt) : Viscosity

# Section 10. Stability and reactivity

No specific test data related to reactivity available for this product or its ingredients. : Reactivity

The product is stable. : Chemical stability

Under normal conditions of storage and use, hazardous reactions will not occur. : Possibility of hazardous

reactions

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

: Conditions to avoid

Reactive or incompatible with the following materials: : Incompatible materials

oxidizing materials

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

: Hazardous decomposition

products

Date of issue/Date of revision

Version : 1

: 06/08/2014.

AkzoNobel

6/11



# **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Exposure	Dose	Species	Result	Product/ingredient name
-	6000 mg/kg	Rat	LD50 Oral	Naphtha (petroleum),
				hydrotreated heavy
-	1098 mg/kg	Rat	LD50 Oral	neodecanoic acid, cobalt salt
-	1001 mg/kg	Rat	LD50 Dermal	2-butanone oxime

### Irritation/Corrosion

Observation	Exposure	Score	Species	Result	Product/ingredient name
-	100 microliters	-	Rabbit	Eyes - Severe irritant	2-butanone oxime

### **Sensitisation**

Not available.

### **Mutagenicity**

Not available.

### Carcinogenicity

Not available.

### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Target organs	Route of exposure	Category	Name
Narcotic effects	Not applicable.	Category 3	Naphtha (petroleum), hydrodesulfurized heavy

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Result	Name
	Naphtha (petroleum), hydrodesulfurized heavy Naphtha (petroleum), hydrotreated heavy

Not available. : Information on the likely

routes of exposure

Potential acute health effects

No known significant effects or critical hazards. : Eye contact

No known significant effects or critical hazards. : Inhalation

No known significant effects or critical hazards. : Skin contact

No known significant effects or critical hazards. : Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

No specific data. : Eye contact

Date of issue/Date of revision Version : 1 : 06/08/2014.



# **Section 11. Toxicological information**

Adverse symptoms may include the following:

headache

drowsiness/fatigue

dizziness/vertigo

muscle weakness

unconsciousness

No specific data. : Skin contact
No specific data. : Ingestion

## Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Not available. : Potential immediate

effects

: Inhalation

Not available. : Potential delayed effects

Long term exposure

Not available. : Potential immediate

effects

Not available. : Potential delayed effects

Potential chronic health effects

Not available.

No known significant effects or critical hazards. : General

No known significant effects or critical hazards. : Carcinogenicity

No known significant effects or critical hazards. : Mutagenicity

No known significant effects or critical hazards. : Teratogenicity

No known significant effects or critical hazards. : Developmental effects

No known significant effects or critical hazards. : Fertility effects

### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Not available.

# **Section 12. Ecological information**

### **Toxicity**

Exposure	Species	Result	Product/ingredient name
96 hours	·	Acute LC50 843000 to 914000 μg/l Fresh water	2-butanone oxime

### Persistence and degradability

Biodegradability	Photolysis	Aquatic half-life	Product/ingredient name
Not readily	-	-	Naphtha (petroleum),
			hydrodesulfurized heavy

#### **Bioaccumulative potential**

Date of issue/Date of revision Version : 1 : 06/08/2014.



# **Section 12. Ecological information**

Potential	BCF	LogPow	Product/ingredient name
high	10 to 2500	-	Naphtha (petroleum),
			hydrodesulfurized heavy
high	10 to 2500	-	Naphtha (petroleum),
			hydrotreated heavy
high	15600	<del>-</del>	neodecanoic acid, cobalt salt
low	5.011872336	0.63	2-butanone oxime

#### **Mobility in soil**

Not available. : Soil/water partition coefficient (Koc)

No known significant effects or critical hazards. : Other adverse effects

# Section 13. Disposal considerations

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

: Disposal methods

# **Section 14. Transport information**

IATA	IMDG	UN	
UN1263	UN1263	UN1263	UN number
PAINT	PAINT	PAINT	UN proper shipping name
3	3	3	Transport hazard class(es)
III	III	III	Packing group
No.	No.	No.	Environmental hazards
The environmentally hazardous substance mark may appear if required by other transportation regulations.	-	-	Additional information

Not applicable.

: IMDG Code Segregation group



# **Section 14. Transport information**

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Special precautions for user

Not available.

: Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

# Section 15. Regulatory information

No known specific national and/or regional regulations applicable to this product (including its ingredients).

: Safety, health and environmental regulations specific for the product

## **Section 16. Other information**

#### **Justification**

Justification	Classification
On basis of test data	Flam. Liq. 3, H226
Calculation method	Aquatic Chronic 3, H412

#### History

06/08/2014. : Date of printing

06/08/2014. : Date of issue/Date of

revision

: Key to abbreviations

No previous validation. : Date of previous issue

1 : Version

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Not available. : References

Indicates information that has changed from previously issued version.

#### Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Date of issue/Date of revision Version : 1 : 06/08/2014.



## **Section 16. Other information**

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

Date of issue/Date of revision Version : 1 : 06/08/2014.