

Safety Data Sheet  
 INTERLAC 800 BASE LIGHT

Sales  
 Order: {SalesOrd}  
 CQA011  
 01/28/2015  
 B2-3

Bulk Sales Reference No.:  
 SDS Revision Date:  
 SDS Revision Number:



1. Identification of the preparation and company

1.1. Product identifier

Product Identity INTERLAC 800 BASE LIGHT  
 Bulk Sales Reference No. CQA011

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.  
 Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC  
 6001 Antoine Drive  
 Houston, Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300  
 International Paint (713) 682-1711  
 Poison Control Center (800) 854-6813  
 Customer Service  
 International Paint (800) 589-1267  
 Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
 Skin Irrit. 3;H316 Causes mild skin irritation.  
 Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapor.

H316 Causes mild skin irritation.

H411 Toxic to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

## CQA011\_B2

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice/attention.

P370 In case of fire: Use water spray, fog, or regular foam..

P391 Collect spillage.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating                      Health: 2                      Flammability: 3                      Reactivity: 0

3. Composition/information on ingredients
---

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Titanium dioxide CAS Number: 0013463-67-7	10 - 25	----	[1][2]
Barium sulfate CAS Number: 0007727-43-7	10 - 25	----	[1][2]
Methyl n-amyl ketone CAS Number: 0000110-43-0	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
Petroleum naphtha CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304 Aquatic Chronic 2;H411 (Self Classification)	[1]
1,2,4-Trimethyl benzene CAS Number: 0000095-63-6	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Aquatic Chronic 2;H411	[1]
Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304	[1][2]
Methyl ethyl ketoxime CAS Number: 0000096-29-7	0.10 - 1.0	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]
Hexanoic acid, 2-ethyl-, cobalt(2+) salt CAS Number: 0000136-52-7	0.10 - 1.0	Acute Tox. 4;H302 Skin Sens. 1;H317 Repr. 2;H361F Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
Methanol CAS Number: 0000067-56-1	0.10 - 1.0	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

4. First aid measures
-----------------------

## 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

## 4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures
---------------------------

## 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

## 5.2. Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

## 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures
--------------------------------

## 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

## 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

## 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at

## CQA011\_B2

least 300 meters (1000 feet).

7. Handling and storage
-------------------------

### 7.1. Precautions for safe handling

#### Handling

Vapors may cause flash fire or ignite explosively.

#### In Storage

Keep away from heat, sparks and flame.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection
--

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000067-56-1	Methanol	OSHA	200 ppm TWA; 260 mg/m3 TWA250 ppm STEL; 325 mg/m3 STEL
		ACGIH	200 ppm TWA250 ppm STEL
		NIOSH	200 ppm TWA; 260 mg/m3 TWA250 ppm STEL; 325 mg/m3 STEL6000 ppm IDLH
		Supplier	
		OHSA, CAN	200 ppm TWA250 ppm STEL
		Mexico	200 ppm TWA LMPE-PPT; 260 mg/m3 TWA LMPE-PPT250 ppm STEL [LMPE-CT]; 310 mg/m3 STEL [LMPE-CT]
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	
		ACGIH	
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	
		OHSA, CAN	
		Mexico	
0000096-29-7	Methyl ethyl ketoxime	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
0000110-43-0	Methyl n-amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA

CQA011\_B2

		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL [LMPE-CT]
		Brazil	
0000136-52-7	Hexanoic acid, 2-ethyl-, cobalt(2+) salt	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	
		Supplier	
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA LMPE-PPT; 435 mg/m3 TWA LMPE-PPT150 ppm STEL [LMPE-CT]; 655 mg/m3 STEL [LMPE-CT]
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	
		OHSA, CAN	10 mg/m3 TWA
		Mexico	
		Brazil	
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)
		Brazil	
0064742-95-6	Petroleum naphtha	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	

Health Data

CAS No.	Ingredient	Source	Value
0000067-56-1	Methanol	NIOSH	Blindness metabolic acidosis
0000095-63-6	1,2,4-Trimethyl benzene	NIOSH	

CQA011\_B2

0000096-29-7	Methyl ethyl ketoxime	NIOSH	
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000136-52-7	Hexanoic acid, 2-ethyl-, cobalt(2+) salt	NIOSH	
0001330-20-7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant; respiratory and eye irritation
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0064742-95-6	Petroleum naphtha	NIOSH	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000096-29-7	Methyl ethyl ketoxime	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000136-52-7	Hexanoic acid, 2-ethyl-, cobalt(2+) salt	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

## CQA011\_B2

Skin	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties
-------------------------------------

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	64 (°C) 147 (°F)
Flash Point	36 (°C) 96 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.31
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

10. Stability and reactivity
------------------------------

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

### 10.3. Possibility of hazardous reactions

No data available

### 10.4. Conditions to avoid

No data available

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

**HIGHLY FLAMMABLE MATERIALS:** Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

## CQA011\_B2

## 11. Toxicological information

## Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
Methyl n-amyl ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rabbit - Category: NA	No data available	No data available
Petroleum naphtha - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
1,2,4-Trimethyl benzene - (95-63-6)	3,400.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	18.00, Rat - Category: 4	No data available
Xylenes (o-, m-, p- isomers) - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available
Methyl ethyl ketoxime - (96-29-7)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available
Hexanoic acid, 2-ethyl-, cobalt(2+) salt - (136-52-7)	1,220.00, Rabbit - Category: 4	5,000.00, Rat - Category: 5	No data available	No data available
Methanol - (67-56-1)	5,628.00, Rat - Category: NA	15,800.00, Rabbit - Category: NA	85.00, Rat - Category: NA	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## CQA011\_B2

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Methyl n-amyl ketone - (110-43-0)	131.00, Pimephales promelas	Not Available	Not Available
Petroleum naphtha - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
1,2,4-Trimethyl benzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	Not Available
Xylenes (o-, m-, p- isomers) - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Methyl ethyl ketoxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus
Hexanoic acid, 2-ethyl-, cobalt(2+) salt - (136-52-7)	Not Available	Not Available	Not Available
Methanol - (67-56-1)	100.00, Pimephales promelas	10,000.00, Daphnia magna	16.912 (96 hr), Ulva pertusa

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

Not Measured

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available

13. Disposal considerations
-----------------------------

#### 13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information
---------------------------

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

#### DOT (Domestic Surface Transportation)

DOT Proper Shipping Name PAINT

DOT Hazard Class 3

UN / NA Number UN 1263

DOT Packing Group III

#### IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name PAINT

IMDG Hazard Class 3

Sub Class 3

IMDG Packing Group III

CERCLA/DOT RQ 581 gal. / 6343 lbs.

System Reference 1  
Code

- 14.4. Packing group III
- 14.5. Environmental hazards  
IMDG Marine Pollutant: Yes ( Titanium dioxide )
- 14.6. Special precautions for user  
Not Applicable
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code  
Not Applicable

15. Regulatory information
----------------------------

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)  
Methanol (5000 lb final RQ; 2270 kg final RQ)  
Benzene, 1,2-dimethyl- (1000 lb final RQ; 454 kg final RQ)  
Benzene, 1,3-dimethyl- (1000 lb final RQ; 454 kg final RQ)  
Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

1,2,4-Trimethyl benzene  
Benzene, ethyl-  
Methanol  
Benzene, 1,2-dimethyl-  
Benzene, 1,3-dimethyl-  
Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

1,2,4-Trimethyl benzene  
Barium sulfate  
Methyl n-amyl ketone  
Titanium dioxide  
Xylenes (o-, m-, p- isomers)

Penn RTK Substances (>1%) :

1,2,4-Trimethyl benzene  
Barium sulfate  
Methyl n-amyl ketone  
Titanium dioxide  
Xylenes (o-, m-, p- isomers)

Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)

RCRA Status:  
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

1,2,4-Trimethyl benzene  
Barium sulfate  
Methyl n-amyl ketone

Titanium dioxide  
 Xylenes (o-, m-, p- isomers)  
 N.J. Special Hazardous Substances (>.01%) :  
 2-Butoxyethanol  
 Ethyl alcohol  
 Benzene, ethyl-  
 Methanol  
 BUTYL ACETATE  
 Benzene, 1,2-dimethyl-  
 Quartz  
 Benzene, 1,3-dimethyl-  
 Xylenes (o-, m-, p- isomers)  
 N.J. Env. Hazardous Substances (>.1%) :  
 1,2,4-Trimethyl benzene  
 Benzene, ethyl-  
 Methanol  
 Benzene, 1,2-dimethyl-  
 Benzene, 1,3-dimethyl-  
 Xylenes (o-, m-, p- isomers)  
 Proposition 65 - Carcinogens (>0%):  
 Ethyl alcohol  
 Benzene, ethyl-  
 Quartz  
 Titanium dioxide  
 Proposition 65 - Female Repro Toxins (>0%):  
 (No Product Ingredients Listed)  
 Proposition 65 - Male Repro Toxins (>0%):  
 (No Product Ingredients Listed)  
 Proposition 65 - Developmental Toxins (>0%):  
 Ethyl alcohol  
 Methanol

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.  
 H226 Flammable liquid and vapor.  
 H301 Toxic if swallowed.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H311 Toxic in contact with skin.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.

## CQA011\_B2

H361F Suspected of damaging fertility.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

End of Document