In accordance with the Standard for Classification and Labelling of Chemical Substance and Material Safety Data Sheet, Article 10 Paragraph

SAFETY DATA SHEET

INTERCRYL 700 SAND

Section 1. Chemical product and company identification

: INTERCRYL 700 SAND A. Product name

Product code : QYB125

B. Relevant identified uses of the substance or mixture and uses advised against

| Identified uses | | | |
|---|--------|--|--|
| Professional application of coatings and inks | | | |
| Uses advised against | Reason | | |
| All Other Uses | | | |

| C. Manufacturer | : International Farg AB Holmedalen 3 Aspereds Industriomrade SE-424 22 Angered Sweden |
|--|---|
| | Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530 |
| Emergency telephone number (with hours of operation) | : +46 8 33 12 31 |
| e-mail address of person responsible for this SDS | : sdsfellinguk@akzonobel.com |

Section 2. Hazards identification

A. Hazard classification

Symbol

- : SKIN SENSITIZATION Category 1 **CARCINOGENICITY - Category 2**
- B. GHS label elements, including precautionary statements .



| Signal word Hazard statements | | Warning May cause an allergic skin reaction. Suspected of causing cancer. |
|----------------------------------|---|---|
| Precautionary statements | | |
| Prevention | : | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Avoid breathing vapour. Contaminated work clothing should not be allowed out of the workplace. |
| Response | : | IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. |
| Storage | : | Store locked up. |
| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |

1



Section 2. Hazards identification

Supplemental label elements

: Wear appropriate respirator when ventilation is inadequate.

C. Other hazards which do : None known. not result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

| Ingredient name | Common name | CAS number | % | Classification |
|--|--|------------|-----------|---|
| titanium dioxide | Titanium dioxide | 13463-67-7 | ≥15 - <20 | Carc. 2, H351 |
| 2-(2-butoxyethoxy)ethanol | 2-(2-butoxyethoxy) ethanol | 112-34-5 | <10 | Eye Irrit. 2, H319 |
| 2-(2-methoxyethoxy)ethanol | 2-(2-methoxyethoxy) | 111-77-3 | <10 | Eye Irrit. 2, H319 |
| | ethanol | | | Repr. 2, H361 (Unborn child) |
| Poly(oxy-1,2-ethanediyl), α- sulfo-ω-(nonylphenoxy)-, branched, ammonium salt | ammomium nonylphenol sulfate | 68649-55-8 | <1 | Skin Irrit. 2, H315 |
| branched, annionium sait | | | | Eye Dam. 1, H318 Aquatic Chronic 2, H411 |
| ammonia | AMMONIA, AQUEOUS | 1336-21-6 | <10 | Skin Corr. 1, H314 |
| | (30% NH3) | | | Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | 5-chloro-2-methyl-3(2h)- isothiazolone mixt. with 2-methyl-3(2h)- isothiazolone | 55965-84-9 | <10 | Acute Tox. 3, H301 |
| | | | | Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

:



Section 4. First aid measures

| Α. | Eye contact | : | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|----|----------------------------|---|---|
| В. | Skin contact | : | Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| C. | Inhalation | : | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| D. | Ingestion | : | Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| E. | Notes to physician | : | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| | Specific treatments | : | No specific treatment. |
| | Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Firefighting measures

| Α. | Extinguishing media | | |
|----|--|---|---|
| | Suitable extinguishing media | : | Use an extinguishing agent suitable for the surrounding fire. |
| | Unsuitable extinguishing media | : | None known. |
| В. | Specific hazards arising from the chemical | : | In a fire or if heated, a pressure increase will occur and the container may burst. |
| | Hazardous thermal decomposition products | : | Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides |

:

Section 5. Firefighting measures

| C. | Special protective equipment for fire- fighters | : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |
|----|---|---|---|
| | Special precautions for fire-fighters | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

C. Methods and material for containment and cleaning up

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|-------------|---|
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

A. <u>Precautions for safe handling</u>

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

٠

Section 7. Handling and storage

B. Conditions for safe storage, including any incompatibilities
 Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

A. <u>Control parameters</u>

Occupational exposure limits

| Ingredient name | Exposure limits | | |
|---------------------------|--|--|--|
| titanium dioxide | Ministry of Labor (Republic of Korea, 8/2013). TWA: 10 mg/m ³ 8 hours. Form: total dust with less than 1% of free SiO2 | | |
| 2-(2-butoxyethoxy)ethanol | ACGIH TLV (United States, 3/2015). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor | | |

B. Appropriate engineering controls If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

| Respiratory protection | s t | Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
|------------------------|--|---|
| Eye protection | a Q L | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. |
| Hand protection | a V c r c r r f f V r r E E | Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. |



K.International.

Section 8. Exposure controls/personal protection

| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
|------------------|---|
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |

Section 9. Physical and chemical properties

| Α. | <u>Appearance</u> | | |
|----|--|---|--|
| | Physical state | : | Liquid. |
| | Colour | : | Various |
| В. | Odour | : | Ammonia. |
| C. | Odour threshold | : | Not available. |
| D. | рН | : | 9 |
| Ε. | Melting/freezing point | : | Not available. |
| F. | Boiling point/boiling range | : | Lowest known value: 100°C (212°F) (water). |
| G. | Flash point | : | Closed cup: 101°C (213.8°F) |
| | Fire point | 1 | Not available. |
| Н. | Evaporation rate | : | Not available. |
| I. | Flammability (solid, gas) | : | Not available. |
| J. | Lower and upper explosive (flammable) limits | : | Not available. |
| Κ. | Vapour pressure | : | Not available. |
| L. | Solubility | : | Insoluble in the following materials: cold water. |
| Μ. | Vapour density | : | Not available. |
| Ν. | Relative density | : | 1.18 |
| 0. | Partition coefficient: n- octanol/water | : | Not available. |
| Ρ. | Auto-ignition temperature | : | Not available. |
| Q. | Decomposition temperature | : | Not available. |
| R. | Viscosity | : | Kinematic (room temperature): 297 mm ² /s (297 cSt) |
| S. | Molecular weight | : | Not applicable. |
| | | | |

Section 10. Stability and reactivity

| Α. | Chemical stability | : | The product is stable. |
|----|------------------------------------|---|---|
| | Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| В. | Conditions to avoid | : | No specific data. |

C. Incompatible materials : No specific data.

:



X.International.

Section 10. Stability and reactivity

D. Hazardous : Und decomposition products shou

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

A. Information on likely : Not available. routes of exposure

| Potential acute health effects | | | | | | | |
|--------------------------------|---|--|--|--|--|--|--|
| Inhalation | : No known significant effects or critical hazards. | | | | | | |
| Ingestion | : No known significant effects or critical hazards. | | | | | | |
| Skin contact | : May cause an allergic skin reaction. | | | | | | |
| Eye contact | : No known significant effects or critical hazards. | | | | | | |
| Over-exposure signs/symptoms | | | | | | | |
| Inhalation | : No specific data. | | | | | | |
| Ingestion | : No specific data. | | | | | | |
| | | | | | | | |

| Skin contact | : Adverse symptoms may include the following: irritation redness |
|--------------|--|
| Eye contact | : No specific data. |

B. Health hazards

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-------------|---------|------------|----------|
| 2-(2-butoxyethoxy)ethanol | LD50 Dermal | Rabbit | 2700 mg/kg | - |
| | LD50 Oral | Rat | 4500 mg/kg | - |
| ammonia | LD50 Oral | Rat | 350 mg/kg | - |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- | LD50 Oral | Rat | 53 mg/kg | - |
| 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- | | | | |
| 3-one [EC no. 220-239-6] (3:1) | | | | |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--------------------------|---------|-------|---|-------------|
| titanium dioxide | Skin - Mild irritant | Human | - | 72 hours 300 Micrograms Intermittent | - |
| 2-(2-butoxyethoxy)ethanol | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 20 milligrams | - |
| 2-(2-methoxyethoxy)ethanol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 500 milligrams | - |
| ammonia | Eyes - Severe irritant | Rabbit | - | 250 Micrograms | - |
| | Eyes - Severe irritant | Rabbit | - | 0.5 minutes 1 milligrams | - |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] | Skin - Severe irritant | Human | - | 0.01 Percent | - |

:

X.International.

Section 11. Toxicological information

| 10 | | | ` |
|-----|---|---|---|
| 1.3 | • | 1 | ۱ |
| ιu | ٠ | | 1 |

Sensitisation

Not available.

CMR - ISHA Article 42 Public Notice No 2013-38 Occupational Exposure Limits

| Product/ingredient name | CAS number | Classification |
|-------------------------|------------|----------------|
| Titanium dioxide | 13463-67-7 | Carc. 2 |

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | · · · · · · · · | Route of exposure | Target organs |
|---------|-----------------|----------------------|------------------------------|
| ammonia | Category 3 | | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

Chronic toxicity

Not available.

| General | : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
|-----------------------|---|
| Carcinogenicity | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |

ATE value

:

| Route | Result | |
|--------|----------------|--|
| Oral | 116586 mg/kg | |
| Dermal | 253981.2 mg/kg | |

Section 12. Ecological information

A. Ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|----------------------------|-------------------------------------|---------------------------------|----------|
| 2-(2-butoxyethoxy)ethanol | Acute LC50 1300000 µg/l Fresh water | Fish - Lepomis macrochirus | 96 hours |
| 2-(2-methoxyethoxy)ethanol | Acute EC50 930 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 960 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| ammonia | Acute LC50 15000 μg/l Fresh water | Fish - Gambusia affinis - Adult | 96 hours |

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|----------------------------|--------|-----|-----------|
| titanium dioxide | - | 352 | low |
| 2-(2-butoxyethoxy)ethanol | 1 | - | low |
| 2-(2-methoxyethoxy)ethanol | -0.47 | - | low |

D. Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. **B.** Disposal precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of

spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | UN | IMDG | IATA |
|----------------------------------|----------------|----------------|----------------|
| A. UN number | Not regulated. | Not regulated. | Not regulated. |
| B. UN proper shipping name | - | - | - |
| C. Transport hazard class(es) | - | - | - |
| D. Packing group | - | - | - |
| | | | |

:

X.International.

Section 14. Transport information

| E. Environmental hazards | No. | No. | No. |
|---|-----|-----|-----|
| F. Additional information | - | - | - |
| IMDG Code Segregation : Not applicable. | | | |

group

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

| Α. | Regulation according to I | SH | <u>A</u> |
|----|---|-----|---|
| | ISHA article 37 (Harmful substances prohibited from manufacture) | : | The following components are listed: Nonylphenols and Nonylphenol ethoxylates |
| | ISHA article 38 (Harmful substances requiring permission) | : | None of the components are listed. |
| | Article 2 of Youth Protection Act on Substances Hazardous to Youth | : | Not applicable. |
| | Exposure Limits of Chem | ica | I Substances and Physical Factors |
| | The following components titanium dioxide 2-(2-butoxyethoxy)ethanol | | ave an OEL: |
| | ISHA Enforcement Regs Annex 11-3 (Exposure standards established for harmful factors) | : | None of the components are listed. |
| | ISHA Enforcement Regs Annex 11-4 (Harmful factors subject to Work Environment Measurement) | : | The following components are listed: Titanium dioxide |
| | ISHA Enforcement Regs Annex 12-2 (Harmful Factors Subject to Special Health Check- up) | : | None of the components are listed. |
| | Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control) | : | The following components are listed: Titanium dioxide |
| В. | Regulation according to C | h | emicals Control Act |
| | K-Reach Article 20 (Toxic chemicals) | | Not applicable |
| | K-Reach Article 27 (Prohibited) | : | None of the components are listed. |

:

Section 15. Regulatory information

| | • | | |
|----|---|-----|---|
| | K-Reach Article 27 (Restricted) | : | The following components are listed: Nonylphenols and Nonylphenol ethoxylates |
| | CSCA Article 11 (TRI) | : | The following components are listed: Barium and its compounds |
| | Korea inventory | : | Not determined. |
| | CSCA Article 39 (Accident Precaution Chemicals) | : | None of the components are listed. |
| C. | Dangerous Materials Safety Management Act | : | Not available. |
| D. | Wastes regulation | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Ε. | Regulation according to | oth | ner foreign laws |
| | Europe inventory | : | Not determined. |
| | United States inventory (TSCA 8b) | : | Not determined. |
| | Japan inventory | : | Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined. |

Section 16. Other information

| Α. | References | : | Not available. |
|----|--------------------------------|---|----------------|
| В. | Date of issue/Date of revision | : | 30/05/2017 |
| С. | Version | : | 3 |
| | Date of printing | : | 30/05/2017 |

D. Other

Indicates information that has changed from previously issued version.

| Key to abbreviations | : ATE = Acute Toxicity Estimate |
|----------------------|---|
| | BCF = Bioconcentration Factor |
| | GHS = Globally Harmonized System of Classification and Labelling of Chemicals |
| | IATA = International Air Transport Association |
| | IBC = Intermediate Bulk Container |
| | IMDG = International Maritime Dangerous Goods |
| | LogPow = logarithm of the octanol/water partition coefficient |
| | MARPOL = International Convention for the Prevention of Pollution From Ships, |
| | 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) |
| | UN = United Nations |
| | |

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

•



X International

Section 16. Other information

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel

: