

: GHS product identifier

# **SAFETY DATA SHEET**

### Intersleek 1100SR DUO Blue Part A

### Section 1. Identification

Intersleek 1100SR DUO Blue Part A

FXA292 : Product code

Identified uses			
Professional application of coatings and inks			
Uses advised against	Reason		
All Other Uses			

International Paint Ltd.

Stoneygate Lane

Felling Gateshead Tyne and Wear NE10 0JY UK

Tel: +44 (0)191 469 6111 Fax: +44 (0)191 438 3711

+44 (0)191 469 6111 (24H) : Emergency telephone

number (with hours of

operation)

+966 55 388 0087 : <u>National advisory body/</u>

Poison Centre (For use only by licensed medical

professionals.)

: Supplier's details

sdsfellinguk@akzonobel.com : e-mail address of person responsible for this SDS

### Section 2. Hazards identification

FLAMMABLE LIQUIDS - Category 3

SKIN CORROSION/IRRITATION - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

LONG-TERM AQUATIC HAZARD - Category 2

: Classification of the substance or mixture

#### **GHS label elements**







: Hazard pictograms

**AkzoNobel** 

Warning

Flammable liquid and vapour.
Causes mild skin irritation.
May cause respiratory irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Date of issue/Date of revision : 05/12/2017

Version: 2



### Section 2. Hazards identification

Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapour.

Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs: Get medical attention.

Store locked up. Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Wear appropriate respirator when ventilation is inadequate.

Prevention

: Response

: Storage: Disposal

: Supplemental label

elements

None known.

: Other hazards which do not result in classification

### Section 3. Composition/information on ingredients

Mixture : Substance/mixture

Classification	CAS number	% by weight	Ingredient name
Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	64742-95-6	≥25 - ≤50	Solvent naphtha (petroleum), light arom.
Skin Irrit. 2, H315 Eye Irrit. 2A, H319	35501-23-6	<10	N,N-Dibutylaminomethyl-triethoxysilane

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If irritation persists, get medical attention.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if adverse health effects persist or are severe. Wash clothing before reuse. Clean shoes thoroughly before reuse.

: Eye contact

: Inhalation

: Skin contact

Date of issue/Date of revision Version : 2 : 05/12/2017



### Section 4. First aid measures

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

: Ingestion

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

No known significant effects or critical hazards. : Eye contact

Can cause central nervous system (CNS) depression. May cause drowsiness or : Inhalation

dizziness. May cause respiratory irritation.

Causes mild skin irritation. : Skin contact

Can cause central nervous system (CNS) depression. Irritating to mouth, throat and : Ingestion

stomach.

Over-exposure signs/symptoms

Adverse symptoms may include the following: : Eye contact

pain or irritation watering

redness

Adverse symptoms may include the following: : Inhalation

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue

dizziness/vertigo

muscle weakness

unconsciousness

Adverse symptoms may include the following: : Skin contact

irritation redness

No specific data. : Ingestion

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Contact poison treatment specialist immediately if large : Notes to physician

quantities have been ingested or inhaled.

No specific treatment. : Specific treatments

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person

providing aid to give mouth-to-mouth resuscitation.

: Protection of first-aiders

See toxicological information (Section 11)

Date of issue/Date of revision Version : 2 : 05/12/2017



## **Section 5. Firefighting measures**

#### **Extinguishing media**

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Do not use water jet.

: Suitable extinguishing media

: Unsuitable extinguishing media

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

: Specific hazards arising from the chemical

Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

: Hazardous thermal decomposition products

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Fire-fighters should wear appropriate protective equipment and self-contained

: Special protective actions for fire-fighters

breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Special protective equipment for fire-fighters

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

: For non-emergency personnel

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

: For emergency responders

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

: Environmental precautions

#### Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and : Small spill explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and : Large spill explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision

Version: 2

: 05/12/2017



## Section 7. Handling and storage

#### Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

: Protective measures

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

: Advice on general occupational hygiene

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

: Conditions for safe storage, including any incompatibilities

### Section 8. Exposure controls/personal protection

#### Control parameters

#### Occupational exposure limits

None.

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

: Appropriate engineering controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

: Environmental exposure controls

#### **Individual protection measures**

Wash hands, forearms and face thoroughly after handling chemical products, before : Hygiene measures eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

: Eye/face protection

**Skin protection** 

Date of issue/Date of revision Version: 2

: 05/12/2017



## Section 8. Exposure controls/personal protection

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

: Hand protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

: Body protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

: Other skin protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

: Respiratory protection

### Section 9. Physical and chemical properties

#### <u>Appearance</u>

Liquid. : Physical state

Blue. : Colour

Solvent. : Odour

Not available. : Odour threshold

Not applicable. : pH

Not available. : Melting point

Lowest known value: 140 to 200°C (284 to 392°F)(Solvent naphtha (petroleum), : **Boiling point** light arom.).

Closed cup: 34°C (93.2°F) : Flash point

Not available. : Evaporation rate

Not available. : Flammability (solid, gas)

Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), : Lower and upper explosive

light arom.) (flammable) limits

Not available. : Vapour pressure

Not available. : Vapour density

0.99 : Relative density Insoluble in the following materials: cold water. : Solubility

Not available. : Partition coefficient: noctanol/water

Not available. : Auto-ignition temperature

Not available. : Decomposition temperature

Kinematic (room temperature): 505.1 mm²/s (505.1 cSt) : Viscosity

Date of issue/Date of revision : 05/12/2017

**Version** : 2 6/11



## Section 10. Stability and reactivity

No specific test data related to reactivity available for this product or its ingredients. : Reactivity

The product is stable. : Chemical stability

Under normal conditions of storage and use, hazardous reactions will not occur. : Possibility of hazardous

reactions

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

: Conditions to avoid

Reactive or incompatible with the following materials:

oxidizing materials

: Incompatible materials

Under normal conditions of storage and use, hazardous decomposition products

: Hazardous decomposition products

should not be produced.

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Exposure	Dose	Species	Result	Product/ingredient name
-	8400 mg/kg	Rat	LD50 Oral	Solvent naphtha (petroleum), light arom.

#### Irritation/Corrosion

Observation	Exposure	Score	Species	Result	Product/ingredient name
-	24 hours 100	-	Rabbit	Eyes - Mild irritant	Solvent naphtha (petroleum),
	microliters				light arom.

#### **Sensitisation**

Not available.

#### **Mutagenicity**

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Target organs	Route of exposure	Category	Name
Respiratory tract irritation and Narcotic effects	Not applicable.	Category 3	Solvent naphtha (petroleum), light arom.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

: 05/12/2017 Version: 2 7/11



# **Section 11. Toxicological information**

Result	Name
ASPIRATION HAZARD - Category 1	Solvent naphtha (petroleum), light arom.

Not available. : Information on likely routes

of exposure

Potential acute health effects

No known significant effects or critical hazards. : Eye contact

Can cause central nervous system (CNS) depression. May cause drowsiness or : Inhalation

dizziness. May cause respiratory irritation.

Causes mild skin irritation. : Skin contact

Can cause central nervous system (CNS) depression. Irritating to mouth, throat and : Ingestion

stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Adverse symptoms may include the following: : Eye contact

pain or irritation

watering redness

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo

muscle weakness unconsciousness

Adverse symptoms may include the following:

irritation

redness

No specific data. : Ingestion

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Not available. : Potential immediate

effects

: Inhalation

: Skin contact

Not available. : Potential delayed effects

Long term exposure

Not available. : Potential immediate

effects

Not available. : Potential delayed effects

Potential chronic health effects

Not available.

No known significant effects or critical hazards. : General

No known significant effects or critical hazards. : Carcinogenicity

No known significant effects or critical hazards. : Mutagenicity

No known significant effects or critical hazards. : Teratogenicity

No known significant effects or critical hazards. : Developmental effects

No known significant effects or critical hazards. : Fertility effects

**Numerical measures of toxicity** 

Date of issue/Date of revision : 05/12/2017

Version: 2 8/11



### **Section 11. Toxicological information**

#### **Acute toxicity estimates**

Not available.

## **Section 12. Ecological information**

#### **Toxicity**

Exposure	Species	Result	Product/ingredient name
48 hours	Daphnia	Acute EC50 6.14 mg/m³	Solvent naphtha (petroleum), light arom.
96 hours	Fish - Mykiss	Acute LC50 9.22 mg/m³	

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Not available.

: Soil/water partition coefficient (Koc)

No known significant effects or critical hazards.

: Other adverse effects

## **Section 13. Disposal considerations**

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

: Disposal methods

## **Section 14. Transport information**

IATA	IMDG	UN	
UN1263	UN1263	UN1263	UN number
Paint	PAINT. Marine pollutant (Solvent naphtha (petroleum), light arom.)	PAINT	UN proper shipping name

Date of issue/Date of revision

Version: 2

: 05/12/2017



# **Section 14. Transport information**

3	3	3	Transport hazard class(es)
III	III	III	Packing group
No.	Yes.	No.	Environmental hazards
The environmentally hazardous substance mark may appear if required by other transportation regulations.  Passenger and Cargo AircraftQuantity limitation: 60 L Packaging instructions: 355 Cargo Aircraft OnlyQuantity limitation: 220 L Packaging instructions: 366 Limited Quantities - Passenger AircraftQuantity limitation: 10 L Packaging instructions: Y344  Special provisions A3, A72, A192	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  Emergency schedules (EmS) F-E, _S-E_  Special provisions 163, 223, 367, 955	Special provisions 163, 223, 367	Additional information

Not applicable. : IMDG Code Segregation group

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Special precautions for user

Not available.

: Transport in bulk according to Annex II of Marpol and the IBC Code

# **Section 15. Regulatory information**

No known specific national and/or regional regulations applicable to this product (including its ingredients).

 Safety, health and environmental regulations specific for the product

# **Section 16. Other information**

#### **Justification**

Justification	Classification
On basis of test data	Flam. Liq. 3, H226
Calculation method	Skin Irrit. 3, H316
Calculation method	STOT SE 3, H335
Calculation method	STOT SE 3, H336
Calculation method	Aquatic Chronic 2, H411

**History** 

05/12/2017 : Date of printing

Date of issue/Date of revision : 05/12/2017

Version : 2 10/11



: Key to abbreviations

### **Section 16. Other information**

05/12/2017 : Date of issue/Date of

revision

02/08/2017 : Date of previous issue

2 : Version

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

Not available. : References

Indicates information that has changed from previously issued version.

#### **Notice to reader**

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

Date of issue/Date of revision Version : 2 : 05/12/2017