Material Safety Data Sheet INTERTHANE 990HS FS30045 DARK BROWN PT A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: Sales Order: {SalesOrd} PCP07W 03/02/2012 A2-4

XInternational.

1	 Identification 	of	the	pre	paratio	on and	com	pany	/

2.1	Hazard identification of the product		
Fax No.	(800) 631–7481		
International Paint	(800) 589–1267		
Customer Service			
Poison Control Center (800) 854–6813			
International Paint (713) 682–1711			
CHEMTREC (USA) (800) 424–9300			
Emergency			
	Houston Texas 77091		
	6001 Antoine Drive		
Company Name	International Paint LLC		
Bulk Sales Reference No.	PCP07W		
Product Identity	INTERTHANE 990HS FS30045 DARK BROWN PT A		



GHS Classification;		
Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	central nerve system
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung, respiratory system
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable

GHS Classification;

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Not Applicable

Overview	Overview NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.						
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.						
Eyes	Eyes Causes severe eye irritation. Avoid contact with eyes.						
Skin	Causes skin irritation. May be harmful if absorbed through the skin.						
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.						
Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.							
HMIS Rating	HMIS Rating Health: 2 Flammability: 2 Reactivity: 0 PPE: X						
	3. Composition/information on ingredients						

CAS No.	Percent	
0000095-63-6	1.0 – 10	
0000110-43-0	1.0 – 10	
0000123-86-4	1.0 – 10	
0000763-69-9	1.0 – 10	
0001309-37-1	1.0 – 10	
0001332-58-7	1.0 – 10	
0001333-86-4	0.10 – 1.0	
0007727-43-7	25 – 50	
0013463–67–7	1.0 – 10	
0064742-95-6	1.0 – 10	
	0000095-63-6 0000110-43-0 0000123-86-4 0000763-69-9 0001309-37-1 0001332-58-7 0001333-86-4 0007727-43-7 0013463-67-7	$\begin{array}{cccccc} 0000095-63-6 & 1.0 - 10 \\ 0000110-43-0 & 1.0 - 10 \\ 0000123-86-4 & 1.0 - 10 \\ 0000763-69-9 & 1.0 - 10 \\ 0001309-37-1 & 1.0 - 10 \\ 0001332-58-7 & 1.0 - 10 \\ 0001333-86-4 & 0.10 - 1.0 \\ 0007727-43-7 & 25 - 50 \\ 0013463-67-7 & 1.0 - 10 \end{array}$

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.			
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.		
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.		
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.		
Ingestion	If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.		
	5. Fire-fighting measures		

	5. Fire–fighting measures				
Flash Point	F: 100 C: 38				
Lower Explosive Limit (LEL) ERG Guide No.	1 (%vol in air) at Normal Atmospheric Temp and Pressure 128				

	6. Accidental release measures
Spill Response Procedures	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.
Public Safety	CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).
ERG Guide No.	128
	7. Handling and storage

Storage TemperatureStore between 40–100F (4–38C).Handling and Storage
PrecautionsKeep away from heat, sparks and flame. Do not smoke. Extinguish all flames and
pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition
during use and until all vapors are gone. Vapors may cause flash fire or ignite
explosively. Prevent build–up of vapors by opening all windows and doors to achieve
cross–ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated
contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

i		Exposi	
CAS No.	Ingredient	Source	Value
0000095–63–6	1,2,4–Trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000110-43-0	Methyl n–amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA; 235 mg/m3 TWA100 ppm STEL; 46 mg/m3 STEL
		Brazil	No Established Limit
0000123-86-4	BUTYL ACETATE	OSHA	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH	150 ppm TWA200 ppm STEL
		NIOSH	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	150 ppm TWA200 ppm STEL
		Mexico	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		Brazil	No Established Limit
0000763-69-9	Ethyl 3-ethoxypropionate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

		Supplier	No Established Limit
		OHSA, CAN	50 ppm TWA; 300 mg/m3 TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0001309-37-1	Iron oxide	OSHA	10 mg/m3 TWA (fume)
		ACGIH	5 mg/m3 TWA (respirable fraction)
		NIOSH	5 mg/m3 TWA (dust and fume, as Fe)2500 mg/m
			IDLH (dust and fume, as Fe)
		Supplier	No Established Limit
		OHSA, CAN	5 mg/m3 TWA (respirable)
		Mexico	5 mg/m3 TWA10 mg/m3 STEL (as Fe)
		Brazil	No Established Limit
0001332-58-7	Kaolin	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA
			(respirable fraction)
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	10 mg/m3 TWA20 mg/m3 STEL
		Brazil	No Established Limit
0001333-86-4	Carbon black	OSHA	3.5 mg/m3 TWA
		ACGIH	3.5 mg/m3 TWA
l		NIOSH	3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black presence of Polycyclic aromatic hydrocarbons, as1750 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA,	3.5 mg/m3 TWA
		CAN	2 5 mg/m2 TW/A7 mg/m2 STEL
		Mexico	3.5 mg/m3 TWA7 mg/m3 STEL No Established Limit
0007727-43-7	Devices excitence	Brazil OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA
0007727-43-7	Danum sunale	0314	(respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463_67_7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		CAN Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
0064742-95-6	Petroleum naphtha	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA,	No Established Limit
	1	CAN	1

Mexico	No Established Limit
Brazil	No Established Limit

Health Data CAS No. Ingredient Source Value NIOSH No Established Limit 0000095–63–6 1,2,4–Trimethyl benzene 0000110-43-0 Methyl n-amyl ketone NIOSH Irritation; liver kidney 0000123-86-4 BUTYL ACETATE NIOSH Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals 0000763–69–9 Ethyl 3–ethoxypropionate NIOSH No Established Limit 0001309-37-1 Iron oxide NIOSH Benign pneumoconiosis termed siderosis 0001332–58–7 Kaolin NIOSH Skin and mucous membrane injury respiratory effects 0001333-86-4 Carbon black NIOSH Lung cardiovascular 0007727-43-7 Barium sulfate NIOSH Eye nose 0013463-67-7 Titanium dioxide NIOSH Lung tumors in animals 0064742–95–6 Petroleum naphtha NIOSH No Established Limit

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4–Trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl n–amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000763–69–9	Ethyl 3-ethoxypropionate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001309–37–1	Iron oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001332–58–7	Kaolin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001333-86-4	Carbon black	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No

1	NTP Known: No; Suspected: No			
	IARC Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;			
	Group 4: No;			
Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.			
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.			
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.			
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.			
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.			
	9. Physical and chemical properties			
Physical State	Liquid Coloured			
pH	No Established Limit			
Specific Gravity	1.55			
Boiling Point F	230			
Vapor Density	Heavier than air			
VOC % Evaporation Rate	Refer to the Technical Data Sheet or label where information is available. Slower than ether			
	10. Stability and reactivity			

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decompostion	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
1,2,4-Trimethyl benzene – (0000095-63-6)	3,400.00, Rat – Category: 5	3,160.00, Rabbit - Category: 5	
Methyl n-amyl ketone - (0000110-43-0)	1,670.00, Rat – Category: 4		
BUTYL ACETATE – (0000123–86–4)	10,768.00, Rat – Category: NA	17,600.00, Rabbit – Category: NA	
Ethyl 3-ethoxypropionate - (0000763-69-9)			

	3,200.00, Rat – Category: 5		
Iron oxide – (0001309–37–1)	10,000.00, Rat – Category: NA		
Kaolin – (0001332–58–7)			
Carbon black – (0001333–86–4)	15,400.00, Rat – Category: NA	3,000.00, Rabbit - Category: 5	
Barium sulfate – (0007727–43–7)			
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA
Petroleum naphtha - (0064742-95-6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit - Category: 4	5.20, Rat – Category: 3

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

	14. Transpo	rt information				
DOT (Domestic Su	Irface Transportation)	IMO / IMDG (Oc	ean Transportation)			
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	· ,			
DOT Hazard Class	3	IMDG Hazard Class	3 – Flammable and Combustible liquid			
UN / NA Number	UN 1263	UN / NA Number	UN 1263			
DOT Packing Group	III	IMDG Packing Group	III			
CERCLA/DOT RQ	3781 gal. / 48704 lbs.	System Reference Code	2			
15. Regulatory information						
selected regulations are represented. All ingredients of this product are on the TSCA (Toxic Substance Control Act) Inventory or are not require listed on the TSCA Inventory. WHMIS Classification B2:D2B						
DOT Marine Pollutants (No Product Ingre	(10%):					
DOT Severe Marine Po	,					
(No Product Ingre	()					
EPCRA 311/312 Chem	icals and RQs (>.1%) :					
BUTYL A	CETATE (5000 lb final RQ; 2	270 kg final RQ)				
Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)						
EPCRA 302 Extremely (No Product Ingre						
EPCRA 313 Toxic Cher	EPCRA 313 Toxic Chemicals (>.1%):					
1,2,4–Trimethyl benzene						
1–Methyl–2–pyrrolidone						
Xylenes (o–, m–, p– isomers)						
Mass RTK Substances (>1%) :						

1,2,4-Trimethyl benzene Barium sulfate Iron oxide Kaolin Methyl n-amyl ketone BUTYL ACETATE Titanium dioxide Mass Extraordinarily Haz Sub (>.01%) : Quartz Penn RTK Substances (>1%) : 1,2,4-Trimethyl benzene Barium sulfate Iron oxide Kaolin Methyl n-amyl ketone **BUTYL ACETATE** Titanium dioxide Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%) : Carbon black Iron oxide Kaolin Methyl n-amyl ketone **BUTYL ACETATE** Titanium dioxide Xylenes (o-, m-, p- isomers) RCRA Status: (No Product Ingredients Listed) N.J. RTK Substances (>1%) : 1,2,4–Trimethyl benzene Barium sulfate Iron oxide Kaolin Methyl n-amyl ketone BUTYL ACETATE Titanium dioxide N.J. Special Hazardous Substances (>.01%) : 1-Methyl-2-pyrrolidone Carbon black Cumene Benzene, ethyl-BUTYL ACETATE Quartz Solvent naphtha (petroleum), medium aliphatic Benzene, methyl-Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%) : 1,2,4-Trimethyl benzene 1-Methyl-2-pyrrolidone Xylenes (o-, m-, p- isomers) Proposition 65 – Carcinogens (>0%): Carbon black Cumene Benzene, ethyl-Formaldehyde Nickel

Quartz Proposition 65 – Female Repro Toxins (>0%): Benzene, methyl– Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): 1–Methyl–2–pyrrolidone Benzene, methyl–

Risk Phrases:

Not Applicable

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.