TLA852\_A1

TLA852

A1

09/29/2013

Safety Data Sheet INTERLINE 850 BUFF PART A Bulk Sales Reference No.: SDS Revision Date: SDS Revision Number:

X.International.

1 Identification of the	preparation and company				
1.1. Product identifier	sieparation and company				
Product Identity	INTERLINE 850 BUFF PART A				
Bulk Sales Reference Number	TLA852				
1.2. Relevant identified uses of the substance or mixtu	ure and uses advised against				
ended Use See Technical Data Sheet.					
Application Method	See Technical Data Sheet.				
1.3. Details of the supplier of the safety data sheet					
Company Name	International Paint Ltda				
	ARGENTINA:				
	Ruta Panamericana Km 37,5				
	Garin, Buenos Aires PO Box: B1606DQE				
	AKZONOBEL CHILE:				
	Calle Limache 3363 Local 3, El Salto				
	Viña del Mar, Chile				
	C.P. 2520642 - Rut 76.048140-8				
	BRAZIL: Avenida Paiva, 999 - Neves				
	Sao Goncalo, RJ				
	24426-148 Brazil				
Emergency					
Suatrans Cotec	0800 7071 767 or 0800 7077 022 or 0800 172020 or				
	55*2*7500 (24 hr)				
International Paint	ARGENTINA:				
	+54 3327 44 7777				
	CHILE: +56 32 267 1174				
	BRAZIL:				
	+55 21 2199-7100				
Poison Control Center (Brazil)	0800-0148110 or +55 11 3069-8800				
Medical Service (Argentina)	+54 3327 44 7144 or +54 3327 44 7282				
Firefighter/HSE (Argentina)	+54 3327 44 7123				
Customer Service	ARGENTINA: +54 3327 44 7777 Fax: +54 3327 44 7738				
	CHILE: +56 32 267 1174 Fax: +56 32 263 1496				
	BRAZIL:				
O Horord identifi	+55 21 2199-7100 Fax: +55 21 2199-7124				

2.1. Classification of the substance or mixture Flam. Liq. 3;H226 Skin Irrit. 3;H316 Aquatic Chronic 3;H412

2.2. Label elements Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapour.

H316 Causes mild skin irritation.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapours / spray.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice/attention.

P333 If skin irritation or a rash occurs:.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations Weight %				
Talc CAS Number: 0014807-96-6	25 - 50			
Nepheline syenite CAS Number: 0037244-96-5	25 - 50			
Reaction of epichlorohydrin and bisphenol A CAS Number: 0025085-99-8	10 - 25			
Methyl isoamyl ketone CAS Number: 0000110-12-3	1.0 - 10			
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10			
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER CAS Number: 0028064-14-4	1.0 - 10			
Petroleum naphtha CAS Number: 0064742-95-6	1.0 - 10			
1,2,4-Trimethyl benzene CAS Number: 0000095-63-6	1.0 - 10			

4. First aid measures	
-----------------------	--

4.1. Description of first aid measures

1.1. Beeenption of mo	
General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	

	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything
	by mouth to an unconscious person.
4.2. Most important sym	nptoms and effects, both acute and delayed
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.
	5. Fire-fighting measures
5.1. Extinguishing media	
Appropriate Extinguishing Methods	Water in form of fog, Co2, foam or dry chemical dust.
Inappropriate Extinguishing Methods	Direct water spray into fire
Specific Hazards	Can liberate toxic fumes or gases during the burning. For decomposition see section 10.
5.2. Special hazards ari	sing from the substance or mixture
Special Methods	Evacuate the area and to fight the fire at a safe distance upwind. Use water in fog to cool containers near the fire. Keep runoff from entering sewer. Extinguishing water must be disposed according to local legislation.
5.3. Advice for fire-fighte	ers
Firefighter Protection	In fire case, to use personal respiratory device and suits for protection.
	6. Accidental release measures
6.1. Personal precaution	ns, protective equipment and emergency procedures
Personal precautions	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material.
Public Safety	Call Suatrans Cotec 0800 7071 767 or 0800 7077 022 or 0800 17 2020 or 55*2*7500 (24 hr) for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.
6.2. Environmental prec	autions
Environmental Precations	Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.
6.3. Methods and mater	rial for containment and cleaning up
	U - F
Clean Up Method	Cover with sand or other non-cumbustible material. Transfer absorbed material with a non-sparking tool.

7.1. Precautions for safe handling

Handle the packages with care in order to avoid damage and spillage.

Be aware of the precautions referred to on the label.

Avoid contact with the eyes and the skin. Avoid swallowing of vapor and the pulverizations. Be aware of the precautions referred to on the label. Use personal protection equipment according to the section 8. No smoking, drinking or eating in the application areas.

All the ignition sources (hot surfaces, sparks, unprotected flames, etc.) must be excluded from the areas of manufacturing and application. The storage areas, the preparation and the application must be well ventilated.

The product can be carried electrostatically. Always use grounding cables when transferring solvents or product. The operators must use adequate outfits which shall not develop static current. (at least 60% of natural fiber) and anti-static shoes.

Solvents based products: The solvent vapors are heavier than the air and can concentrate on the floor and explosive mixtures may be formed with the air .

Water based products: It does not require special cares for not being inflammable or explosive. Use only the indicated personal protection equipments.

7.2. Conditions for safe storage, including any incompatibilities Store between 40-100F (4-38C).

	8. Exposure	controls an	d personal protection				
	8.	1. Control p	parameters				
		Expos	ure				
CAS No.	. Ingredient Source Value						
0000095-63-6	1,2,4-Trimethyl benzene	ACGIH					
		Brazil					
0000110-12-3	Methyl isoamyl ketone	ACGIH	20 ppm TWA50 ppm STEL				
		Brazil					
0013463-67-7	Titanium dioxide	ACGIH	10 mg/m3 TWA				
		Brazil					
0014807-96-6 Talc		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and				
		Brazil					
0025085-99-8	Reaction of epichlorohydrin	ACGIH					
and bisphenol A		Brazil					
0028064-14-4 PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER		ACGIH					
		Brazil					
0037244-96-5 Nepheline syenite		ACGIH					
		Brazil					
0064742-95-6	Petroleum naphtha	ACGIH					
		Brazil					

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	NIOSH	
0000110-12-3	Methyl isoamyl ketone	NIOSH	Irritation; liver kidney
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0014807-96-6	Talc		(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0025085-99-8	Reaction of epichlorohydrin and bisphenol A	NIOSH	
	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	NIOSH	
0037244-96-5	Nepheline syenite	NIOSH	
0064742-95-6	Petroleum naphtha	NIOSH	

Carcinogen Data				
CAS No.	Ingredient	Source	Value	
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0000110-12-3	Methyl isoamyl ketone	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;		
0014807-96-6	Talc	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;		
0025085-99-8	Reaction of	OSHA	Select Carcinogen: No		
	epichlorohydrin and	NTP	Known: No; Suspected: No		
	bisphenol A	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0028064-14-4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0037244-96-5	Nepheline syenite	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		

#### 8.2. Exposure controls

Respiratory Protection	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.				
Eye and face protection	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 8 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.				
Skin and body protection	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 8 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.				
Engineering Controls	Prevent build-up of cross-ventilation.	vapors by opening all windows and doors to achieve			
Special Precations	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.				
	9. Phy	vsical and chemical properties			
Appearance		Beige Liquid			
Odour threshold		Not Measured			
рН		No Established Limit			
Melting point / freezing	point	Not Measured			
Initial boiling point and b	ooiling range	100 (°C) 212 (°F)			
Flash Point		42 (°C) 108 (°F)			
Evaporation rate (Ether = 1)		Not Measured			
Flammability (solid, gas)		Not Applicable			
Upper/lower flammabilit	y or explosive limits	Lower Explosive Limit: 1			
		Upper Explosive Limit: No Established Limit			
Vapour pressure (Pa)		Not Measured			

Vapor Density	Heavier than air
Specific Gravity	1.72
Solubility in Water	
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit
VOC %	Refer to the Technical Data Sheet or label where information is available.

10.1. Reactivity

10. Stability and reactivity

ctivity

Keep away from alkaline or strong strong acid to prevent probable exothermal reactions.

10.2. Chemical stability

This product is stable

10.3. Possibility of hazardous reactions

Dangerous Polymerization will not occur. Heat and vapors in excess can be generated when inproperly used.

10.4. Conditions to avoid

Keep away from alkaline or strong strong acid to prevent probable exothermal reactions.

Strong oxidizing agents

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Can liberate toxic vapors in the welding process. The vapors can produce Dioxide and Monoxide of Carbon. 11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 3 and 8 for chemical specific data.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	
Talc - (14807-96-6)	No data available	No data available	No data available	No data available	
Nepheline syenite - (37244-96-5)	No data available	No data available	No data available	No data available	
Reaction of epichlorohydrin and bisphenol A - (25085-99-8)	No data available	No data available	No data available	No data available	
Methyl isoamyl ketone - (110-12-3)	3,200.00, Rat - Category: 5	8,110.00, Rabbit - Category: NA	No data available	No data available	
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA	
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER - (28064-14-4)	2,000.00, Rat - Category: 4	No data available	No data available	No data available	
Petroleum naphtha - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available	
1,2,4-Trimethyl benzene - (95-63-6)	3,400.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	18.00, Rat - Category: 4	No data available	

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable

Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)		Not Applicable
Sensitization (skin)		Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity		Not Applicable
Reproductive Toxicity		Not Applicable
Specific target organ systemic toxicity (single exposure)		Not Applicable
Specific target organ systemic Toxicity (repeated exposure)		Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 199/45/CE and is classified according to the same as for the environment. For details, see sections 8 and 11. There are no data available on the product. Avoid contamination of drains or watercourses

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l	
Talc - (14807-96-6)	Not Available	Not Available	Not Available	
Nepheline syenite - (37244-96-5)	Not Available	Not Available	Not Available	
Reaction of epichlorohydrin and bisphenol A - (25085-99-8)	Not Available	Not Available	0.00 ( hr),	
Methyl isoamyl ketone - (110-12-3)	159.00, Pimephales promelas	560.00, Daphnia magna	920.00 (72 hr), Chlorococcales	
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata	
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER - (28064-14-4)	9.00, Oncorhynchus mykiss	9.00, Daphnia magna	Not Available	
Petroleum naphtha - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum	
1,2,4-Trimethyl benzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	Not Available	

12.2. Persistence and degradability No data available 12.3. Bioaccumulative potential Not Measured 12.4. Mobility in soil No data available 12.5. Results of PBT and vPvB assessment This product contains no PBT/vPvB chemicals. 12.6. Other adverse effects No data available

13. Disposal considerations

13.1. Waste treatment methods

General

Note: Disposal must be in accordance with the federal, state and local regulations.

and disposal	legislation. Remaining portior in accordance the	is of the product: local legislation.	posal of the product must in Residues that will not be us Used packing: Do not reuse nce the local legislation.	ed must be discarded		
14. Transport information						
14.1. UN number 14.2. UN proper shipping 14.3. Transport hazard c		UN 1263 PAINT				
Domestic Surface Proper Shippi Name Hazard Class UN / NA Num Packaging Gr CERCLA/DO	ing PAINT 3 iber UN 1263 roup III T RQ 2095 gal. Ibs.	/ 30012	IMO / IMDG (Ocean T IMDG Proper Shipping Name IMDG Hazard Class UN / NA Number IMDG Packing Group System Reference Code EMS Marine Pollutant	PAINT 3 UN 1263		
Air Transport (ICAC Proper Shippi Name Hazard Class UN / NA Num Packaging Gr	ing PAINT 3 iber UN 1263					
14.4. Packing group 14.5. Environmental haz IMDG Marine I	ards Pollutant: No	III				
14.6. Special precaution Not App 14.7. Transport in bulk a Not App	licable ccording to Annex licable	II of MARPOL73				
	Decreto 2.657, fro Products at Work. Act # 96.044 of 18 Decreto 1.797, of Resolution ANTT of Road Transport Decreto 3214 of M NBR 7500: Identif storage of product NBR 7501: Termin NBR 7503: Road Features, dimensi NBR 9735: Set of Products Proceo Substance Contro	m 3/07/98, regard //05/88. Regulatic 25/01/1996, Bill c # 420, of 12/02/21 of Hazardous Pr ITE ication for the roal is. hology Transpo transport of hazardons and filling. equipments for Edures. All ingredi	ding the Safety in the Utiliza ons of Road Transport of Da of Hazardous Products in the 004: complementary instruct	ngerous Products. Mercosul range. tions to the Regulation e moving and the y form and envelope sport of Hazardous d on the TSCA (Toxic		
	Inventory. B3 D2B					
		16. Other inform	mation			

The information contained in this Material Safety Data Sheet (MSDS) has the purpose of being a description of the product safety requirements, which were obtained from the literature and current legislation specific about raw materials/ingredients. Thus, the accuracy of the data contained herein is not, expressly or implicitly, assured by the Manufacturer. The product shall not be used for purposes other than the ones specified by the Manufacturer. The user is always liable for taking all required measures to comply with the provisions in this

MSDS, as well as with the requirements expressed in the regulations and effective legislation.

Bibliographic references:

- Council Directive 67/548/EEC of June 27, 1967.

- Work and Job department clause # 3.214 of June 08, 1978.

- ABNT NBR 14725 (parts I,II,III and IV) Chemical products Information on safety, health and environment.

Specific use: product meant only for professional use, check the product data sheet.

CAS: Chemical Abstract Service register number It s a register number indicated by the American Chemical Society, which identifies only a specific chemical component.

TLA852\_A1 End of Document



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : www.yachtpaint.com , www.international-marine.com, www.international-pc.com