

In accordance with the Standard for Classification and Labelling of Chemical Substance and Material Safety Data Sheet, Article 10 Paragraph

SAFETY DATA SHEET

Intersleek 1100SR DUO Part B

Section 1. Chemical product and company identification

: Intersleek 1100SR DUO Part B A. Product name

Product code : FXA293

B. Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Professional application of coatings and inks			
Uses advised against	Reason		
All Other Uses			

C. Manufacturer : International Paint Ltd.

Stoneygate Lane

Felling Gateshead Tyne and Wear NE10 0JY UK

Tel: +44 (0)191 469 6111 Fax: +44 (0)191 438 3711

Emergency telephone number (with hours of

operation)

e-mail address of person responsible for this SDS

: +44 (0)191 469 6111 (24H)

: sdsfellinguk@akzonobel.com

Section 2. Hazards identification

A. Hazard classification : FLAMMABLE LIQUIDS - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

ASPIRATION HAZARD - Category 1

LONG-TERM AQUATIC HAZARD - Category 2

B. GHS label elements, including precautionary statements

Symbol









Signal word Danger

Hazard statements Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

May cause respiratory irritation. May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Precautionary statements

Date of issue/Date of revision

Version 2:

: 05/12/2017

1/12



Section 2. Hazards identification

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid

release to the environment. Avoid breathing vapour.

: Collect spillage. IF INHALED: Remove victim to fresh air and keep at rest in a Response

> position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water or shower.

: Store locked up. Store in a well-ventilated place. Keep cool. Storage

: Dispose of contents and container in accordance with all local, regional, national **Disposal**

and international regulations.

Supplemental label

elements

: Wear appropriate respirator when ventilation is inadequate.

C. Other hazards which do

not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	Common name	CAS number	%	Classification
Solvent naphtha (petroleum), light arom.	solvent naphtha (petroleum), light arom.	64742-95-6	≥20 - <30	Flam. Liq. 3, H226
				STOT SE 3, H335 STOT SE 3, H336
				Asp. Tox. 1, H304
				Aquatic Chronic 2, H411

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

A. Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

B. Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.



Section 4. First aid measures

C. Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

D. Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

E. Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

A. Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

B. Specific hazards arising from the chemical

: Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: No specific data.

C. Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Date of issue/Date of revision

: 05/12/2017



Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions
- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

C. Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

A. Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- B. Conditions for safe storage, including any incompatibilities
- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.



Section 8. Exposure controls/personal protection

A. Control parameters

Occupational exposure limits

None.

B. Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Hand protection

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



Section 9. Physical and chemical properties

A. Appearance

Physical state : Liquid.

Colour Colourless. [Light]

B. Odour : Solvent.

: Not available. C. Odour threshold D. pH : Not applicable.

E. Melting/freezing point : Not available.

F. Boiling point/boiling

range

: Lowest known value: 140 to 200°C (284 to 392°F)(Solvent naphtha (petroleum),

light arom.).

G. Flash point : Closed cup: 49°C (120.2°F)

Fire point : Not available. H. Evaporation rate : Not available. Flammability (solid, gas) : Not available.

J. Lower and upper

: Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light arom.)

explosive (flammable)

limits

K. Vapour pressure : Not available.

L. Solubility : Insoluble in the following materials: cold water.

M. Vapour density : Not available.

N. Relative density : 1.29

O. Partition coefficient: n-

octanol/water

: Not available.

P. Auto-ignition

temperature

: Not available.

Q. Decomposition

temperature

: Not available.

R. Viscosity : Kinematic (room temperature): 8 mm²/s (8 cSt)

: Not applicable. S. Molecular weight

Section 10. Stability and reactivity

A. Chemical stability

: The product is stable.

reactions

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

C. Incompatible materials

: Reactive or incompatible with the following materials:

oxidizing materials

: 05/12/2017

D. Hazardous

decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.



Section 11. Toxicological information

A. Information on likely

: Not available.

routes of exposure

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness. May cause respiratory irritation.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed

and enters airways.

Skin contact : No known significant effects or critical hazards. : No known significant effects or critical hazards. Eye contact

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness

Ingestion : Adverse symptoms may include the following:

nausea or vomiting

Skin contact : No specific data. Eye contact : No specific data.

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), light arom.	LD50 Oral	Rat	8400 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Solvent naphtha (petroleum), light arom.	Eyes - Mild irritant	Rabbit	-	24 hours 100 microliters	-

Sensitisation

Not available.

CMR - ISHA Article 42 Public Notice No 2013-38 Occupational Exposure Limits

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Date of issue/Date of revision : 05/12/2017 AkzoNobel 7/12 Version 2:



Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom.	Category 3		Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1

Potential chronic health effects

Chronic toxicity

Not available.

General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. **Teratogenicity** : No known significant effects or critical hazards. Developmental effects : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

ATE value

Not available.

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Acute EC50 6.14 mg/m³	Daphnia	48 hours
,, g	Acute LC50 9.22 mg/m³	Fish - Mykiss	96 hours

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Not available.

D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

E. Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision

: 05/12/2017



Section 13. Disposal considerations

A. Disposal methods

: The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

B. Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	UN1263	UN1263	UN1263
B. UN proper shipping name	PAINT	PAINT. Marine pollutant (Solvent naphtha (petroleum), light arom.)	Paint
C. Transport hazard class(es)	3	3	3
D. Packing group	III	III	III
E. Environmental hazards	No.	Yes.	No.
F. Additional information	Special provisions 163, 223, 367	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules (EmS) F-E, _S-E_ Special provisions 163, 223, 367, 955	The environmentally hazardous substance mark may appear if required by other transportation regulations. Passenger and Cargo AircraftQuantity limitation: 60 L Packaging instructions: 355 Cargo Aircraft OnlyQuantity limitation: 220 L Packaging instructions: 366 Limited Quantities - Passenger AircraftQuantity limitation: 10 L Packaging instructions: Y344 Special provisions A3, A72, A192

IMDG Code Segregation group

: Not applicable.

:

Date of issue/Date of revision

: 05/12/2017



Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 37

(Harmful substances

prohibited from

manufacture)

ISHA article 38

(Harmful substances

requiring permission)

Article 2 of Youth

Protection Act on Substances Hazardous

to Youth

: None of the components are listed.

: None of the components are listed.

: None of the components are listed.

: Not applicable.

Exposure Limits of Chemical Substances and Physical Factors

None of the components have an OEL.

ISHA Enforcement Regs: None of the components are listed.

Annex 11-3 (Exposure standards established

for harmful factors)

ISHA Enforcement Regs

Annex 11-4 (Harmful

factors subject to Work

Environment Measurement)

ISHA Enforcement Regs: None of the components are listed.

Annex 12-2 (Harmful **Factors Subject to**

Special Health Check-

up)

Standard of Industrial

Safety and Health **Annex 12 (Hazardous** substances subject to

control)

B. Regulation according to Chemicals Control Act

K-Reach Article 20

(Toxic chemicals)

K-Reach Article 27

(Prohibited)

: Not applicable

: None of the components are listed.

: None of the components are listed.

K-Reach Article 27

(Restricted)

: None of the components are listed.

CSCA Article 11 (TRI) : None of the components are listed.

Korea inventory : Not determined.

CSCA Article 39

(Accident Precaution

Chemicals)

: None of the components are listed.

Date of issue/Date of revision

: 05/12/2017

AkzoNobel

10/12



Section 15. Regulatory information

C. Dangerous Materials

Safety Management Act

: Class: Class 4 - Flammable Liquid

Item: 4. Class 2 petroleums - Water-insoluble liquid

Threshold: 1000 L Danger category: III

Signal word: Contact with sources of ignition prohibited

D. Wastes regulation : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

E. Regulation according to other foreign laws

Europe inventory : Not determined. **United States inventory** : Not determined.

(TSCA 8b)

Japan inventory : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Section 16. Other information

A. References : Not available.B. Date of issue/Date of : 05/12/2017

revision

C. Version : 2

Date of printing : 05/12/2017

D. Other

▼ Indicates information that has changed from previously issued version.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

11/12

© AkzoNobel

Version 2:

:

Date of issue/Date of revision : 05/12/2017

05/12/2017



Section 16. Other information