

# AKZO NOBEL International Paint (Suzhou) Co.Ltd.

## **Safety Data Sheet**

## SYB000 INTERFINE 979 WHITE PART A

**Version Number** 5 **Revision Date** 07/21/17

# 1. Product and company identification

**1.1. Product identifier** INTERFINE 979 WHITE PART A

Product Code SYB000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Refer Technical Data Sheet.

For professional use only.

Application Method Refer Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Importer or

Manufacturer AKZO NOBEL International Paint (Suzhou) Co.Ltd.

No.129 Hongxi Road New District Suzhou, Jiangsu, 215151

China

 Telephone No.
 86(512)66167888

 Fax No.
 86(512)66163911

 1.4. Emergency telephone number (24 hour)
 86(532)83889090

For Poisons Advice telephone For Advice to Doctors & Hospitals only

# 2. Hazard identification of the product

## 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapour.

Skin Irrit. 2;H315 Causes skin irritation.

Eye Irrit. 2;H319 Causes serious eye irritation.

Skin Sens. 1;H317 May cause an allergic skin reaction.

## 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

## [Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

## [Response]:

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P321 Specific treatment (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337 If eye irritation persists:

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370 In case of fire:

P378 Use alcohol resistant foam, CO2, powder, water spray for extinction. Do not use water jet.

## [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

## [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

## 2.3. Other hazards

This product contains no PBT/vPvB chemicals.

## 3. Composition/information on ingredients

This product contains the following hazardous substances.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Methoxydimethylphenylsiloxane CAS Number: 0068957-04-0	25- <50	Acute Tox. 4;H302	[1]
1,6-Hexanediol diacrylate CAS Number: 0013048-33-4	10- <25	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]
Isopropanol CAS Number: 0000067-63-0	2.5- <10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]

<sup>[1]</sup> Substance classified with a health or environmental hazard.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

#### 4. First aid measures

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>[3]</sup> PBT-substance or vPvB-substance.

<sup>\*</sup>The full texts of the Hazard (H) phrases are shown in Section 16.

## 4.1. Description of first aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

#### **Skin Contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

## **Eye Contact**

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

# Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available

# 4.3. Indication of any immediate medical attention and special treatment needed and notes for physician

No data available

# 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media: alcohol resistant foam, CO2, powder, water spray.

Do not use - water jet.

Note; Fire will produce dense black smoke. Decomposition products may be hazardous to health. Avoid exposure and use breathing apparatus as appropriate.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

#### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

## 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

#### 6. Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

## 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

## 6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

# 7. Handling and storage

## 7.1. Precautions for safe handling

## Handling

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

## In Storage

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from the following materials: oxidising agents, strong alkalis, strong acids.

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Observe label precautions. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty a container; containers are not pressure vessels.

There are no exposure scenarios, see details in section 1.

## 7.3. Specific end use(s)

Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same material.

Prevent unauthorised access.

All sources of ignition (hot surfaces, sparks, open flames etc) should be excluded from areas of preparation and application. All electrical equipment (including torches) should be protected (Ex) to the

appropriate standard.

The product may charge electrostatically. Always use earthing leads when pouring solvents and transferring product. Operators should wear clothing which does not generate static (at least 60% natural fibre) and antistatic footwear; floors should be of conducting type.

## 8. Exposure controls and personal protection

## 8.1. Control parameters

Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygenists).

Material	Short term (15 min. ave)		Long term (8hr time weighted average)		Comments
Icanrananal	ppm 500	mg/m³ 1250	ppm	mg/M3	
Isopropanol	500	1230	400	999	

Key to notification

- (P) Peak exposure limit
- (R) Suppliers Recommended Limit
- (Sk) There is a risk of absorption through unbroken skin
- (Sen) Sensitiser
- (Cat1) Category 1 established human carcinogen
- (Cat2) Category 2 probable human carcinogen
- (Cat3) Category 3 substances suspected of having carcinogenic potential

#### **DNEL/PNEC** values

No Data Available

## 8.2. Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

#### **Eye Protection**

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Evewear should comply with an approved standard.

Wear a full face shield if mixing or pouring operations pose a risk of splashes.

An eye wash station is suggested as a good work place practice.

#### **Skin Protection**

Gloves of an appropriate material should be worn during mixing and application.

#### Other

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help to protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.

#### **Respiratory Protection**

When concentrations exceed the exposure limits shown above, workers must wear appropriate approved respirators. Provision of other controls such as exhaust ventilation should be considered if practical.

#### Thermal hazards

No Data Available

# 9. Physical and chemical properties

Appearance White Liquid
Odour Smell of Solvent
Odour threshold Not Measured

pH N/A

Melting point / freezing point (°C) Not Measured

Initial boiling point and boiling range (°C) 82
Flash Point (C) 32

Evaporation rate (Ether = 1) Not Measured Flammability (solid, gas) Not Applicable

**Upper/lower flammability or explosive limits**Lower Explosive Limit: 2 Isopropanol

Upper Explosive Limit: No data available

Vapour pressure (Pa)Not MeasuredVapour DensityHeavier than air.

Specific Gravity

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Autoignition temperature (°C)

Decomposition temperature

Not Measured

Not Measured

Viscosity (cSt) N/A

#### 9.2. Other information

No further information

## 10. Stability and reactivity

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.

#### 10.3. Possibility of hazardous reactions

May react exothermically with: oxidising agents, strong alkalis, strong acids.

#### 10.4. Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

Keep away from the following materials: oxidising agents, strong alkalis, strong acids.

#### 10.6. Hazardous decomposition products

Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

# 11. Toxicological information

## **Acute toxicity**

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

The preparation has been assessed using the Acute Toxicity Data listed below, and classified for toxicological hazards accordingly. See section 2 for details.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
1,6-Hexanediol diacrylate - (13048-33-4)	5,000.00, Rat	Not Available	Not Available	Not Available
Isopropanol - (67-63-0)	4,710.00, Rat	12,800.00, Rat	72.60, Rat	Not Available
Methoxydimethylphenylsiloxane - (68957-04-0)	Not Available	Not Available	Not Available	Not Available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

# 12. Ecological information

## 12.1. Toxicity

The preparation has been assessed according to the GHS criteria and is not classified as dangerous for the environment.

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

## **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Methoxydimethylphenylsiloxane - (68957-04-0)	Not Available	Not Available	Not Available
1,6-Hexanediol diacrylate - (13048-33-4)	Not Available	Not Available	Not Available
Isopropanol - (67-63-0)	1,400.00, Lepomis macrochirus	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus

## 12.2. Persistence and degradability

There is no data available on the preparation itself.

## 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available

## 13. Disposal considerations

#### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and empty containers should be disposed of in accordance with State and Federal regulations.

Using information provided in this data sheet advice should be obtained from the local Waste Regulation Authority as to whether special waste regulations apply.

## 14. Transport information

**14.1. UN number** 1263 **14.2. UN proper shipping name** Paint

14.3. Transport hazard class(es)

Road and Rail Transport UN1263, Paint, CLASS 3, PG III, HAZCHEM \*3Y

IMDG Class/Div 3 Sub Class

reference:

**Ems** F-E,S-E

ICAO/IATA Class 3 Sub Class

14.4. Packing group

## 14.5. Environmental hazards

Road and Rail Environmentally Hazardous: No Transport

**IMDG** Marine Pollutant: No

reference:

## 14.6. Special precautions for user

No further information

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

# 15. Regulatory information

This product and all its components complies with the chemical and transport regulations from the country listed in section 1.3.

Other regulatory information specific to the hazardous chemical(s):

None noted.

#### 16. Other information

The information on this SDS is based upon the present state of our knowledge and on current law. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Safety Data Sheet is required according to legislation.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

This SDS is valid for 5 years from the revised date on page 1. The revision date is in American format (e.g. MM/DD/YY).

End of document



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.