52050_A0

Material Safety Data Sheet INTERCRYL 520WB DEEP BASE

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: 52050
MSDS Revision Date: 02/10/2009
MSDS Revision Number: A0-



1. Identification of the preparation and company

Product Identity INTERCRYL 520WB DEEP BASE

Bulk Sales Reference No. 52050

Company Name International Paint LLC

6001 Antoine Drive Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 527–3887

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Interlux (800) 631–7481

2. Hazard identification of the product

GHS Classification;

	1		
Item	Category	Hazard	
Flammability	Not classified	Not applicable	
Acute Toxicity (mouth)	Not classified	Not applicable	
Acute Toxicity (skin)	Not classified	Not applicable	
Acute Toxicity (inhalation)	Not classified	Not applicable	
Acute Toxicity (ingestion)	Not classified	Not applicable	
Skin corrosion/irritation	Not classified	Not applicable	
Eye damage/irritation	Not classified	Not applicable	
Sensitization (respiratory)	Not classified	Not applicable	
Sensitization (skin)	Not classified	Not applicable	
Germ toxicity	Not classified	Not applicable	
Specific target organ systemic toxicity (single exposure)	1	Not applicable	
	2	Not applicable	
	3	respiratory tract irritation	
Specific target organ systemic Toxicity (repeated exposure)	1	lung	
	2	Not applicable	
Aspiration hazard	Not classified	Not applicable	
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable	
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable	
Carcinogenicity	Not classified	Not applicable	
Reproductive Toxicity	Not classified	Not applicable	
Organic Peroxide	Not classified	Not applicable	

52050 A0

Safety Phrases: Not Applicable

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 2* Flammability: 1 Reactivity: 0

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Titanium dioxide	013463-67-7	1.0 – 10
Silica, cristobalite	014464-46-1	1.0 – 10
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	025265-77-4	1.0 – 10
Kieselguhr, soda ash flux-calcined	068855-54-9	1.0 – 10

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

Ingestion If swallowed, immediately contact Poison Control Center at

1–800–854–6813. DO NOT induce vomiting unless instructed to do so by

medical personnel. Never give anything by mouth to an unconscious

person.

5. Fire-fighting measures

Flash Point F: No Established Limit

C: No Established Limit

Lower Explosive Limit (LEL)

.62 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No. 1

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non–combustible material and

transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain

released material and runoff from fire control.

Public Safety CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak

area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed

spaces before entering.

ERG Guide No. 159

7. Handling and storage

Storage Temperature

Store between 32 and 120 F

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build—up of vapors by opening all windows and doors to achieve cross—ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

CAS No.	Ingredient	Source	Value
013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWAEV (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
014464-46-1	Silica, cristobalite	OSHA	No Established Limit
		ACGIH	0.025 mg/m3 TWA (respirable fraction)
			0.05 mg/m3 TWA (respirable dust)25 mg/m3 IDLH (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	0.05 mg/m3 TWAEV (designated substance regulation)0.05 mg/m3 TWAEV
		Mexico	0.05 mg/m3 TWA
		Brazil	No Established Limit
	025265-77-4 2,2,4-Trimethylpentane-1,3-diol		No Established Limit
	nonoisobutyrate	ACGIH	No Established Limit
		NIOSH	No Established Limit
		- ' '	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
	Kieselguhr, soda ash	OSHA	No Established Limit
flux-calcined	flux-calcined	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
014464-46-1	Silica, cristobalite	NIOSH	Chronic lung disease (silicosis)
	2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	NIOSH	No Established Limit
068855-54-9	Kieselguhr, soda ash flux-calcined	NIOSH	No Established Limit

Carcinogen Data

52050 A0

CAS No.	Ingredient	Source	Value
013463-67-7		OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
014464-46-1	014464-46-1 Silica, cristobalite		Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
025265-77-4	025265-77-4 2,2,4-Trimethylpentane-1,3-diol		Select Carcinogen: No
n		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
068855-54-9	flux-calcined	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

Respiratory Select equipment to provide protection from the ingredients listed in Section 3 of this

document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of

the information contained in this Material Safety Data Sheet.

Eyes Avoid contact with eyes. Protective equipment should be selected to provide

protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment

must be thoroughly cleaned, or discarded after each use.

Skin Protective equipment should be selected to provide protection from exposure to the

chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded

after each use.

Engineering Controls Prevent build-up of vapors by opening all windows and doors to achieve

cross-ventilation.

immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

soap and water.

9. Physical and chemical properties

Physical State Liquid

pH Not Determined

Specific Gravity 1.12
Boiling Point F 212

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet for this product

Evaporation Rate Slower than ether

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous Decompostion May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Titanium dioxide – (013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabitt - Category: NA	6,082.00, Rat – Category: NA
Silica, cristobalite – (014464–46–1)			
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate - (025265-77-4)	3,200.00, Rat – Category: 5	15,200.00, Rat – Category: NA	
Kieselguhr, soda ash flux-calcined - (068855-54-9)			

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation) IMDG Proper Shipping PAINT OR PAINT **DOT Proper Shipping** PAINT OR PAINT RELATED MATERIAL, Name RELATED MATERIAL, Name NMFC 149980 NMFC 149980 **DOT Hazard Class** NR **IMDG Hazard Class** Not Regulated UN / NA Number Not Regulated UN / NA Number Not Regulated **DOT Packing Group** Not Regulated **IMDG Packing Group** Not Regulated CERCLA/DOT RQ 9762 gal. / 90909 lbs. System Reference 9 Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all–inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification D2B

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

Nitrous acid, sodium salt (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

Nitrous acid, sodium salt

Mass RTK Substances (>1%):

Silica, cristobalite

Titanium dioxide

Mass Extraordinarily Haz Sub (>.01%):

Ammonia

Formaldehyde

Quartz

Silica, cristobalite

Penn RTK Substances (>1%):

Kieselguhr, soda ash flux-calcined

Silica, cristobalite

Titanium dioxide

Penn Special Hazardous Substances (>.01%):

Formaldehyde

Rhode Island Hazardous Substances (>.1%):

Titanium dioxide

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Silica, cristobalite

Titanium dioxide

N.J. Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

Ammonia

Formaldehyde

Sodium hydroxide

N.J. Env. Hazardous Substances (>.1%):

Nitrous acid, sodium salt

Proposition 65 - Carcinogens (>0%):

Ethylene oxide

Formaldehyde

Quartz

Proposition 65 - Female Repro Toxins (>0%):

Ethylene oxide

Proposition 65 – Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):

(No Product Ingredients Listed)

Risk Phrases: Not Applicable

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.