

Safety Data Sheet  
 INTERCRYL 520WB LIGHT BASE

Sales  
 Order: {SalesOrd}

Bulk Sales Reference No.:  
 SDS Revision Date:  
 SDS Revision Number:

52011  
 09/27/2013  
 B2-2



1. Identification of the preparation and company

1.1. Product identifier

Product Identity INTERCRYL 520WB LIGHT BASE  
 Bulk Sales Reference No. 52011

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.  
 Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC  
 6001 Antoine Drive  
 Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300  
 International Paint (713) 682-1711  
 Poison Control Center (800) 854-6813  
 Customer Service  
 International Paint (800) 589-1267  
 Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Aquatic Chronic 1;H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H410 Very toxic to aquatic life with long lasting effects.

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 2 Flammability: 1 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations   | Weight %   | GHS Classification  | Notes  |
|--|------------|---|--------|
| Titanium dioxide<br>CAS Number: 0013463-67-7                                   | 10 - 25    | ----  | [1][2] |
| Limestone<br>CAS Number: 0001317-65-3  | 1.0 - 10   | ----  | [1]    |
| Trizinc diphosphate<br>CAS Number: 0007779-90-0                                | 1.0 - 10   | Aquatic Acute<br>1;H400<br>Aquatic Chronic<br>1;H410            | [1]    |
| 2,2,4-Trimethylpentane-1,3-diol<br>monoisobutyrate<br>CAS Number: 0025265-77-4 | 1.0 - 10   | ----  | [1]    |
| Silica, amorphous<br>CAS Number: 0007631-86-9                                  | 1.0 - 10   | ----  | [1][2] |
| Zinc oxide<br>CAS Number: 0001314-13-2   | 0.10 - 1.0 | Aquatic Acute<br>1;H400<br>Aquatic Chronic<br>1;H410            | [1][2] |
| Nitrous acid, sodium salt<br>CAS Number: 0007632-00-0                          | 0.10 - 1.0 | Ox. Sol. 3;H272<br>Acute Tox. 3;H301<br>Aquatic Acute<br>1;H400 | [1]    |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

#### 4. First aid measures

##### 4.1. Description of first aid measures

|            |   |
|------------|---|
| General    | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.  |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.  |
| Eyes       | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.   |
| Skin       | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.  |
| Ingestion  | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

##### 4.2. Most important symptoms and effects, both acute and delayed

|                 |  |
|-----------------|--|
| Overview        | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation      | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.  |
| Eyes            | Causes severe eye irritation. Avoid contact with eyes.   |
| Skin            | Causes skin irritation. May be harmful if absorbed through the skin.   |
| Ingestion       | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.   |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.   |

#### 5. Fire-fighting measures

##### 5.1. Extinguishing media

## 52011\_B2

**SMALL FIRES:** Use dry chemical, CO<sub>2</sub>, water spray or foam. **LARGE FIRES:** Use water spray, fog, or foam. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

### 5.2. Special hazards arising from the substance or mixture

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 159

|                                       |
|---------------------------------------|
| <b>6. Accidental release measures</b> |
|---------------------------------------|

#### 6.1. Personal precautions, protective equipment and emergency procedures

**ELIMINATE ALL IGNITION SOURCES** (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. **LARGE SPILLS:** Dike far ahead of liquid spill to contain released material and runoff from fire control.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

#### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

|                                |
|--------------------------------|
| <b>7. Handling and storage</b> |
|--------------------------------|

#### 7.1. Precautions for safe handling

##### Handling

Vapors may cause flash fire or ignite explosively.

##### In Storage

Keep away from heat, sparks and flame.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

#### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

|   |
|---|
| <b>8. Exposure controls and personal protection</b> |
|---|

#### 8.1. Control parameters

##### Exposure

| CAS No.      | Ingredient | Source   | Value   |
|--------------|------------|----------|---|
| 0001314-13-2 | Zinc oxide | OSHA     | 5 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust);<br>5 mg/m <sup>3</sup> TWA (respirable fraction)10 mg/m <sup>3</sup> STEL (fume) |
|              |            | ACGIH    | 2 mg/m <sup>3</sup> TWA (respirable fraction)10 mg/m <sup>3</sup> STEL (respirable fraction)  |
|              |            | NIOSH    | 5 mg/m <sup>3</sup> TWA (dust and fume)10 mg/m <sup>3</sup> STEL (fume)15 mg/m <sup>3</sup> Ceiling (dust)500 mg/m <sup>3</sup> IDLH                    |
|              |            | Supplier |   |

52011\_B2

|              |   |           |   |
|--------------|---|-----------|---|
|              |   | OSHA, CAN | 2 mg/m3 TWA (respirable)10 mg/m3 STEL (respirable)                                      |
|              |   | Mexico    | 5 mg/m3 TWA LMPE-PPT (fume); 10 mg/m3 TWA LMPE-PPT (dust)10 mg/m3 STEL [LMPE-CT] (fume) |
|              |   | Brazil    |   |
| 0001317-65-3 | Limestone                                       | OSHA      | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)                            |
|              |   | ACGIH     |   |
|              |   | NIOSH     | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)                                |
|              |   | Supplier  |   |
|              |   | OSHA, CAN |   |
|              |   | Mexico    | 10 mg/m3 TWA LMPE-PPT20 mg/m3 STEL [LMPE-CT]  |
|              |   | Brazil    |   |
| 0007631-86-9 | Silica, amorphous                               | OSHA      |   |
|              |   | ACGIH     |   |
|              |   | NIOSH     | 6 mg/m3 TWA3000 mg/m3 IDLH  |
|              |   | Supplier  |   |
|              |   | OSHA, CAN |   |
|              |   | Mexico    |   |
|              |   | Brazil    |   |
| 0007632-00-0 | Nitrous acid, sodium salt                       | OSHA      |   |
|              |   | ACGIH     |   |
|              |   | NIOSH     |   |
|              |   | Supplier  |   |
|              |   | OSHA, CAN |   |
|              |   | Mexico    |   |
|              |   | Brazil    |   |
| 0007779-90-0 | Trizinc diphosphate                             | OSHA      |   |
|              |   | ACGIH     |   |
|              |   | NIOSH     |   |
|              |   | Supplier  |   |
|              |   | OSHA, CAN |   |
|              |   | Mexico    |   |
|              |   | Brazil    |   |
| 0013463-67-7 | Titanium dioxide                                | OSHA      | 15 mg/m3 TWA (total dust)   |
|              |   | ACGIH     | 10 mg/m3 TWA  |
|              |   | NIOSH     | 5000 mg/m3 IDLH   |
|              |   | Supplier  |   |
|              |   | OSHA, CAN | 10 mg/m3 TWA  |
|              |   | Mexico    | 10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)                            |
|              |   | Brazil    |   |
| 0025265-77-4 | 2,2,4-Trimethylpentane-1,3-diol monoisobutyrate | OSHA      |   |
|              |   | ACGIH     |   |
|              |   | NIOSH     |   |
|              |   | Supplier  |   |
|              |   | OSHA, CAN |   |
|              |   | Mexico    |   |
|              |   | Brazil    |   |

## Health Data

| CAS No.      | Ingredient                                      | Source | Value                                       |
|--------------|---|--------|---|
| 0001314-13-2 | Zinc oxide                                      | NIOSH  | Metal fume fever                            |
| 0001317-65-3 | Limestone                                       | NIOSH  | Eye and skin irritation Physical irritation |
| 0007631-86-9 | Silica, amorphous                               | NIOSH  |   |
| 0007632-00-0 | Nitrous acid, sodium salt                       | NIOSH  |   |
| 0007779-90-0 | Trizinc diphosphate                             | NIOSH  |   |
| 0013463-67-7 | Titanium dioxide                                | NIOSH  | Lung tumors in animals                      |
| 0025265-77-4 | 2,2,4-Trimethylpentane-1,3-diol monoisobutyrate | NIOSH  |   |

## Carcinogen Data

| CAS No.      | Ingredient                                      | Source | Value   |
|--------------|---|--------|---|
| 0001314-13-2 | Zinc oxide                                      | OSHA   | Select Carcinogen: No   |
|              |   | NTP    | Known: No; Suspected: No  |
|              |   | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0001317-65-3 | Limestone                                       | OSHA   | Select Carcinogen: No   |
|              |   | NTP    | Known: No; Suspected: No  |
|              |   | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0007631-86-9 | Silica, amorphous                               | OSHA   | Select Carcinogen: No   |
|              |   | NTP    | Known: No; Suspected: No  |
|              |   | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0007632-00-0 | Nitrous acid, sodium salt                       | OSHA   | Select Carcinogen: No   |
|              |   | NTP    | Known: No; Suspected: No  |
|              |   | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0007779-90-0 | Trizinc diphosphate                             | OSHA   | Select Carcinogen: No   |
|              |   | NTP    | Known: No; Suspected: No  |
|              |   | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0013463-67-7 | Titanium dioxide                                | OSHA   | Select Carcinogen: Yes  |
|              |   | NTP    | Known: No; Suspected: No  |
|              |   | IARC   | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0025265-77-4 | 2,2,4-Trimethylpentane-1,3-diol monoisobutyrate | OSHA   | Select Carcinogen: No   |
|              |   | NTP    | Known: No; Suspected: No  |
|              |   | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |

## 8.2. Exposure controls

|             |   |
|-------------|---|
| Respiratory | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes        | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.  |
| Skin        | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be   |

## 52011\_B2

required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

|                      |  |
|----------------------|--|
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation.  |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

|                                     |
|-------------------------------------|
| 9. Physical and chemical properties |
|-------------------------------------|

|   |  |
|---|--|
| Appearance                                      | Coloured Liquid  |
| Odour threshold                                 | Not Measured   |
| pH  | 9  |
| Melting point / freezing point                  | Not Measured   |
| Initial boiling point and boiling range         | 100 (°C) 212 (°F)  |
| Flash Point                                     | No Established Limit (°C) No Established Limit(°F)                         |
| Evaporation rate (Ether = 1)                    | Not Measured   |
| Flammability (solid, gas)                       | Not Applicable   |
| Upper/lower flammability or explosive limits    | Lower Explosive Limit: .62<br>Upper Explosive Limit: No Established Limit  |
| vapor pressure (Pa)                             | Not Measured   |
| Vapor Density                                   | Heavier than air   |
| Specific Gravity                                | 1.28   |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured   |
| Auto-ignition temperature                       | Not Measured   |
| Decomposition temperature                       | Not Measured   |
| Viscosity (cSt)                                 | No Established Limit   |
| VOC %   | Refer to the Technical Data Sheet or label where information is available. |

|                              |
|------------------------------|
| 10. Stability and reactivity |
|------------------------------|

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

|                               |
|-------------------------------|
| 11. Toxicological information |
|-------------------------------|

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, | Inhalation Dust/Mist LD50, |
|------------|------------------|------------------|------------------------|----------------------------|
|------------|------------------|------------------|------------------------|----------------------------|

## 52011\_B2

|  |                               |                                  | mg/L/4hr          | mg/L/4hr                  |
|--|-------------------------------|----------------------------------|-------------------|---------------------------|
| Titanium dioxide - (13463-67-7)                                | 10,000.00, Rat - Category: NA | 10,000.00, Rabbit - Category: NA | No data available | 6.82, Rat - Category: NA  |
| Limestone - (1317-65-3)  | No data available             | No data available                | No data available | No data available         |
| Trizinc diphosphate - (7779-90-0)                              | 5,000.00, Rat - Category: 5   | No data available                | No data available | No data available         |
| 2,2,4-Trimethylpentane-1,3-diol monoisobutyrate - (25265-77-4) | 3,200.00, Rat - Category: 5   | 15,200.00, Rabbit - Category: NA | No data available | No data available         |
| Silica, amorphous - (7631-86-9)                                | 5,110.00, Rat - Category: NA  | 5,000.00, Rabbit - Category: 5   | No data available | No data available         |
| Zinc oxide - (1314-13-2)                                       | 5,000.00, Rat - Category: 5   | No data available                | No data available | 2.50, Mouse - Category: 4 |
| Nitrous acid, sodium salt - (7632-00-0)                        | 180.00, Rat - Category: 3     | No data available                | No data available | 5.50, Rat - Category: NA  |

| Item  | Category       | Hazard         |
|---|----------------|----------------|
| Acute Toxicity (mouth)                                      | Not Classified | Not Applicable |
| Acute Toxicity (skin)                                       | Not Classified | Not Applicable |
| Acute Toxicity (inhalation)                                 | Not Classified | Not Applicable |
| Skin corrosion/irritation                                   | Not Classified | Not Applicable |
| Eye damage/irritation                                       | Not Classified | Not Applicable |
| Sensitization (respiratory)                                 | Not Classified | Not Applicable |
| Sensitization (skin)  | Not Classified | Not Applicable |
| Germ toxicity   | Not Classified | Not Applicable |
| Carcinogenicity   | Not Classified | Not Applicable |
| Reproductive Toxicity                                       | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure)   | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard   | Not Classified | Not Applicable |

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## Aquatic Ecotoxicity

| Ingredient   | 96 hr LC50 fish, mg/l           | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l                              |
|--|---------------------------------|----------------------------|--|
| Titanium dioxide - (13463-67-7)                                | 1,000.00, Fundulus heteroclitus | 5.50, Daphnia magna        | 5.83 (72 hr), Pseudokirchneriella subcapitata  |
| Limestone - (1317-65-3)  | Not Available                   | Not Available              | Not Available                                  |
| Trizinc diphosphate - (7779-90-0)                              | 0.09, Oncorhynchus mykiss       | 0.04, Daphnia magna        | 0.136 (72 hr), Selenastrum capricornutum       |
| 2,2,4-Trimethylpentane-1,3-diol monoisobutyrate - (25265-77-4) | 30.00, Pimephales promelas      | 95.00, Daphnia magna       | 18.40 (72 hr), Selenastrum capricornutum       |
| Silica, amorphous - (7631-86-9)                                | 10,000.00, Danio rerio          | 10,000.00, Daphnia magna   | 10,000.00 (72 hr), Scenedesmus subspicatus     |
| Zinc oxide - (1314-13-2)                                       | 1.10, Oncorhynchus mykiss       | 0.098, Daphnia magna       | 0.042 (72 hr), Pseudokirchneriella subcapitata |

52011\_B2

|   |                           |                      |                                   |
|---|---------------------------|----------------------|-----------------------------------|
| Nitrous acid, sodium salt - (7632-00-0) | 0.11, Oncorhynchus mykiss | 12.50, Daphnia magna | 159.00 (72 hr), Tetraselmis chuii |
|---|---------------------------|----------------------|-----------------------------------|

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number Not Regulated

14.2. UN proper shipping name Not Regulated

14.3. Transport hazard class(es)

| DOT (Domestic Surface Transportation) |   | IMO / IMDG (Ocean Transportation) |                              |
|---------------------------------------|---|-----------------------------------|------------------------------|
| DOT Proper Shipping Name              | Not Regulated                             | IMDG Proper Shipping Name         | Not Regulated                |
| DOT Hazard Class                      | Not Regulated                             | IMDG Hazard Class Sub Class       | Not Regulated Not applicable |
| UN / NA Number                        | Not Regulated                             | IMDG Packing Group                | Not Regulated                |
| DOT Packing Group                     | Not Regulated                             | System Reference Code             | 9                            |
| CERCLA/DOT RQ                         | Not Applicable gal. / Not Applicable lbs. |                                   |                              |

14.4. Packing group Not Regulated

14.5. Environmental hazards

IMDG Marine Pollutant: Yes ( Trizinc diphosphate )

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification Not Regulated

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)



DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :  
Nitrous acid, sodium salt (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :  
Nitrous acid, sodium salt

Mass RTK Substances (>1%) :  
Limestone  
Silica, amorphous  
Titanium dioxide

Penn RTK Substances (>1%) :  
Limestone  
Silica, amorphous  
Titanium dioxide

Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)

RCRA Status:  
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :  
Limestone  
Silica, amorphous  
Titanium dioxide

N.J. Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)  
Ammonia  
Ammonium hydroxide  
Quartz  
Silica, cristobalite  
Sodium hydroxide

N.J. Env. Hazardous Substances (>.1%) :  
Nitrous acid, sodium salt

Proposition 65 - Carcinogens (>0%):  
Ethylene oxide  
Quartz  
Titanium dioxide

Proposition 65 - Female Repro Toxins (>0%):  
Ethylene oxide

Proposition 65 - Male Repro Toxins (>0%):  
Ethylene oxide

Proposition 65 - Developmental Toxins (>0%):  
Ethylene oxide

|                       |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H272 May intensify fire; oxidizer.  
H301 Toxic if swallowed.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

End of Document