PHP99G_A0

PHP99G

A0

09/29/2015

Safety Data Sheet INTERTHANE 990 LIGHT GREEN 10 GY 9/1 Bulk Sales Reference No.: SDS Revision Date: SDS Revision Number:

XInternational.

1. Identification of the	preparation and company
1.1. Product identifier	h ch a su anna a annhan A
Product Identity	INTERTHANE 990 LIGHT GREEN 10 GY 9/1
Bulk Sales Reference Number	PHP99G
1.2. Relevant identified uses of the substance or mixt	ure and uses advised against
Intended Use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.
1.3. Details of the supplier of the safety data sheet	
Company Name	International Paint Ltda
	ARGENTINA:
	Ruta Panamericana Km 37,5
	Garin, Buenos Aires PO Box: B1606DQE
	AKZONOBEL CHILE:
	Calle Limache 3363 Local 3, El Salto
	Viña del Mar, Chile
	C.P. 2520642 - Rut 76.048140-8
	BRAZIL:
	Avenida Paiva, 999 - Neves
	Sao Goncalo, RJ 24426-148 Brazil
Emergency	
Suatrans Cotec	0800 7071 767 or 0800 7077 022 or 0800 172020 or
	55*2*7500 (24 hr)
International Paint	ARGENTINA:
	+54 3327 44 7777
	CHILE: +56 32 267 1174
	BRAZIL:
	+55 21 2199-7100
Poison Control Center (Brazil)	0800-0148110 or +55 11 3069-8800
Medical Service (Argentina)	+54 3327 44 7144 or +54 3327 44 7282
Firefighter/HSE (Argentina)	+54 3327 44 7123
Customer Service	ARGENTINA: +54 3327 44 7777 Fax: +54 3327 44 7738
	CHILE:
	+56 32 267 1174 Fax: +56 32 263 1496
	BRAZIL:
	+55 21 2199-7100 Fax: +55 21 2199-7124
2. Hazard identifi	ication of the product

2.1. Classification of the substance or mixture Flam. Liq. 3;H226 Skin Irrit. 2;H315 Eye Irrit. 2;H319 Aquatic Acute 2;H401 Aquatic Chronic 3;H412

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapours / spray.

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P331 Do NOT induce vomiting.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %
Titanium dioxide CAS Number: 0013463-67-7	10 - 25
Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7	10 - 25
Limestone CAS Number: 0001317-65-3	1.0 - 10
Benzene, ethyl- CAS Number: 0000100-41-4	1.0 - 10
Propylene glycol monomethyl ether acetate CAS Number: 0000108-65-6	1.0 - 10
Silica, amorphous CAS Number: 0007631-86-9	1.0 - 10
Aluminum hydroxide CAS Number: 0021645-51-2	1.0 - 10

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	

	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
4.2. Most important syn	nptoms and effects, both acute and delayed
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.
Skin	Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.
	5. Fire-fighting measures
5.1. Extinguishing medi	
Appropriate Extinguishing Methods	Water in form of fog, Co2, foam or dry chemical dust.
Inappropriate Extinguishing Methods	Direct water spray into fire
Specific Hazards	Can liberate toxic fumes or gases during the burning. For decomposition see section 10.
5.2. Special hazards ar	ising from the substance or mixture
Special Methods	Evacuate the area and to fight the fire at a safe distance upwind. Use water in fog to cool containers near the fire. Keep runoff from entering sewer. Extinguishing water must be disposed according to local legislation.
5.3. Advice for fire-fight	
Firefighter Protection	In fire case, to use personal respiratory device and suits for protection.
-	6. Accidental release measures
6.1. Personal precautio	ns, protective equipment and emergency procedures
Personal precautions	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material.
Public Safety	Call Suatrans Cotec 0800 7071 767 or 0800 7077 022 or 0800 17 2020 or 55*2*7500 (24 hr) for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.
6.2. Environmental prec	
Environmental Precations	Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.
6.3. Methods and mate	rial for containment and cleaning up
Clean Up Method	Cover with sand or other non-cumbustible material. Transfer absorbed material with a
	non-sparking tool.

^{7.1.} Precautions for safe handling

Handle the packages with care in order to avoid damage and spillage.

Be aware of the precautions referred to on the label. Avoid contact with the eyes and the skin. Avoid swallowing of vapor and the pulverizations. Be aware of the

precautions referred to on the label. Use personal protection equipment according to the section 8. No smoking, drinking or eating in the application areas.

All the ignition sources (hot surfaces, sparks, unprotected flames, etc.) must be excluded from the areas of manufacturing and application. The storage areas, the preparation and the application must be well ventilated. The product can be carried electrostatically. Always use grounding cables when transferring solvents or product. The operators must use adequate outfits which shall not develop static current. (at least 60% of natural fiber) and anti-static shoes.

Solvents based products: The solvent vapors are heavier than the air and can concentrate on the floor and explosive mixtures may be formed with the air .

Water based products: It does not require special cares for not being inflammable or explosive. Use only the indicated personal protection equipments.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

	8. Exposure	controls an	d personal protection
	8.	1. Control p	parameters
		Expos	ure
CAS No. Ingredient		Source	Value
0000100-41-4	Benzene, ethyl-	ACGIH	20 ppm TWA
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0000108-65-6	Propylene glycol monomethyl	ACGIH	
	ether acetate	Brazil	
0001317-65-3	0001317-65-3 Limestone		
	Brazil		
0001330-20-7	Xylenes (o-, m-, p- isomers)	ACGIH	100 ppm TWA150 ppm STEL
	Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT	
0007631-86-9	Silica, amorphous	ACGIH	
		Brazil	
0013463-67-7	Titanium dioxide	ACGIH	10 mg/m3 TWA
		Brazil	
0021645-51-2	Aluminum hydroxide	ACGIH	
		Brazil	

Health Data					
CAS No.	Ingredient	Source	Value		
0000100-41-4	Benzene, ethyl-	NIOSH	Eye skin		
	Propylene glycol monomethyl ether acetate	NIOSH			
0001317-65-3	Limestone	NIOSH	Eye and skin irritation Physical irritation		
0001330-20-7	Xylenes (o-, m-, p- isomers)		Central nervous system depressant; respiratory and eye irritation		
0007631-86-9	Silica, amorphous	NIOSH			
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals		
0021645-51-2	Aluminum hydroxide	NIOSH			

CAS No.	Ingredient	Source	Value
0000100-41-4	Benzene, ethyl-	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000108-65-6	Propylene glycol	OSHA	Select Carcinogen: No
	monomethyl ether	NTP	Known: No; Suspected: No
	acetate	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001317-65-3	Limestone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

0001330-20-7	y = = = (= y = y = y	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0007631-86-9	Silica, amorphous	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;	
0021645-51-2	Aluminum hydroxide	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

8.2. Exposure controls

Respiratory Protection	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.
Eye and face protection	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 8 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin and body protection	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 8 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Special Precations	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.
	9. Physical and chemical properties
Appearance	Green Liquid
Odour threshold	Not Measured

Appearance	Green Liquid
Odour threshold	Not Measured
рН	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	100 (°C) 212 (°F)
Flash Point	24 (°C) 75.2 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limit	s Lower Explosive Limit: .6
	Upper Explosive Limit: No Established Limit
Vapour pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.24
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured

	—
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.
	10. Stability and reactivity
10.1. Reactivity	
Keep away from alkaline or strong	strong acid to prevent probable exothermal reactions.
10.2. Chemical stability	
This product is stable	
10.3. Possibility of hazardous read	tions
• •	occur. Heat and vapors in excess can be generated when inproperly used.
10.4. Conditions to avoid	
Strong oxidizing agents	strong acid to prevent probable exothermal reactions.
10.5. Incompatible materials	
Strong oxidizing agents	
10.6. Hazardous decomposition pr	roducts
• ··· · · · · · · ·	

Can liberate toxic vapors in the welding process. The vapors can produce Dioxide and Monoxide of Car	bon.
11. Toxicological information	

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 3 and 8 for chemical specific data.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
Xylenes (o-, m-, p- isomers) - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available
Limestone - (1317-65-3)	No data available	No data available	No data available	No data available
Benzene, ethyl (100-41-4)	3,500.00, Rat - Category: 5	15,433.00, Rabbit - Category: NA	17.20, Rat - Category: 4	No data available
Propylene glycol monomethyl ether acetate - (108-65-6)	8,532.00, Rat - Category: NA	5,000.00, No data Rabbit - available Category: 5		No data available
Silica, amorphous - (7631-86-9)	5,110.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available
Aluminum hydroxide - (21645-51-2)	5,000.00, Rat - Category: 5	No data available	No data available	No data available

Item	Category	Hazard	
Acute Toxicity (mouth)	Not Classified	Not Applicable	
Acute Toxicity (skin)	Not Classified	Not Applicable	
Acute Toxicity (inhalation)	Not Classified	Not Applicable	
Skin corrosion/irritation	2	Causes skin irritation.	
Eye damage/irritation	2	Causes serious eye irritation.	
Sensitization (respiratory)		Not Applicable	
Sensitization (skin)		Not Applicable	
Germ toxicity	Not Classified	Not Applicable	
Carcinogenicity		Not Applicable	
Reproductive Toxicity		Not Applicable	
		Not Applicable	

Specific target organ systemic toxicity (single exposure)		
Specific target organ systemic Toxicity (repeated exposure)		Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 199/45/CE and is classified according to the same as for the environment. For details, see sections 8 and 11. There are no data available on the product. Avoid contamination of drains or watercourses

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l	
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata	
Xylenes (o-, m-, p- isomers) - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales	
Limestone - (1317-65-3)	Not Available	Not Available	Not Available	
Benzene, ethyl (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata	
Propylene glycol monomethyl ether acetate - (108-65-6)	100.00, Salmo gairdneri	500.00, Daphnia magna	Not Available	
Silica, amorphous - (7631-86-9)	10,000.00, Danio rerio	10,000.00, Daphnia magna	10,000.00 (72 hr), Scenedesmus subspicatus	
Aluminum hydroxide - (21645-51-2)	Not Available	Not Available	Not Available	

12.2. Persistence and degradability
No data available
12.3. Bioaccumulative potential
Not Measured
12.4. Mobility in soil
No data available
12.5. Results of PBT and vPvB assessment
This product contains no PBT/vPvB chemicals.
12.6. Other adverse effects
No data available

	13. Disposal considerations
13.1. Waste treatment	methods
General	Note: Disposal must be in accordance with the federal, state and local regulations.
Method of treatment and disposal	Product: The treatment and the disposal of the product must in accordance the local legislation.
	Remaining portions of the product: Residues that will not be used must be discarded in accordance the local legislation. Used packing: Do not reuse the packing. Recycle if appropriate or discard in accordance the local legislation.
	14. Transport information
14.1. UN number	UN 1263
14.2. UN proper shipp	ing name PAINT
440 T	

14.3. Transport hazard class(es)

Domestic Surface Transportation		IMO / IMDG (Ocean Transportation)					
Proper Ship Name	ping	PAINT		IMDG Proper Shipping Name	PAINT		
Hazard Clas	SS	3		IMDG Hazard Class	3		
UN / NA Nu	Imber	UN 1263		UN / NA Number	UN 1263		
Packaging (Group	III		IMDG Packing Group)		
CERCLA/D	OT RQ	88 gal. / 905 lbs.		System Reference Code	1		
Risk Numbe	ər	30		EMS	F-E,S-E		
				Marine Pollutant	No		
Air Transport (IC)	AO-ITI / I.	ATA-DGR)					
Proper Ship Name	ping	PAINT					
Hazard Clas	SS	3					
UN / NA Nu	Imber	UN 1263					
Packaging (Group	III					
14.4. Packing group		111					
14.5. Environmental ha	azards						
IMDG Marine	e Pollutar	nt: No					
14.6. Special precautio		er					
'	oplicable						
		g to Annex II of MARPOL	$_{-}/3//8$ ai	nd the IBC Code			
Not Ap	oplicable						
	<u> </u>	15. Regulatory					
Regulatory Overview	Regulatory Overview Decreto 2.657, from 3/07/98, regarding the Safety in the Utilization of Chemical Products at Work						
	Products at Work. Act # 96.044 of 18/05/88. Regulations of Road Transport of Dangerous Products.						
Decreto 1.797, of 25/01/1996, Bill of Hazardous Products in the Mercosul range.							
Resolution ANTT # 420, of 12/02/2004: complementary instructions to the Regulation							
of Road Transport of Hazardous Products. Decreto 3214 of MTE							
NBR 7500: Identification for the road transport, the handling, the moving and the							
storage of products.							
NBR 7501: Terminology Transport of Hazardous Products.							
NBR 7503: Road transport of hazardous products emergency form and envelope Features, dimensions and filling.							
NBR 9735: Set of equipments for Emergency in the Road Transport of Hazardous							
Products Procedures. All ingredients of this product are listed on the TSCA (Toxic							
		nce Control Act) Inventor	y or are	not required to be listed	d on the TSCA		
WHMIS Classification	Invento B2 D2I	,					
WINNIS Classification	62 U2I	D					

The information contained in this Material Safety Data Sheet (MSDS) has the purpose of being a description of the product safety requirements, which were obtained from the literature and current legislation specific about raw materials/ingredients. Thus, the accuracy of the data contained herein is not, expressly or implicitly, assured by the Manufacturer. The product shall not be used for purposes other than the ones specified by the Manufacturer. The user is always liable for taking all required measures to comply with the provisions in this MSDS, as well as with the requirements expressed in the regulations and effective legislation.

16. Other information

Bibliographic references:

Specific use: product meant only for professional use, check the product data sheet.

CAS: Chemical Abstract Service register number It s a register number indicated by the American Chemical Society, which identifies only a specific chemical component.

⁻ Council Directive 67/548/EEC of June 27, 1967.

⁻ Work and Job department clause # 3.214 of June 08, 1978.

⁻ ABNT NBR 14725 (parts I,II,III and IV) Chemical products Information on safety, health and environment.

PHP99G_A0 End of Document

AkzoNobel

Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : www.yachtpaint.com , www.international-marine.com, www.international-pc.com