Material Safety Data Sheet INTERGARD 292 BLUE PART A

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: NHA218
MSDS Revision Date: 05/12/2011
MSDS Revision Number: A8-5



1. Identification of the preparation and company

Product Identity INTERGARD 292 BLUE PART A

Bulk Sales Reference No. NHA218

Company Name International Paint LLC

6001 Antoine Drive Houston, Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product

GHS Classification;

· · · · · · · · · · · · · · · · · · ·	1	
Item	Category	Hazard
Flammability	Not classified	Not applicable
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	blood (circulatory system), central nerve system, kidneys, liver
	2	Not applicable
	3	respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	blood (circulatory system)
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable
Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

NHA218 A8

Safety Phrases: Not Applicable

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 2 Flammability: 1 Reactivity: 0 PPE: X

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
2-Butoxyethanol	0000111-76-2	1.0 – 10
Ethylene glycol monopropyl ether	0002807-30-9	1.0 – 10
Barium sulfate	0007727-43-7	1.0 – 10
Titanium dioxide	0013463-67-7	1.0 – 10
Wollastonite (Ca(SiO3))	0013983-17-0	1.0 – 10
Talc	0014807-96-6	1.0 – 10
Modified Epoxy Resin	TS-RE2404	10 – 25

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious

nedical personnel. Never give anything by mouth to an unconscious

person.

5. Fire-fighting measures

Flash Point F: No Established Limit

C: No Established Limit

Lower Explosive Limit (LEL) 1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No. 159

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and

transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain

released material and runoff from fire control.

Public Safety

CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

ERG Guide No. 159

7. Handling and storage

Storage Temperature

Store between 40-100F (4-38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build—up of vapors by opening all windows and doors to achieve cross—ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

CAS No. Ingredient		Value
2-Butoxyethanol	OSHA	50 ppm TWA; 240 mg/m3 TWA
	ACGIH	20 ppm TWA
	NIOSH	5 ppm TWA; 24 mg/m3 TWA700 ppm IDLH
	Supplier	No Established Limit
	OHSA, CAN	20 ppm TWA
	Mexico	26 ppm TWA; 120 mg/m3 TWA75 ppm STEL; 360 mg/m3 STEL
	Brazil	39 ppm TWA; 190 mg/m3 TWA
Ethylene glycol monopropyl	OSHA	No Established Limit
ether	ACGIH	No Established Limit
	NIOSH	No Established Limit
	Supplier	No Established Limit
	OHSA, CAN	25 ppm TWA; 110 mg/m3 TWA
	Mexico	No Established Limit
	Brazil	No Established Limit
Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
	ACGIH	10 mg/m3 TWA
	NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
	Supplier	No Established Limit
	OHSA, CAN	10 mg/m3 TWA (total dust)
	Mexico	No Established Limit
	Brazil	No Established Limit
Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
	ACGIH	10 mg/m3 TWA
	NIOSH	5000 mg/m3 IDLH
	Supplier	No Established Limit
	OHSA, CAN	10 mg/m3 TWA (total dust)
	Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
	Brazil	No Established Limit
Wollastonite (Ca(SiO3))	OSHA	No Established Limit
	ACGIH	No Established Limit
	NIOSH	No Established Limit
	Supplier	No Established Limit
	2-Butoxyethanol Ethylene glycol monopropyl ether Barium sulfate Titanium dioxide	2-Butoxyethanol OSHA ACGIH NIOSH Supplier OHSA, CAN OHSA, CAN Mexico Brazil Ethylene glycol monopropyl ether OSHA ACGIH NIOSH Supplier OHSA, CAN Mexico Brazil Barium sulfate OSHA ACGIH NIOSH NIOSH Supplier OHSA, CAN OSHA ACGIH NIOSH NIOSH Supplier OHSA, CAN OHSA, CAN Mexico Brazil Wollastonite (Ca(SiO3)) OSHA ACGIH NIOSH NIOSH

		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0014807-96-6	Talc	OSHA	No Established Limit
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	2 mg/m3 TWA (containing no Asbestos and
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	2 mg/m3 TWA (respirable fraction)
		Brazil	No Established Limit
TS-RE2404	Modified Epoxy Resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000111–76–2	2–Butoxyethanol	1	Adverse effects on blood and hematopoietic system tissue irritation
0002807-30-9	Ethylene glycol monopropyl ether	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	No Established Limit
0014807–96–6	Talc		(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
TS-RE2404	Modified Epoxy Resin	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value	
0000111–76–2	2-Butoxyethanol	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0002807-30-9	Ethylene glycol	OSHA	Select Carcinogen: No	
	monopropyl ether	NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;	
0013983-17-0 Wollastonite (Ca(SiO3))		OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0014807–96–6	Talc	OSHA	Select Carcinogen: No	

NHA218 A8

	i e		
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
TS-RE2404	Modified Epoxy Resin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site—specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls

Prevent build-up of vapors by opening all windows and doors to achieve

cross-ventilation.

Other Work Practices

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State Liquid Coloured pH No Established Limit

Specific Gravity 1.36 Boiling Point F 210

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous May produce hazardous fumes when heated to decomposition as in welding. Fumes

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
2-Butoxyethanol - (0000111-76-2)	470.00, Rat – Category: 4	220.00, Rabbit – Category: 3	2.21, Rat – Category: 3
Ethylene glycol monopropyl ether – (0002807–30–9)			

NHA218 A8

	3,089.00, Rat – Category: 5		
Barium sulfate - (0007727-43-7)			
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit - Category: NA	6,082.00, Rat – Category: NA
Wollastonite (Ca(SiO3)) - (0013983-17-0)			
Talc - (0014807-96-6)			
Modified Epoxy Resin – (TS-RE2404)			

General NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8

and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)
DOT Proper Shipping PAINT OR PAINT IMDG Proper Shipping PAINT OR PAINT

Name RELATED MATERIAL, Name RELATED MATERIAL, NMFC 149980 NMFC 149980

NMFC 149980 NMFC 149980 NMFC 149980 NR IMDG Hazard Class Not Regulated

UN / NA Number Not Regulated UN / NA Number Not Regulated DOT Packing Group Not Regulated IMDG Packing Group Not Regulated

CERCLA/DOT RQ 5872 gal. / 66667 lbs. System Reference 9

Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification No Established Limit

DOT Marine Pollutants (10%):

DOT Hazard Class

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

Nitrous acid, sodium salt (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

Barium

Nitrous acid, sodium salt

Mass RTK Substances (>1%):

Barium sulfate

2-Butoxyethanol

Talc

Titanium dioxide

Mass Extraordinarily Haz Sub (>.01%):

Quartz Penn RTK Substances (>1%): Barium sulfate 2-Butoxyethanol Talc Titanium dioxide Penn Special Hazardous Substances (>.01%): (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%): Barium 2-Butoxyethanol Diacetone alcohol Kaolin Mica Talc Titanium dioxide RCRA Status (%): N.J. RTK Substances (>1%): Barium sulfate 2-Butoxyethanol Talc Titanium dioxide N.J. Special Hazardous Substances (>.01%): Barium 2-Butoxyethanol Propylene glycol monomethyl ether N.J. Env. Hazardous Substances (>.1%): Barium Nitrous acid, sodium salt Proposition 65 – Carcinogens (>0%): 1,4-Dioxane Acetaldehyde Benzene, (chloromethyl)-Epichlorohydrin Ethylene oxide Lead Quartz Proposition 65 - Female Repro Toxins (>0%): Ethylene oxide Lead Proposition 65 – Male Repro Toxins (>0%): Epichlorohydrin Ethylene oxide Lead Proposition 65 – Developmental Toxins (>0%): Ethylene oxide Lead Risk Phrases: Not Applicable

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be

caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.