

SYA201_A0

Material Safety Data Sheet INTERFINE 979SG DARK GREY PART A



Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:

Sales
Order: {SalesOrd}
SYA201
05/17/2013
A0-

1. Identification of the preparation and company

Product Identity	INTERFINE 979SG DARK GREY PART A
Bulk Sales Reference No.	SYA201
Company Name	International Paint LLC 6001 Antoine Drive Houston, Texas 77091
Emergency	
CHEMTREC (USA)	(800) 424-9300
International Paint	(713) 682-1711
Poison Control Center	(800) 854-6813
Customer Service	
International Paint	(800) 589-1267
Fax No.	(800) 631-7481

2. Hazard identification of the product



Warning

GHS Classification:

Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	central nerve system, kidneys, systemic toxicity
	2	Not applicable
	3	respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung, respiratory system
	2	blood (circulatory system), liver, spleen
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable

SYA201_A0

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S20: When using do not eat or drink.

S24: Avoid contact with skin.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. Can result in irritation of the mouth, stomach tissue and digestive tract.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.
HMIS Rating	Health: 2 Flammability: 2 Reactivity: 0 PPE: X

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Isopropyl alcohol	0000067-63-0	1.0 – 10
Iron oxide	0001309-37-1	1.0 – 10
Barium sulfate	0007727-43-7	10 – 25
1,6-Hexanediol diacrylate	0013048-33-4	10 – 25
Titanium dioxide	0013463-67-7	1.0 – 10
Polyoestradiol phosphate	0028014-46-2	0.10 – 1.0
SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME	0068957-04-0	25 – 50
Silica gel, pptd., cryst.-free	0112926-00-8	1.0 – 10
Acrylated Urethane Oligomer	TS-KH6529	10 – 25

4. First aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

SYA201_A0

5. Fire-fighting measures

Flash Point F: 90
C: 32

Lower Explosive Limit (LEL) 1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No. 128

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

Public Safety CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No. 128

7. Handling and storage

Storage Temperature Store between 40-100F (4-38C).

Handling and Storage Precautions Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure			
CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl alcohol	OSHA	400 ppm TWA; 980 mg/m3 TWA500 ppm STEL; 1225 mg/m3 STEL
		ACGIH	200 ppm TWA400 ppm STEL
		NIOSH	400 ppm TWA; 980 mg/m3 TWA500 ppm STEL; 1225 mg/m3 STEL2000 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	200 ppm TWA400 ppm STEL
		Mexico	400 ppm TWA; 980 mg/m3 TWA500 ppm STEL; 1225 mg/m3 STEL
		Brazil	310 ppm TWA; 765 mg/m3 TWA
0001309-37-1	Iron oxide	OSHA	10 mg/m3 TWA (fume)
		ACGIH	5 mg/m3 TWA (respirable fraction)
		NIOSH	5 mg/m3 TWA (dust and fume, as Fe)2500 mg/m3 IDLH (dust and fume, as Fe)
		Supplier	No Established Limit
		OHSA, CAN	5 mg/m3 TWA (respirable)
		Mexico	5 mg/m3 TWA10 mg/m3 STEL (as Fe)
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA

SYA201_A0

		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0013048-33-4	1,6-Hexanediol diacrylate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
0028014-46-2	Polyoestradiol phosphate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0068957-04-0	SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0112926-00-8	Silica gel, pptd., cryst.-free	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA
		Brazil	No Established Limit
TS-KH6529	Acrylated Urethane Oligomer	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
---------	------------	--------	-------

SYA201_A0

0000067-63-0	Isopropyl alcohol	NIOSH	Mucous membrane irritation; possible carcinogenic effects
0001309-37-1	Iron oxide	NIOSH	Benign pneumoconiosis termed siderosis
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013048-33-4	1,6-Hexanediol diacrylate	NIOSH	No Established Limit
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0028014-46-2	Polyoestradiol phosphate	NIOSH	No Established Limit
0068957-04-0	SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME	NIOSH	No Established Limit
0112926-00-8	Silica gel, pptd., cryst.-free	NIOSH	No Established Limit
TS-KH6529	Acrylated Urethane Oligomer	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001309-37-1	Iron oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013048-33-4	1,6-Hexanediol diacrylate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0028014-46-2	Polyoestradiol phosphate	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068957-04-0	SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0112926-00-8	Silica gel, pptd., cryst.-free	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
TS-KH6529	Acrylated Urethane Oligomer	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other

SYA201_A0

manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State	Liquid Coloured
pH	No Established Limit
Specific Gravity	1.41
Boiling Point F	180
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether

10. Stability and reactivity

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Isopropyl alcohol – (0000067–63–0)	4,396.00, Rat – Category: 5	12,800.00, Rat – Category: NA	72.60, Rat – Category: NA
Iron oxide – (0001309–37–1)	10,000.00, Rat – Category: NA	-----	-----
Barium sulfate – (0007727–43–7)	-----	-----	-----
1,6–Hexanediol diacrylate – (0013048–33–4)	5,000.00, Rat – Category: 5	-----	-----
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA
Polyoestradiol phosphate – (0028014–46–2)	-----	-----	-----
SILOXANES AND SILICONES, DI–ME, METHOXY PH, POLYME – (0068957–04–0)	-----	-----	-----
Silica gel, pptd., cryst.–free – (0112926–00–8)	-----	-----	-----
Acrylated Urethane Oligomer – (TS–KH6529)	-----	-----	-----

General	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8
---------	--

SYA201_A0

and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3	IMDG Hazard Class	3 – Flammable and Combustible liquid
UN / NA Number	UN 1263	UN / NA Number	UN 1263
DOT Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	Not Applicable gal. / Not Applicable lbs.	System Reference Code	2

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2;D2B

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%):
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):
Isopropyl alcohol

Mass RTK Substances (>1%):
Barium sulfate
Iron oxide
Isopropyl alcohol
Silica gel, pptd., cryst.-free
Titanium dioxide

Mass Extraordinarily Haz Sub (>.01%):
Quartz

Penn RTK Substances (>1%):
Barium sulfate
Iron oxide
Isopropyl alcohol
Silica gel, pptd., cryst.-free
Titanium dioxide

Penn Special Hazardous Substances (>.01%):
(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%):
Iron oxide
Isopropyl alcohol

1,2-Propylene glycol

Titanium dioxide

RCRA Status (%):

N.J. RTK Substances (>1%) :

Barium sulfate

Iron oxide

Isopropyl alcohol

Silica gel, pptd., cryst.-free

Titanium dioxide

N.J. Special Hazardous Substances (>.01%) :

Isopropyl alcohol

Manganese

Phosphoric acid

Quartz

N.J. Env. Hazardous Substances (>.1%) :

Isopropyl alcohol

Proposition 65 – Carcinogens (>0%):

Cobalt

Nickel

Quartz

Proposition 65 – Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):

(No Product Ingredients Listed)

Risk Phrases:

R22: Harmful if swallowed.

R43: May cause sensitisation by skin contact.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.