

Safety Data Sheet
INTERLINE 604 PART B

Bulk Sales Reference No.: THA665
SDS Revision Date: 09/30/2015
SDS Revision Number: A0



1. Identification of the preparation and company

1.1. Product identifier

Product Identity INTERLINE 604 PART B
Bulk Sales Reference Number THA665

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint Ltda
ARGENTINA:
Ruta Panamericana Km 37,5
Garin, Buenos Aires
PO Box: B1606DQE
AKZONOBEL CHILE:
Calle Limache 3363 Local 3, El Salto
Viña del Mar, Chile
C.P. 2520642 - Rut 76.048140-8
BRAZIL:
Avenida Paiva, 999 - Neves
Sao Goncalo, RJ
24426-148 Brazil

Emergency

Suatrans Cotec 0800 7071 767 or 0800 7077 022 or 0800 172020 or
55*2*7500 (24 hr)

International Paint

ARGENTINA:
+54 3327 44 7777

CHILE:
+56 32 267 1174

BRAZIL:
+55 21 2199-7100

Poison Control Center (Brazil)

0800-0148110 or +55 11 3069-8800

Medical Service (Argentina)

+54 3327 44 7144 or +54 3327 44 7282

Firefighter/HSE (Argentina)

+54 3327 44 7123

Customer Service

ARGENTINA:
+54 3327 44 7777 Fax: +54 3327 44 7738

CHILE:
+56 32 267 1174 Fax: +56 32 263 1496

BRAZIL:
+55 21 2199-7100 Fax: +55 21 2199-7124

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226
Skin Irrit. 2;H315
Eye Dam. 1;H318
Skin Sens. 1;H317
Aquatic Acute 3;H402

2.2. Label elements

THA665_A0

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H402 Harmful to aquatic life.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapours / spray.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % |
|--|------------|
| CASHEW, NUTSHELL LIQ., POLYMER WITH DIETHYLENETRIAMINE CAS Number: 0068413-29-6 | 25 - 50 |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS Number: 0068609-97-2 | 10 - 25 |
| Butanol CAS Number: 0000071-36-3 | 10 - 25 |
| Benzyl alcohol CAS Number: 0000100-51-6 | 10 - 25 |
| Diethylene triamine CAS Number: 0000111-40-0 | 1.0 - 10 |
| Stoddard solvent CAS Number: 0008052-41-3 | 1.0 - 10 |
| Triethylene tetramine CAS Number: 0000112-24-3 | 0.10 - 1.0 |
| Tetraethylenepentamine CAS Number: 0000112-57-2 | 0.10 - 1.0 |

4. First aid measures

4.1. Description of first aid measures

General Remove contaminated clothing and shoes. Get medical attention immediately. Wash

THA665_A0

| | |
|------------|---|
| | clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------|--|
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| Chronic effects | Cancer hazard. Contains an ingredient which can cause cancer (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. |

| |
|---------------------------|
| 5. Fire-fighting measures |
|---------------------------|

5.1. Extinguishing media

| | |
|-------------------------------------|---|
| Appropriate Extinguishing Methods | Water in form of fog, Co2, foam or dry chemical dust. |
| Inappropriate Extinguishing Methods | Direct water spray into fire |
| Specific Hazards | Can liberate toxic fumes or gases during the burning. For decomposition see section 10. |

5.2. Special hazards arising from the substance or mixture

| | |
|-----------------|---|
| Special Methods | Evacuate the area and to fight the fire at a safe distance upwind. Use water in fog to cool containers near the fire. Keep runoff from entering sewer. Extinguishing water must be disposed according to local legislation. |
|-----------------|---|

5.3. Advice for fire-fighters

| | |
|------------------------|--|
| Firefighter Protection | In fire case, to use personal respiratory device and suits for protection. |
|------------------------|--|

| |
|--------------------------------|
| 6. Accidental release measures |
|--------------------------------|

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|----------------------|---|
| Personal precautions | ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. |
| Public Safety | Call Suatrans Cotec 0800 7071 767 or 0800 7077 022 or 0800 17 2020 or 55*2*7500 (24 hr) for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. |

6.2. Environmental precautions

| | |
|---------------------------|---|
| Environmental Precautions | Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. |
|---------------------------|---|

6.3. Methods and material for containment and cleaning up

| | |
|-----------------|---|
| Clean Up Method | Cover with sand or other non-cumbustible material. Transfer absorbed material with a non-sparking tool. |
|-----------------|---|

| |
|-------------------------|
| 7. Handling and storage |
|-------------------------|

7.1. Precautions for safe handling

THA665_A0

Handle the packages with care in order to avoid damage and spillage.

Be aware of the precautions referred to on the label.

Avoid contact with the eyes and the skin. Avoid swallowing of vapor and the pulverizations. Be aware of the precautions referred to on the label. Use personal protection equipment according to the section 8.

No smoking, drinking or eating in the application areas.

All the ignition sources (hot surfaces, sparks, unprotected flames, etc.) must be excluded from the areas of manufacturing and application. The storage areas, the preparation and the application must be well ventilated.

The product can be carried electrostatically. Always use grounding cables when transferring solvents or product. The operators must use adequate outfits which shall not develop static current. (at least 60% of natural fiber) and anti-static shoes.

Solvents based products: The solvent vapors are heavier than the air and can concentrate on the floor and explosive mixtures may be formed with the air .

Water based products: It does not require special cares for not being inflammable or explosive. Use only the indicated personal protection equipments.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---------------------------------|
| 0000071-36-3 | Butanol | ACGIH | 20 ppm TWA |
| | | Brazil | 40 ppm TWA LT; 115 mg/m3 TWA LT |
| 0000100-51-6 | Benzyl alcohol | ACGIH | |
| | | Brazil | |
| 0000111-40-0 | Diethylene triamine | ACGIH | 1 ppm TWA |
| | | Brazil | |
| 0000112-24-3 | Triethylene tetramine | ACGIH | |
| | | Brazil | |
| 0000112-57-2 | Tetraethylenepentamine | ACGIH | |
| | | Brazil | |
| 0008052-41-3 | Stoddard solvent | ACGIH | 100 ppm TWA |
| | | Brazil | |
| 0068413-29-6 | CASHEW, NUTSHELL LIQ., POLYMER WITH DIETHYLENETRIA | ACGIH | |
| | | Brazil | |
| 0068609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | ACGIH | |
| | | Brazil | |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| 0000071-36-3 | Butanol | NIOSH | Eye and mucous membrane irritation CNS depression |
| 0000100-51-6 | Benzyl alcohol | NIOSH | |
| 0000111-40-0 | Diethylene triamine | NIOSH | Skin and respiratory irritation and sensitization |
| 0000112-24-3 | Triethylene tetramine | NIOSH | |
| 0000112-57-2 | Tetraethylenepentamine | NIOSH | |
| 0008052-41-3 | Stoddard solvent | NIOSH | Eye nose |
| 0068413-29-6 | CASHEW, NUTSHELL LIQ., POLYMER WITH DIETHYLENETRIA | NIOSH | |
| 0068609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | NIOSH | |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|------------|--------|--|
| 0000071-36-3 | Butanol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

THA665_A0

| | | | |
|--------------|--|------|--|
| 0000100-51-6 | Benzyl alcohol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000111-40-0 | Diethylene triamine | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000112-24-3 | Triethylene tetramine | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000112-57-2 | Tetraethylenepentamine | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0008052-41-3 | Stoddard solvent | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0068413-29-6 | CASHEW, NUTSHELL LIQ., POLYMER WITH DIETHYLENETRIA | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0068609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

| | |
|--------------------------|---|
| Respiratory Protection | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. |
| Eye and face protection | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 8 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin and body protection | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 8 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls | Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. |
| Special Precautions | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

9. Physical and chemical properties

| | |
|---|----------------------|
| Appearance | Yellow Liquid |
| Odour threshold | Not Measured |
| pH | No Established Limit |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 110 (°C) 230 (°F) |
| Flash Point | 51 (°C) 124 (°F) |
| Evaporation rate (Ether = 1) | Not Measured |

THA665_A0

| | |
|---|--|
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: .6 Upper Explosive Limit: No Established Limit |
| Vapour pressure (Pa) | Not Measured |
| Vapor Density | Heavier than air |
| Specific Gravity | 0.94 |
| Solubility in Water | Not Measured |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | No Established Limit Not Measured |
| VOC % | Refer to the Technical Data Sheet or label where information is available. |

| |
|-------------------------------------|
| 10. Stability and reactivity |
|-------------------------------------|

10.1. Reactivity

Keep away from alkaline or strong strong acid to prevent probable exothermal reactions.

10.2. Chemical stability

This product is stable

10.3. Possibility of hazardous reactions

Dangerous Polymerization will not occur. Heat and vapors in excess can be generated when improperly used.

10.4. Conditions to avoid

Keep away from alkaline or strong strong acid to prevent probable exothermal reactions.

Strong oxidizing agents

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Can liberate toxic vapors in the welding process. The vapors can produce Dioxide and Monoxide of Carbon.

| |
|--------------------------------------|
| 11. Toxicological information |
|--------------------------------------|

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 3 and 8 for chemical specific data.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|---|-----------------------------|--------------------------------|---------------------------------|-------------------------------------|
| CASHEW, NUTSHELL LIQ., POLYMER WITH DIETHYLENETRIA - (68413-29-6) | No data available | No data available | No data available | No data available |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. - (68609-97-2) | No data available | No data available | No data available | No data available |
| Butanol - (71-36-3) | 2,292.00, Rat - Category: 5 | 3,430.00, Rabbit - Category: 5 | No data available | No data available |
| Benzyl alcohol - (100-51-6) | 1,230.00, Rat - Category: 4 | 2,000.00, Rabbit - Category: 4 | No data available | 4.178, Rat - Category: 4 |
| Diethylene triamine - (111-40-0) | 1,080.00, Rat - Category: 4 | 1,090.00, Rabbit - Category: 4 | No data available | No data available |
| Stoddard solvent - (8052-41-3) | No data available | No data available | No data available | No data available |
| Triethylene tetramine - (112-24-3) | 2,780.00, Rat - Category: 5 | 550.00, Rabbit - Category: 3 | No data available | No data available |
| Tetraethylenepentamine - (112-57-2) | 2,140.00, Rat - Category: 5 | No data available | No data available | No data available |

| | | |
|------|----------|--------|
| Item | Category | Hazard |
|------|----------|--------|

THA665_A0

| | | |
|---|----------------|--------------------------------------|
| Acute Toxicity (mouth) | Not Classified | Not Applicable |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | 2 | Causes skin irritation. |
| Eye damage/irritation | 1 | Causes serious eye damage. |
| Sensitization (respiratory) | | Not Applicable |
| Sensitization (skin) | 1 | May cause an allergic skin reaction. |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | | Not Applicable |
| Reproductive Toxicity | | Not Applicable |
| Specific target organ systemic toxicity (single exposure) | | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 199/45/CE and is classified according to the same as for the environment. For details, see sections 8 and 11. There are no data available on the product. Avoid contamination of drains or watercourses

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|---|-------------------------------|----------------------------|---|
| CASHEW, NUTSHELL LIQ., POLYMER WITH DIETHYLENETRIA - (68413-29-6) | Not Available | Not Available | Not Available |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. - (68609-97-2) | Not Available | Not Available | Not Available |
| Butanol - (71-36-3) | 1,376.00, Pimephales promelas | 1,328.00, Daphnia magna | 500.00 (96 hr), Scenedesmus subspicatus |
| Benzyl alcohol - (100-51-6) | 10.00, Lepomis macrochirus | 55.00, Daphnia magna | 700.00 (72 hr), Algae |
| Diethylene triamine - (111-40-0) | 1,014.00, Poecilia reticulata | 53.50, Daphnia magna | 345.60 (96 hr), Pseudokirchneriella subcapitata |
| Stoddard solvent - (8052-41-3) | Not Available | Not Available | Not Available |
| Triethylene tetramine - (112-24-3) | 495.00, Pimephales promelas | 33.90, Daphnia magna | 20.00 (72 hr), Selenastrum capricornutum |
| Tetraethylenepentamine - (112-57-2) | 420.00, Poecilia reticulata | 24.00, Daphnia magna | 2.00 (72 hr), Pseudokirchneriella subcapitata |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

THA665_A0

13.1. Waste treatment methods

General Note: Disposal must be in accordance with the federal, state and local regulations.
 Method of treatment and disposal Product: The treatment and the disposal of the product must in accordance the local legislation.
 Remaining portions of the product: Residues that will not be used must be discarded in accordance the local legislation. Used packing: Do not reuse the packing. Recycle if appropriate or discard in accordance the local legislation.

14. Transport information

14.1. UN number UN 1789
 14.2. UN proper shipping name HYDROCHLORIC ACID SOLUTION
 14.3. Transport hazard class(es)

| Domestic Surface Transportation | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------|----------------------------|-----------------------------------|--|
| Proper Shipping Name | HYDROCHLORIC ACID SOLUTION | IMDG Proper Shipping Name | HYDROCHLORIC ACID |
| Hazard Class | 8 | IMDG Hazard Class | Class 8, No division Corrosive materials |
| UN / NA Number | UN 1789 | UN / NA Number | UN 1789 |
| Packaging Group | II | IMDG Packing Group | II |
| CERCLA/DOT RQ | 4381 gal. / 34483 lbs. | System Reference Code | 6 |
| Risk Number | 80 | EMS | |
| | | Marine Pollutant | No |

Air Transport (ICAO-ITI / IATA-DGR)

| | |
|----------------------|----------------------------|
| Proper Shipping Name | HYDROCHLORIC ACID SOLUTION |
| Hazard Class | 8 |
| UN / NA Number | UN 1789 |
| Packaging Group | II |

14.4. Packing group II

14.5. Environmental hazards
 IMDG Marine Pollutant: No

14.6. Special precautions for user
 Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
 Not Applicable

15. Regulatory information

Regulatory Overview Decreto 2.657, from 3/07/98, regarding the Safety in the Utilization of Chemical Products at Work.
 Act # 96.044 of 18/05/88. Regulations of Road Transport of Dangerous Products.
 Decreto 1.797, of 25/01/1996, Bill of Hazardous Products in the Mercosul range.
 Resolution ANTT # 420, of 12/02/2004: complementary instructions to the Regulation of Road Transport of Hazardous Products.
 Decreto 3214 of MTE
 NBR 7500: Identification for the road transport, the handling, the moving and the storage of products.
 NBR 7501: Terminology Transport of Hazardous Products.
 NBR 7503: Road transport of hazardous products emergency form and envelope Features, dimensions and filling.
 NBR 9735: Set of equipments for Emergency in the Road Transport of Hazardous Products Procedures. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3 D2B E

16. Other information

THA665_A0

The information contained in this Material Safety Data Sheet (MSDS) has the purpose of being a description of the product safety requirements, which were obtained from the literature and current legislation specific about raw materials/ingredients. Thus, the accuracy of the data contained herein is not, expressly or implicitly, assured by the Manufacturer. The product shall not be used for purposes other than the ones specified by the Manufacturer. The user is always liable for taking all required measures to comply with the provisions in this MSDS, as well as with the requirements expressed in the regulations and effective legislation.

Bibliographic references:

- Council Directive 67/548/EEC of June 27, 1967.
- Work and Job department clause # 3.214 of June 08, 1978.
- ABNT NBR 14725 (parts I,II,III and IV) Chemical products Information on safety, health and environment.

Specific use: product meant only for professional use, check the product data sheet.

CAS: Chemical Abstract Service register number It s a register number indicated by the American Chemical Society, which identifies only a specific chemical component.

THA665_A0

End of Document



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : www.yachtpaint.com , www.international-marine.com, www.international-pc.com