Material Safety Data Sheet INTERLAC 537V BLUE WHITE

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: Sales Order: {SalesOrd} CIA105 06/26/2013 A0-2

XInternational.

	1. Identification of the preparation and company				
Product Identity	INTERLAC 537V BLUE WHITE				
Bulk Sales Reference No.	CIA105				
Company Name	International Paint LLC				
	6001 Antoine Drive				
	Houston, Texas 77091				
F					
Emergency					
CHEMTREC (USA)	(800) 424–9300				
International Paint	(713) 682–1711				
Poison Control Center	(800) 854–6813				
Customer Service					
International Paint	(800) 589–1267				
Fax No.	(800) 631–7481				

2. Hazard identification of the product



Danger	
--------	--

CHE Classification:	Dang	
GHS Classification; Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	Not applicable
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects

Carcinogenicity	1A	May cause cancer
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.				
Inhalation		Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.			
Eyes	Causes severe eye irritation. Avoid contact with eyes.				
Skin	Causes skin irritation. May be harmful if absorbed through the skin.				
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.				
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.				
HMIS Rating	Health: 2	Flammability: 2	Reactivity: 0	PPE: X	

3. Composition/information on ingredients				
Ingredient	CAS No.	Percent		
1,2,4–Trimethyl benzene	0000095-63-6	1.0 – 10		
p-Chloro-a,a,a-trifluorotoluene	0000098-56-6	10 – 25		
Methyl n–amyl ketone	0000110-43-0	1.0 – 10		
Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic acid, 1,4,5,6,7,7-hexachloro-	0000115-28-6	0.10 – 1.0		
Titanium dioxide	0013463–67–7	10 – 25		
Quartz	0014808-60-7	0.10 - 1.0		
Aluminum hydroxide	0021645-51-2	10 – 25		
Petroleum naphtha	0064742-95-6	1.0 – 10		
Talc (*non-asbestiform)	14807–96–6*	1.0 – 10		
ALKYD RESIN (PROPRIETARY)	Proprietary	25 – 50		

This product contains 0.16 percent Quartz.

	4. First aid measures
General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
	5. Fire-fighting measures

Lower Explosive Limit ERG Guide No.	(LEL) .7 (%vol in air) at Normal Atmospheric Temp and Pressure 128	
	6. Accidental release measures	
Spill Response Procedures	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.	
Public Safety	CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).	
ERG Guide No.	128	
	7. Handling and storage	
Storage Temperature	Store between 40–100F (4–38C).	
Handling and Storage Precautions	Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build–up of vapors by opening all windows and doors to achieve cross–ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling	

contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

	Exposure				
CAS No.	Ingredient	Source	Value		
0000095–63–6 1	1,2,4–Trimethyl benzene	OSHA	No Established Limit		
		ACGIH	No Established Limit		
		NIOSH	25 ppm TWA; 125 mg/m3 TWA		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
0000098–56–6 p	-Chloro-a,a,a-trifluorotoluene	OSHA	No Established Limit		
		ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
0000110–43–0 N	lethyl n–amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA		
		ACGIH	50 ppm TWA		
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH		
		Supplier	No Established Limit		
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA		
		Mexico	50 ppm TWA; 235 mg/m3 TWA100 ppm STEL; 465 mg/m3 STEL		
		Brazil	No Established Limit		

0000115–28–6	Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic	OSHA	No Established Limit
	acid, 1,4,5,6,7,7-hexachloro-	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
0014808-60-7	Quartz	OSHA	No Established Limit
		ACGIH	0.025 mg/m3 TWA (respirable fraction)
		NIOSH	0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	0.10 mg/m3 TWA (designated substance regulation, respirable)0.10 mg/m3 TWA (respirable fraction)
		Mexico	0.1 mg/m3 TWA (respirable fraction)
		Brazil	No Established Limit
021645 51 2	Aluminum hydroxide	OSHA	No Established Limit
5021045-51-2		ACGIH	No Established Limit
		NIOSH	No Established Limit
			No Established Limit
		Supplier OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
064742_95_6	Petroleum naphtha	OSHA	No Established Limit
5004742-55-0	r euoleum naphtna	ACGIH	No Established Limit
		NIOSH	No Established Limit
			No Established Limit
		Supplier	
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
14807–96–6*	Talc (*non-asbestiform)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
Proprietary	ALKYD RESIN (PROPRIETARY)	OSHA	No Established Limit
-		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
	1		

Brazil No Established Limit

Health Data				
CAS No.	Ingredient	Source	Value	
0000095-63-6	1,2,4–Trimethyl benzene	NIOSH	No Established Limit	
0000098-56-6	p–Chloro–a,a,a–trifluorotoluene	NIOSH	No Established Limit	
0000110-43-0	Methyl n–amyl ketone	NIOSH	Irritation; liver kidney	
	Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic acid, 1,4,5,6,7,7-hexachloro-	NIOSH	No Established Limit	
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals	
0014808-60-7	Quartz	NIOSH	Chronic lung disease (silicosis)	
0021645-51-2	Aluminum hydroxide	NIOSH	No Established Limit	
0064742-95-6	Petroleum naphtha	NIOSH	No Established Limit	
14807–96–6*	Talc (*non-asbestiform)	NIOSH	No Established Limit	
Proprietary	ALKYD RESIN (PROPRIETARY)	NIOSH	No Established Limit	

_|

CAS No.	Carcinogen I Ingredient	Source	Value
	1,2,4–Trimethyl benzene		Select Carcinogen: No
0000090-00-0		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group
			2b: No; Group 3: No; Group 4: No;
0000098-56-6	p-Chloro-a,a,a-trifluorotoluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group
			2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl n–amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000115–28–6	Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic	OSHA	Select Carcinogen: Yes
	acid, 1,4,5,6,7,7-hexachloro-	NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0013463–67–7		OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0014808–60–7		OSHA	Select Carcinogen: Yes
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group
			2b: No; Group 3: No; Group 4: No;
0021645–51–2	Aluminum hydroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742–95–6		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
14807–96–6*	Talc (*non-asbestiform)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	ALKYD RESIN (PROPRIETARY)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group
			2b: No; Group 3: No; Group 4: No;

Carcinogen Data

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

	9. Physical and chemical properties
Physical State	Liquid Coloured
рН	No Established Limit
Specific Gravity	1.65
Boiling Point F	152
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether
	10. Stability and reactivity
General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly

	handled.	
Incompatible Materials	Strong oxidizing agents.	
Hazardous	May produce hazardous fumes when heated to decomposition as in welding. Fume	s
Decomposition	may produce Carbon Dioxide and Carbon Monoxide.	

11. Toxicological information				
Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	
1,2,4–Trimethyl benzene – (0000095–63–6)	3,400.00, Rat – Category: 5	3,160.00, Rabbit - Category: 5		
p-Chloro-a,a,a-trifluorotoluene - (0000098-56-6)	13,000.00, Rat – Category: NA	2,700.00, Rabbit - Category: 5	33.00, Rat – Category: NA	
Methyl n-amyl ketone - (0000110-43-0)	1,670.00, Rat – Category: 4			
Bicyclo[2.2.1]hept–5–ene–2,3–dicarboxylic acid, 1,4,5,6,7,7–hexachloro– – (0000115–28–6)				
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA	
Quartz – (0014808–60–7)				

	500.00, Rat – Category: 4		
Aluminum hydroxide – (0021645–51–2)	5,000.00, Rat – Category: 5		
Petroleum naphtha – (0064742–95–6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit - Category: 4	5.20, Rat – Category: 3
Talc (*non-asbestiform) - (14807-96-6*)			
ALKYD RESIN (PROPRIETARY) – (Proprietary)			

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

	14. Transpo	ort information			
DOT (Domestic Su	Irface Transportation)	IMO / IMDG (Oce	ean Transportation)		
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT		
DOT Hazard Class	3	IMDG Hazard Class	3 – Flammable and Combustible liquid		
UN / NA Number	UN 1263	UN / NA Number	UN 1263		
DOT Packing Group	111	IMDG Packing Group	III		
CERCLA/DOT RQ	Not Applicable gal. / Not Applicable lbs.	System Reference Code	1		
	15. Regulate	ory information			
Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.					
WHMIS Classification	B3:D2B				
DOT Marine Pollutants (No Product Ingr					
DOT Severe Marine Po (No Product Ingr					
EPCRA 311/312 Chem (No Product Ingr					
EPCRA 302 Extremely (No Product Ingr					
EPCRA 313 Toxic Che	micals (>.1%) :				
1,2,4–Trimethyl benzene					
Bicyclo[2	.2.1]hept-5-ene-2,3-dicarbox	ylic acid, 1,4,5,6,7,7–hexachloi	ro-		
Cyclohex	anol				
Mass RTK Substances	(>1%):				
1,2,4–Tri	methyl benzene				
,	-amyl ketone				
Titanium dioxide					
Mass Extraordinarily H	az Sub (>.01%) :				

Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic acid, 1,4,5,6,7,7-hexachloro-Quartz Silica. cristobalite Penn RTK Substances (>1%) : 1,2,4-Trimethyl benzene Methyl n-amyl ketone Titanium dioxide Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%) : Cyclohexanol Methyl n-amyl ketone Propylene glycol monomethyl ether Quartz Stoddard solvent Titanium dioxide **RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%) : 1,2,4-Trimethyl benzene Methyl n-amyl ketone Titanium dioxide N.J. Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic acid, 1,4,5,6,7,7-hexachloro-Naphthalene Propylene glycol monomethyl ether Quartz Silica, cristobalite Solvent naphtha (petroleum), medium aliphatic N.J. Env. Hazardous Substances (>.1%) : 1,2,4-Trimethyl benzene Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic acid, 1,4,5,6,7,7-hexachloro-Cyclohexanol Proposition 65 - Carcinogens (>0%): Bicyclo[2.2.1]hept-5-ene-2,3-dicarboxylic acid, 1,4,5,6,7,7-hexachloro-Naphthalene Quartz Proposition 65 – Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): (No Product Ingredients Listed) **Risk Phrases:**

R45: May cause cancer.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.