

2200RX_A5

Material Safety Data Sheet INTERZINC 22 HYDROLYSATE INTERMEDIATE

Sales
Order: {SalesOrd}
2200RX
05/12/2011
A5-3

Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:



1. Identification of the preparation and company

Product Identity INTERZINC 22 HYDROLYSATE INTERMEDIATE
Bulk Sales Reference No. 2200RX
Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency
CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product



Danger

GHS Classification:

Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	blood (circulatory system), respiratory system
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	liver, respiratory system, teeth
	2	kidneys, liver, respiratory system
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable

2200RX_A5

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	1A	May damage fertility or the unborn child.
Organic Peroxide	Not classified	Not applicable

Safety Phrases: Not Applicable

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.			
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.			
Eyes	Causes severe eye irritation. Avoid contact with eyes.			
Skin	Causes skin irritation. May be harmful if absorbed through the skin.			
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.			
Chronic effects	Birth defect hazard. Contains an ingredient which can cause birth defects (See Section 2 and Section 15 for each ingredient).			
HMIS Rating	Health: 1	Flammability: 0	Reactivity: 0	PPE: X

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Ethyl alcohol	0000064-17-5	1.0 – 10
Ethyl silicate	0000078-10-4	10 – 25
Propylene glycol monomethyl ether	0000107-98-2	25 – 50
Hydrochloric acid	0007647-01-0	1.0 – 10
Silicic acid, ethyl ester	0011099-06-2	25 – 50

4. First aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Flash Point	F: 94 C: 34
Lower Explosive Limit (LEL)	1.6 (%vol in air) at Normal Atmospheric Temp and Pressure
ERG Guide No.	Not Determined

6. Accidental release measures

Spill Response Procedures	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry
---------------------------	---

2200RX_A5

earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

Public Safety CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No. Not Determined

7. Handling and storage

Storage Temperature Store between 40–100F (4–38C).

Handling and Storage Precautions Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure			
CAS No.	Ingredient	Source	Value
0000064–17–5	Ethyl alcohol	OSHA	1000 ppm TWA; 1900 mg/m3 TWA
		ACGIH	1000 ppm STEL
		NIOSH	1000 ppm TWA; 1900 mg/m3 TWA3300 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	1000 ppm STEL
		Mexico	1000 ppm TWA; 1900 mg/m3 TWA
		Brazil	780 ppm TWA; 1480 mg/m3 TWA
0000078–10–4	Ethyl silicate	OSHA	100 ppm TWA; 850 mg/m3 TWA
		ACGIH	10 ppm TWA
		NIOSH	10 ppm TWA; 85 mg/m3 TWA700 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 ppm TWA
		Mexico	10 ppm TWA; 85 mg/m3 TWA30 ppm STEL; 255 mg/m3 STEL
		Brazil	No Established Limit
0000107–98–2	Propylene glycol monomethyl ether	OSHA	150 ppm STEL; 540 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	100 ppm TWA; 360 mg/m3 TWA150 ppm STEL; 540 mg/m3 STEL
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	No Established Limit
		Brazil	No Established Limit
0007647–01–0	Hydrochloric acid	OSHA	5 ppm Ceiling; 7 mg/m3 Ceiling
		ACGIH	2 ppm Ceiling
		NIOSH	5 ppm Ceiling; 7 mg/m3 Ceiling50 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	2 ppm Ceiling
		Mexico	No Established Limit
		Brazil	No Established Limit
0011099–06–2	Silicic acid, ethyl ester	OSHA	No Established Limit
		ACGIH	No Established Limit

2200RX_A5

		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000064-17-5	Ethyl alcohol	NIOSH	Eye respiratory
0000078-10-4	Ethyl silicate	NIOSH	Eye and nose irritation; lung liver
0000107-98-2	Propylene glycol monomethyl ether	NIOSH	Eye nose
0007647-01-0	Hydrochloric acid	NIOSH	Eye mucous membrane
0011099-06-2	Silicic acid, ethyl ester	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000064-17-5	Ethyl alcohol	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000078-10-4	Ethyl silicate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000107-98-2	Propylene glycol monomethyl ether	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007647-01-0	Hydrochloric acid	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0011099-06-2	Silicic acid, ethyl ester	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	

2200RX_A5

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State	Liquid Coloured
pH	No Established Limit
Specific Gravity	1.00
Boiling Point F	212
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether

10. Stability and reactivity

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Ethyl alcohol – (0000064–17–5)	7,060.00, Rat – Category: NA	-----	124.70, Rat – Category: NA
Ethyl silicate – (0000078–10–4)	6,270.00, Rat – Category: NA	-----	-----
Propylene glycol monomethyl ether – (0000107–98–2)	5,200.00, Rat – Category: NA	13,000.00, Rabbit – Category: NA	54.60, Rat – Category: NA
Hydrochloric acid – (0007647–01–0)	700.00, Rat – Category: 4	5,010.00, Rabbit – Category: NA	-----
Silicic acid, ethyl ester – (0011099–06–2)	-----	-----	-----

General	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.
---------	---

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) DOT Proper Shipping Name DOT Hazard Class UN / NA Number	IMO / IMDG (Ocean Transportation) IMDG Proper Shipping Name IMDG Hazard Class UN / NA Number
---	---

2200RX_A5

DOT Packing Group
CERCLA/DOT RQ 48822 gal. / 408163
lbs.

IMDG Packing Group
System Reference 0
Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification No Established Limit

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

- Hydrochloric acid (5000 lb final RQ; 2270 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :

- Hydrochloric acid (500 lb TPQ (gas only))

EPCRA 313 Toxic Chemicals (>.1%) :

- Hydrochloric acid

Mass RTK Substances (>1%) :

- Ethyl alcohol
- Ethyl silicate
- Hydrochloric acid
- Propylene glycol monomethyl ether

Mass Extraordinarily Haz Sub (>.01%) :

- Hydrochloric acid

Penn RTK Substances (>1%) :

- Ethyl alcohol
- Ethyl silicate
- Hydrochloric acid
- Propylene glycol monomethyl ether
- Silicic acid, ethyl ester

Penn Special Hazardous Substances (>.01%) :

(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%) :

- Ethyl alcohol
- Ethyl silicate
- Hydrochloric acid
- Propylene glycol monomethyl ether

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

- Ethyl alcohol
- Ethyl silicate
- Hydrochloric acid
- Propylene glycol monomethyl ether

N.J. Special Hazardous Substances (>.01%) :

- Ethyl alcohol
- Ethyl silicate
- Hydrochloric acid
- Propylene glycol monomethyl ether

N.J. Env. Hazardous Substances (>.1%) :

- Hydrochloric acid

Proposition 65 – Carcinogens (>0%):
(No Product Ingredients Listed)

2200RX_A5

Proposition 65 – Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):
Ethyl alcohol

Risk Phrases:

R61: May cause harm to the unborn child.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.