In accordance with the Standard for Classification and Labelling of Chemical Substance and Material Safety Data Sheet, Article 10 Paragraph

SAFETY DATA SHEET

Intershield 7100LWT Buff Part A

Section 1. Chemical product and company identification

- A. Product name
- : Intershield 7100LWT Buff Part A
- **Product code** : EGA760

B. Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Professional application of coatings and inks			
Uses advised against	Reason		
All Other Uses			

C. Manufacturer	: International Paint Ltd. Stoneygate Lane Felling Gateshead Tyne and Wear NE10 0JY UK Tel: +44 (0)191 469 6111	Fax: +44 (0)191 438 3711
Emergency telephone number (with hours of operation)	: +44 (0)191 469 6111 (24H)	
e-mail address of person responsible for this SDS	: sdsfellinguk@akzonobel.com	

Section 2. Hazards identification

A. Hazard classification	: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
	SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION (Fertility) - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2 LONG-TERM AQUATIC HAZARD - Category 2

B. GHS label elements, including precautionary statements :

Symbol

٠



Signal word : Warning Hazard statements : Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Toxic to aquatic life with long lasting effects.

Precautionary statements

AkzoNobel

K.International.

Section 2. Hazards identification

Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	:	Collect spillage. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	
C. Other hazards which do not result in classification	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	Common name	CAS number	%	Classification
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	phenoxy resin	25068-38-6	≥50 - <60	Skin Irrit. 2, H315
				Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
aluminium hydroxide	aluminum hydroxide	21645-51-2	≥5 - <10	Not classified.
2,2-bis(acryloyloxymethyl)butyl acrylate	trimethylolpropane triacrylate	15625-89-5	<10	Skin Irrit. 2, H315
				Eye Irrit. 2, H319 Skin Sens. 1, H317
diboron calcium tetraoxide	calcium metaborate	13701-64-9	<10	Eye Irrit. 2, H319
Phenol, isopropylated, phosphate (3:1)	phenol, isopropylated, phosphate (3:1)	68937-41-7	<10	Repr. 2, H361fd (Fertility and Unborn child) STOT RE 2, H373 Aquatic Chronic 2, H411
Man-made vitreous (silicate) fibres	Man-made vitreous (silicate) fibres	287922-11-6	<10	Skin Irrit. 2, H315

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

:



Section 4. First-aid measures

Α.	Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
В.	Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
C.	Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
D.	Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
E.	Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	Specific treatments	:	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Α.	Extinguishing media		
	Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
	Unsuitable extinguishing media	:	None known.
В.	Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

:

X.International.

Section 5. Fire-fighting measures

C.	Special protective equipment for fire- fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Special precautions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

C. Methods and material for containment and cleaning up

- Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop
up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry
material and place in an appropriate waste disposal container. Dispose of via a
licensed waste disposal contractor.
- Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

A. Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



Section 7. Handling and storage

B. Conditions for safe storage, including any incompatibilities
 Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

A. <u>Control parameters</u>

Occupational exposure limits

Ingredient name	Exposure limits
aluminium hydroxide	ACGIH TLV (United States, 3/2015). TWA: 1 mg/m ³ 8 hours. Form: Respirable fraction

В.	Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
	Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
C.	Personal protective equip	om	ent
	Respiratory protection	:	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
	Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
	Hand protection	:	Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

1



X.International.

Section 8. Exposure controls/personal protection

```
Hygiene measures
```

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	Not available.
Odour	:	Solvent.
Odour threshold	:	Not available.
рН	:	Not applicable.
Melting/freezing point	:	Not available.
Boiling point/boiling range	:	Not available.
Flash point	:	Closed cup: 93°C (199.4°F)
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Vapour pressure	:	Not available.
Solubility	:	Insoluble in the following materials: cold water.
Vapour density	:	Not available.
Relative density	:	1.39
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (room temperature): 101 mm ² /s (101 cSt)
Molecular weight	:	Not applicable.
	Colour Odour Odour threshold pH Melting/freezing point Boiling point/boiling range Flash point Evaporation rate Flammability (solid, gas) Lower and upper explosive (flammable) limits Vapour pressure Solubility Vapour density Relative density Relative density Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition	Physical state:Colour:Odour threshold:Ddour threshold:pH:Melting/freezing point:Boiling point/boiling:range:Flash point:Evaporation rate:Flammability (solid, gas):Lower and upper:explosive (flammable):limits:Vapour pressure:Solubility:Vapour density:Relative density:Partition coefficient: n- octanol/water:Auto-ignition temperature:Viscosity:

Section 10. Stability and reactivity

Α.	Chemical stability Possibility of hazardous reactions		The product is stable. Under normal conditions of storage and use, hazardous reactions will not occur.
В.	Conditions to avoid	:	No specific data.
C.	Incompatible materials	:	No specific data.
D.	Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

٠

Α.

X.International.

Section 11. Toxicological information

:	Not available.
ect	<u>s</u>
:	No known significant effects or critical hazards.
:	Irritating to mouth, throat and stomach.
:	Causes skin irritation. May cause an allergic skin reaction.
:	Causes serious eye irritation.
pt	oms
:	Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
:	Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
:	Adverse symptoms may include the following: irritation redness reduced foetal weight increase in foetal deaths skeletal malformations
:	Adverse symptoms may include the following: pain or irritation watering redness
	ect : : : : : :

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2-bis(acryloyloxymethyl) butyl acrylate	LD50 Dermal	Rabbit	5170 mg/kg	-
Phenol, isopropylated, phosphate (3:1)	LD50 Dermal	Rabbit	>10000 mg/kg	-
	LD50 Oral	Rat	>20000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
2,2-bis(acryloyloxymethyl) butyl acrylate	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-

:

Version 2 :

AkzoNobel



Section 11. Toxicological information

	•				
Phenol, isopropylated, phosphate (3:1)	Eyes - Mild irritant	Rabbit	-	0.1 Mililiters	-

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	· · · · · · · ·	Route of exposure	Target organs
Phenol, isopropylated, phosphate (3:1)	Category 2	Not determined	Not determined

Aspiration hazard

Not available.

Potential chronic health effects

Chronic toxicity

Not available.

General	nce sensitized, a severe allergic reaction may occur when subsequently exposed overy low levels.	
Carcinogenicity	o known significant effects or critical hazards.	
Mutagenicity	o known significant effects or critical hazards.	
Teratogenicity	uspected of damaging the unborn child.	
Developmental effects	o known significant effects or critical hazards.	
Fertility effects	uspected of damaging fertility.	

ATE value

Not available.

Section 12. Ecological information

A. Ecotoxicity

:

Not available.

B. Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin	-	-	Not readily



Section 12. Ecological information

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin	2.64 to 3.78	-	low
2,2-bis(acryloyloxymethyl) butyl acrylate	0.67	-	low
Phenol, isopropylated, phosphate (3:1)	4.92 to 5.17	-	high

D. <u>Mobility in soil</u>

Soil/water partition : Not available. coefficient (K_{oc})

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Α.	Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
В.	Disposal precautions	: This material and its container must be disposed of in a safe way. Care should be

B. Disposal precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
A. UN number	UN3082	UN3082	UN3082
B. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Phenol, isopropylated, phosphate (3:1)). Marine pollutant (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Phenol, isopropylated, phosphate (3:1))
C. Transport hazard class(es)	9	9	9
D. Packing group		III	

Version 2 :

X.International.

Section 14. Transport information

E. Environmental hazards	Yes.	Yes.	Yes.
F. Additional information	This product is not regulated	This product is not regulated	This product is not regulated
	as a dangerous good when	as a dangerous good when	as a dangerous good when
	transported in sizes of ≤ 5 L or	transported in sizes of ≤ 5 L or	transported in sizes of ≤ 5 L or
	≤ 5 kg, provided the	≤ 5 kg, provided the	≤ 5 kg, provided the
	packagings meet the general	packagings meet the general	packagings meet the general
	provisions of 4.1.1.1, 4.1.1.2	provisions of 4.1.1.1, 4.1.1.2	provisions of 5.0.2.4.1, 5.0.2.6.
	and 4.1.1.4 to 4.1.1.8.	and 4.1.1.4 to 4.1.1.8.	1.1 and 5.0.2.8.

IMDG Code Segregation : Not applicable. group

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Α.	Regulation according to ISHA					
	ISHA Article 37	:	None of the components are listed.			
	ISHA Article 38	:	None of the components are listed.			
	Article 2 of Youth	:	Not applicable.			
	Protection Act on Substances Hazardous					
	to Youth					
	Exposure Limits of Chemical Substances and Physical Factors					
	The following components have an OEL: aluminium hydroxide					
	Exposure Standards established for Harmful Factors	:	None of the components are listed.			
	Harmful Factors Subject to Work Environment Measurement	:	The following components are listed: Aluminum compounds			
	Harmful Factors Subject to Special Health Check- up	:	The following components are listed: Aluminum and compounds			
	Hazardous Substances Subject to Control	:	The following components are listed: Aluminum and its compounds			
В.	Regulation according to TCCA					
	TCCA Toxic chemicals	:	Not applicable			
	TCCA Observational chemicals	:	None of the components are listed.			
	TCCA Article 32 (Banned)	:	None of the components are listed.			
	TCCA Article 32 (Restricted)	:	None of the components are listed.			
	TCCA Article 17 (TRI)	:	The following components are listed: 4,4'-(1-Methylethylidene) bisphenol polymer with (chloromethyl)oxirane; Boron and its compounds; Aluminium and its compounds			
	Korea inventory	:	Not determined.			
	Accident Precaution chemicals	:	None of the components are listed.			

:

Section 15. Regulatory information

C.	Dangerous Materials Safety Management Act	:	Not available.		
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.		
E. <u>Regulation according to other foreign laws</u>					
	Europe inventory	:	Not determined.		
	United States inventory (TSCA 8b)	:	Not determined.		
	Japan inventory	:	Not determined.		
	Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).		

Section 16. Other information

Α.	References	:	Not available.			
В.	Date of issue/Date of revision	:	14/06/2016			
C.	Version	:	2			
	Date of printing	:	14/06/2016			
D.	Other					
Indicates information that has changed from previously issued version.						
	Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations			

Notice to reader

•

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).



XInternational

Section 16. Other information

© AkzoNobel



AkzoNobel