Material Safety Data Sheet INTERGARD 5377 DARK GREY PART A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: Sales Order: {SalesOrd} HNA580 12/05/2011 A1-8

XInternational.

| 1. Identification of the preparation and company | | | |
|--|---------------------------------|--|--|
| Product Identity | INTERGARD 5377 DARK GREY PART A | | |
| Bulk Sales Reference No. | HNA580 | | |
| Company Name | International Paint LLC | | |
| | 6001 Antoine Drive | | |
| | Houston, Texas 77091 | | |
| Emergency | | | |
| CHEMTREC (USA) | (800) 424–9300 | | |
| International Paint | (713) 682–1711 | | |
| Poison Control Center | (800) 854–6813 | | |
| Customer Service | | | |
| International Paint | (800) 589–1267 | | |
| Fax No. | (800) 631–7481 | | |

2. Hazard identification of the product



GHS Classification;

| GHS Classification; | | |
|---|----------------|--|
| Item | Category | Hazard |
| Flammability | 3 | Flammable liquid and vapor |
| Acute Toxicity (mouth) | Not classified | Not applicable |
| Acute Toxicity (skin) | Not classified | Not applicable |
| Acute Toxicity (inhalation) | Not classified | Not applicable |
| Acute Toxicity (ingestion) | Not classified | Not applicable |
| Skin corrosion/irritation | Not classified | Not applicable |
| Eye damage/irritation | Not classified | Not applicable |
| Sensitization (respiratory) | Not classified | Not applicable |
| Sensitization (skin) | Not classified | Not applicable |
| Germ toxicity | Not classified | Not applicable |
| Specific target organ systemic toxicity (single exposure) | 1 | central nerve system, kidneys, liver, respiratory system |
| | 2 | central nerve system |
| | 3 | respiratory tract irritation |
| Specific target organ systemic Toxicity (repeated exposure) | 1 | central nerve system, lung, respiratory system |
| | 2 | Not applicable |
| Aspiration hazard | Not classified | Not applicable |
| Harmfulness to aquatic Environment (acute) | Not classified | Not applicable |
| Harmfulness to aquatic Environment (long term effect) | Not classified | Not applicable |
| Carcinogenicity | Not classified | Not applicable |

| Reproductive Toxicity | Not classified | Not applicable |
|-----------------------|----------------|----------------|
| Organic Peroxide | Not classified | Not applicable |

| Safety Phrases: | Not Applicable | | | | |
|-----------------|--|--|---|-----------|--|
| Overview | overexposure to solve Intentional misuse by | re associated repeated a ents with permanent bra deliberately concentrati I contact with eyes, skin | in and nervous system ng and inhaling the co | n damage. | |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. | | | | |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. | | | | |
| Skin | Causes skin irritation. May be harmful if absorbed through the skin. | | | | |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. | | | | |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. | | | | |
| HMIS Rating | Health: 3 | Flammability: 3 | Reactivity: 0 | PPE: X | |

| 3. Composition/information on ingredients | | | |
|---|--------------|----------|--|
| Ingredient | CAS No. | Percent | |
| 1,2,4–Trimethyl benzene | 0000095-63-6 | 1.0 – 10 | |
| Benzene, ethyl- | 0000100-41-4 | 1.0 – 10 | |
| Xylenes (o–, m–, p– isomers) | 0001330-20-7 | 1.0 – 10 | |
| Kaolin | 0001332-58-7 | 1.0 – 10 | |
| Carbon black | 0001333-86-4 | 1.0 – 10 | |
| Titanium dioxide | 0013463–67–7 | 1.0 – 10 | |
| Talc | 0014807–96–6 | 10 – 25 | |
| Reaction product of epichlorohydrin & bisphenol A | 0025085–99–8 | 25 – 50 | |
| Petroleum naphtha, light aromatic | 0064742-95-6 | 1.0 – 10 | |
| | | | |

| | 4. First aid measures | | |
|--|---|--|--|
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. | | |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. | | |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. | | |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. | | |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. | | |
| | 5. Fire-fighting measures | | |
| Flash Point | F: 106 C: 41 | | |
| Lower Explosive Limit (LEL) ERG Guide No. | 1 (%vol in air) at Normal Atmospheric Temp and Pressure 128 | | |

6. Accidental release measures

| Spill Response Procedures | ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. |
|-------------------------------------|---|
| Public Safety | CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet). |
| ERG Guide No. | 128 |
| | 7. Handling and storage |
| Storage Temperature | Store between 40–100F (4–38C). |
| Handling and Storage Precautions | Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling. |

| | | Expos | ure |
|--------------|------------------------------|--------------|---|
| CAS No. | Ingredient | Source | Value |
| 0000095-63-6 | 1,2,4–Trimethyl benzene | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | 25 ppm TWA; 125 mg/m3 TWA |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0000100-41-4 | Benzene, ethyl– | OSHA | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | ACGIH | 100 ppm TWA125 ppm STEL |
| | | NIOSH | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 100 ppm TWA125 ppm STEL |
| | | Mexico | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | Brazil | 78 ppm TWA; 340 mg/m3 TWA |
| 0001330–20–7 | Xylenes (o–, m–, p– isomers) | OSHA | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL |
| | | ACGIH | 100 ppm TWA150 ppm STEL |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 100 ppm TWA150 ppm STEL |
| | | Mexico | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL |
| | | Brazil | 78 ppm TWA; 340 mg/m3 TWA |
| 0001332–58–7 | Kaolin | OSHA | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| | | ACGIH | 2 mg/m3 TWA (particulate matter containing no asbestos and |

| | | NIOSH | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust) | | |
|--------------|-------------------------------|--------------|---|--|--|
| | | Supplier | No Established Limit | | |
| | | OHSA, CAN | 2 mg/m3 TWA (containing no Asbestos and | | |
| | | Mexico | 10 mg/m3 TWA20 mg/m3 STEL | | |
| | | Brazil | No Established Limit | | |
| 0001333-86-4 | Carbon black | OSHA | 3.5 mg/m3 TWA | | |
| | | ACGIH | 3.5 mg/m3 TWA | | |
| | | NIOSH | 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as1750 mg/m3 IDLH | | |
| | | Supplier | No Established Limit | | |
| | | OHSA, CAN | 3.5 mg/m3 TWA | | |
| | | Mexico | 3.5 mg/m3 TWA7 mg/m3 STEL | | |
| | | Brazil | No Established Limit | | |
| 0013463-67-7 | Titanium dioxide | OSHA | 15 mg/m3 TWA (total dust) | | |
| | | ACGIH | 10 mg/m3 TWA | | |
| | | NIOSH | 5000 mg/m3 IDLH | | |
| | | Supplier | No Established Limit | | |
| | | OHSA, CAN | 10 mg/m3 TWA (total dust) | | |
| | | Mexico | 10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti) | | |
| | | Brazil | No Established Limit | | |
| 0014807–96–6 | Talc | OSHA | No Established Limit | | |
| | | ACGIH | 2 mg/m3 TWA (particulate matter containing no asbestos and | | |
| | | NIOSH | 2 mg/m3 TWA (containing no Asbestos and | | |
| | | Supplier | No Established Limit | | |
| | | OHSA, CAN | 2 mg/m3 TWA (containing no Asbestos and | | |
| | | Mexico | 2 mg/m3 TWA (respirable fraction) | | |
| | | Brazil | No Established Limit | | |
| | Reaction product of | OSHA | No Established Limit | | |
| | epichlorohydrin & bisphenol A | ACGIH | No Established Limit | | |
| | | NIOSH | No Established Limit | | |
| | | Supplier | No Established Limit | | |
| | | OHSA, CAN | No Established Limit | | |
| | | Mexico | No Established Limit | | |
| | | Brazil | No Established Limit | | |
| 0064742–95–6 | Petroleum naphtha, light | OSHA | No Established Limit | | |
| | | ACGIH | No Established Limit | | |
| | | NIOSH | No Established Limit | | |
| | | Supplier | No Established Limit | | |
| | | OHSA, CAN | No Established Limit | | |
| | | Mexico | No Established Limit | | |
| | | Brazil | No Established Limit | | |

| CAS No. | Ingredient | Source | Value |
|--------------|------------------------------|--------|---|
| 0000095-63-6 | 1,2,4–Trimethyl benzene | NIOSH | No Established Limit |
| 0000100-41-4 | Benzene, ethyl- | NIOSH | Eye skin |
| 0001330–20–7 | Xylenes (o–, m–, p– isomers) | | Central nervous system depressant; respiratory and eye irritation |
| 0001332–58–7 | Kaolin | | Skin and mucous membrane injury respiratory effects |

| 0001333-86-4 | Carbon black | NIOSH | Lung cardiovascular |
|--------------|---|-------|---|
| 0013463-67-7 | Titanium dioxide | NIOSH | Lung tumors in animals |
| 0014807–96–6 | Talc | | (containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects |
| | Reaction product of epichlorohydrin & bisphenol A | NIOSH | No Established Limit |
| 0064742-95-6 | Petroleum naphtha, light aromatic | NIOSH | No Established Limit |

| Carcinogen Data | | | | |
|-----------------|--------------------------|--------|--|--|
| CAS No. | Ingredient | Source | Value | |
| 0000095-63-61 | 1,2,4–Trimethyl | OSHA | Select Carcinogen: No | |
| | benzene | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |
| 0000100-41-4 | Benzene, ethyl– | OSHA | Select Carcinogen: Yes | |
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; | |
| 0001330–20–7 | Xylenes (o–, m–, p– | OSHA | Select Carcinogen: No | |
| | isomers) | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; | |
| 0001332–58–7 | Kaolin | OSHA | Select Carcinogen: No | |
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |
| 0001333-86-4 | Carbon black | OSHA | Select Carcinogen: Yes | |
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; | |
| 0013463–67–7 | Titanium dioxide | OSHA | Select Carcinogen: Yes | |
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; | |
| 0014807–96–6 | Talc | OSHA | Select Carcinogen: No | |
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; | |
| 0025085–99–8 | epichlorohydrin & | OSHA | Select Carcinogen: No | |
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |
| 0064742–95–6 | Petroleum naphtha, light | OSHA | Select Carcinogen: No | |
| | aromatic | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |

Respiratory

Eyes

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document.

| Skin | Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the |
|----------------------|--|
| | chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls | Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |
| | 9. Physical and chemical properties |

| | 10. Stability and reactivity |
|------------------|--|
| Evaporation Rate | Slower than ether |
| VOC % | Refer to the Technical Data Sheet or label where information is available. |
| Vapor Density | Heavier than air |
| Boiling Point F | 279 |
| Specific Gravity | 1.42 |
| pН | No Established Limit |
| Physical State | Liquid Coloured |

| General | This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled. |
|---------------------------|--|
| Incompatible Materials | Strong oxidizing agents. |
| Hazardous Decompostion | May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide. |

| 11. Toxicological information | | | | | | |
|--|----------------------------------|-------------------------------------|---------------------------------------|--|--|--|
| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | | | |
| 1,2,4-Trimethyl benzene – (0000095–63–6) | 3,400.00, Rat – Category: 5 | 3,160.00, Rabbit - Category: 5 | | | | |
| Benzene, ethyl- – (0000100–41–4) | 3,500.00, Rat – Category: 5 | 15,354.00, Rabbit – Category: NA | 17.20, Rat – Category: 4 | | | |
| Xylenes (o–, m–, p– isomers) – (0001330–20–7) | 4,300.00, Rat – Category: 5 | 1,700.00, Rabbit - Category: 4 | 29.08, rat – Category: NA | | | |
| Kaolin – (0001332–58–7) | | | | | | |
| Carbon black – (0001333–86–4) | 15,400.00, Rat – Category: NA | 3,000.00, Rabbit - Category: 5 | | | | |
| Titanium dioxide – (0013463–67–7) | 10,000.00, Rat – Category: NA | 10,000.00, Rabbit – Category: NA | 6,082.00, Rat – Category: NA | | | |
| Talc – (0014807–96–6) | | | | | | |
| Reaction product of epichlorohydrin & bisphenol A – (0025085–99–8) | | | | | | |
| Petroleum naphtha, light aromatic – (0064742–95–6) | 8,400.00, Rat – Category: NA | 2,000.00, Rabbit - Category: 4 | 5.20, Rat – Category: 3 | | | |

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

| | 14. Transpo | ort information | | | |
|--|---|---|---|--|--|
| DOT (Domestic Su | Inface Transportation) | | ean Transportation) | | |
| DOT (Domestic Surface Transportation) DOT Proper Shipping PAINT Name | | IMDG Proper Shipping Name | • • | | |
| DOT Hazard Class | 3 | IMDG Hazard Class | 3 – Flammable and Combustible liquid | | |
| UN / NA Number | IN / NA Number UN 1263 | | UN 1263 | | |
| DOT Packing Group CERCLA/DOT RQ | III 107 gal. / 1269 lbs. | IMDG Packing Group System Reference | 2 | | |
| 01.102.1201.1.4 | ga., . <u>_</u> | Code | - | | |
| | 15. Regulat | ory information | | | |
| Regulatory Overview | selected regulations a | Section 15 is not intended to b re represented. All ingredients ubstance Control Act) Inventory rentory. | of this product are listed | | |
| WHMIS Classification | B3;D2B | | | | |
| DOT Marine Pollutants | | | | | |
| (No Product Ingr DOT Severe Marine Po (No Product Ingr | ollutants (1%): | | | | |
| | icals and RQs (>.1%) : | | | | |
| Benzene | , ethyl- (1000 lb final RQ; 45 | 54 kg final RQ) | | | |
| | (· · · · · · · · · · · · · · · · · · · | final RQ; 45.4 kg final RQ) | | | |
| EPCRA 302 Extremely (No Product Ingr | () | | | | |
| EPCRA 313 Toxic Che | | | | | |
| | methyl benzene | | | | |
| Benzene | | | | | |
| | (o–, m–, p– isomers) | | | | |
| Mass RTK Substances | methyl benzene | | | | |
| | | | | | |
| Carbon black Benzene, ethyl– | | | | | |
| Kaolin | | | | | |
| Talc | | | | | |
| Titanium | dioxide | | | | |
| Xylenes | (o–, m–, p– isomers) | | | | |
| Mass Extraordinarily H (No Product Ingr | . , | | | | |
| Penn RTK Substances | (>1%): | | | | |
| | methyl benzene | | | | |
| Carbon b | | | | | |
| Benzene | , ethyl– | | | | |
| Kaolin | | | | | |
| Talc Titanium | dioxido | | | | |
| | aioxiae (o–, m–, p– isomers) | | | | |
| Ayienes | (0-, 11-, p-1soliters) | | | | |

Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%) : Carbon black Benzene, ethyl-Kaolin Magnesium carbonate Talc Titanium dioxide Xylenes (o-, m-, p- isomers) **RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%) : 1,2,4-Trimethyl benzene Carbon black Benzene, ethyl-Kaolin Talc Titanium dioxide Xylenes (o-, m-, p- isomers) N.J. Special Hazardous Substances (>.01%) : Carbon black Cumene Benzene, ethyl-Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%) : 1,2,4-Trimethyl benzene Benzene, ethyl-Xylenes (o-, m-, p- isomers) Proposition 65 – Carcinogens (>0%): Carbon black Cumene Benzene, ethyl-Nickel Proposition 65 – Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): (No Product Ingredients Listed)

Risk Phrases:

Not Applicable

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.