Safety Data Sheet INTERGARD 292 ORANGE PART A

Bulk Sales Reference No .:

MSDS Revision Date:

MSDS Revision Number:

Sales Order: {SalesOrd} NHA219 09/28/2013 A6-

X International

1. Identification of the preparation and company		
1.1. Product identifier Product Identity Bulk Sales Reference No.	INTERGARD 292 ORANGE PART A NHA219	
1.2. Relevant identified uses of the substance or mixte Intended Use Application Method	ure and uses advised against See Technical Data Sheet. See Technical Data Sheet.	
1.3. Details of the supplier of the safety data sheet		
Company Name	International Paint LLC 6001 Antoine Drive Houston, Texas 77091	
Emergency		
CHEMTREC (USA)	(800) 424-9300	
International Paint	(713) 682-1711	
Poison Control Center	(800) 854-6813	
Customer Service		
International Paint	(800) 589-1267	
Fax No.	(800) 631-7481	
2. Hazard identifi	cation of the product	

2.1. Classification of the substance or mixture

Skin Irrit. 3;H316 Causes mild skin irritation. Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.

Warning.

H316 Causes mild skin irritation. H412 Harmful to aquatic life with long lasting effects.

P273 Avoid release to the environment.

P332+313 If skin irritation occurs: Get medical advice/attention.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating H	lealth: 2	Flammability: 1	Reactivity: 0
---------------	-----------	-----------------	---------------

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Modified Epoxy Resin CAS Number: TS-RE2404	10 - 25		[1]
Barium sulfate CAS Number: 0007727-43-7	10 - 25		[1][2]
Talc CAS Number: 0014807-96-6	1.0 - 10		[1][2]
Wollastonite (Ca(SiO3)) CAS Number: 0013983-17-0	1.0 - 10		[1]
Ethylene glycol monopropyl ether CAS Number: 0002807-30-9	1.0 - 10	Acute Tox. 4;H312 Eye Irrit. 2;H319	[1]
2-Butoxyethanol CAS Number: 0000111-76-2	1.0 - 10	Acute Tox. 4;H332 Acute Tox. 4;H312 Acute Tox. 4;H302 Eye Irrit. 2;H319 Skin Irrit. 2;H315	[1][2]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10		[1][2]
Nitrous acid, sodium salt CAS Number: 0007632-00-0	0.10 - 1.0	Ox. Sol. 3;H272 Acute Tox. 3;H301 Aquatic Acute 1;H400	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
4.2. Most important syr	nptoms and effects, both acute and delayed
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.
	5. Fire-fighting measures

5.1. Extinguishing media

SMALL FIRES: Use dry chemical, CO2, water spray or foam. LARGE FIRES: Use water spray, fog, or foam. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike

fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses. ERG Guide No. 159

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

	8. Exposu	ure controls an	d personal protection	
		8.1. Control p	parameters	
		Expos	ure	
CAS No.	Ingredient Source Value			
0000111-76-2	2-Butoxyethanol	OSHA	50 ppm TWA; 240 mg/m3 TWA	
		ACGIH	20 ppm TWA	
		NIOSH	5 ppm TWA; 24 mg/m3 TWA700 ppm IDLH	
		Supplier	No Established Limit	
		OHSA, CAN	20 ppm TWA	

Mexico

Brazil

26 ppm TWA LMPE-PPT; 120 mg/m3 TWA LMPE-PPT75 ppm STEL [LMPE-CT]; 360 mg/m3

39 ppm TWA LT; 190 mg/m3 TWA LT

STEL [LMPE-CT]

000007.00.0		00114	No Totoblished Linit
	Ethylene glycol monopropyl ether	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier OHSA,	No Established Limit 25 ppm TWA; 110 mg/m3 TWA
		CAN	
		Mexico	No Established Limit
		Brazil	No Established Limit
0007632-00-0	Nitrous acid, sodium salt	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7 Titaniı	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
	Mexico	10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)	
		Brazil	No Established Limit
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA,	No Established Limit
		CAN	
		Mexico	No Established Limit
		Brazil	No Established Limit
0014807-96-6	Talc	OSHA	No Established Limit
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	2 mg/m3 TWA (containing no Asbestos and
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	2 mg/m3 TWA LMPE-PPT (respirable fraction)
		Brazil	No Established Limit
TS-RE2404	Modified Epoxy Resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA,	No Established Limit
		CAN	
		Mexico	No Established Limit

			Brazil	No Established Limit
--	--	--	--------	----------------------

Health Data			
CAS No.	Ingredient	Source	Value
0000111-76-2	2-Butoxyethanol		Adverse effects on blood and hematopoietic system tissue irritation
0002807-30-9	Ethylene glycol monopropyl ether	NIOSH	No Established Limit
0007632-00-0	Nitrous acid, sodium salt	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	No Established Limit
0014807-96-6	Talc	NIOSH	(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
TS-RE2404	Modified Epoxy Resin	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000111-76-2 2-Butoxyethanol		OSHA	Select Carcinogen: No
			Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0002807-30-9	Ethylene glycol	OSHA	Select Carcinogen: No
	monopropyl ether	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007632-00-0	Nitrous acid, sodium salt	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0014807-96-6	Talc	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
TS-RE2404	Modified Epoxy Resin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in

Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Depending on the site-specific conditions of use, provide adequate ventilation.
Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties			
Appearance	Coloured Liquid		
Odour threshold	Not Measured		
рН	No Established Limit		
Melting point / freezing point	Not Measured		
Initial boiling point and boiling range	99 (°C) 210 (°F)		
Flash Point	No Established Limit (°C) No Established Limit(°F)		
Evaporation rate (Ether = 1)	Not Measured		
Flammability (solid, gas)	Not Applicable		
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1		
	Upper Explosive Limit: No Established Limit		
vapor pressure (Pa)	Not Measured		
Vapor Density	Heavier than air		
Specific Gravity	1.35		
Partition coefficient n-octanol/water (Log Kow)	Not Measured		
Auto-ignition temperature	Not Measured		
Decomposition temperature	Not Measured		
Viscosity (cSt)	No Established Limit		
VOC %	Refer to the Technical Data Sheet or label where information is available.		

10.1. Reactivity No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10. Stability and reactivity

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Modified Epoxy Resin - (TS-RE2404)	No data available	No data available	No data available	No data available
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
Talc - (14807-96-6)	No data available	No data available	No data available	No data available
Wollastonite (Ca(SiO3)) - (13983-17-0)	No data available	No data available	No data available	No data available
Ethylene glycol monopropyl ether - (2807-30-9)	3,089.00, Rat - Category: 5	876.00, Rabbit - Category: 3	No data available	No data available
2-Butoxyethanol - (111-76-2)	470.00, Rat - Category: 4	220.00, Rabbit - Category: 3	2.21, Rat - Category: 3	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
Nitrous acid, sodium salt - (7632-00-0)	180.00, Rat - Category: 3	No data available	No data available	5.50, Rat - Category: NA

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/l	mg/l	mg/l
Modified Epoxy Resin - (TS-RE2404)	Not Available	Not Available	Not Available

Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Talc - (14807-96-6)	Not Available	Not Available	Not Available
Wollastonite (Ca(SiO3)) - (13983-17-0)	Not Available	Not Available	Not Available
Ethylene glycol monopropyl ether - (2807-30-9)	Not Available	Not Available	Not Available
2-Butoxyethanol - (111-76-2)	220.00, Fish (Piscis)	1,000.00, Daphnia magna	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
Nitrous acid, sodium salt - (7632-00-0)	0.11, Oncorhynchus mykiss	12.50, Daphnia magna	159.00 (72 hr), Tetraselmis chuii

12.2. Persistence and degradability
No data available
12.3. Bioaccumulative potential
Not Measured
12.4. Mobility in soil
No data available
12.5. Results of PBT and vPvB assessment
This product contains no PBT/vPvB chemicals.

13. Disposal considerations

13.1. Waste treatment methods

14.6. Special precautions for user

Not Applicable

12.6. Other adverse effects

No data available

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number		Not Regulated		
14.2. UN proper shipping nar	ne	Not Regulated		
14.3. Transport hazard class	(es)			
DOT (Domestic Surface	Transportation))	IMO / IMDG (Ocean	Transportation)
DOT Proper Shipping Name	Not Regulated	ł	IMDG Proper Shipping Name	Not Regulated
DOT Hazard Class	Not Regulated	ł	IMDG Hazard Class Sub Class	Not Regulated Not applicable
UN / NA Number	Not Regulated	Ł		
DOT Packing Group	Not Regulated	Ł	IMDG Packing Group	Not Regulated
CERCLA/DOT RQ	5916 gal. / 66	667 lbs.	System Reference Code	9
14.4. Packing group		Not Regulated		
14.5. Environmental hazards				
IMDG Marine Pollu	tant: No			

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

	15. Regulatory information
Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.
WHMIS Classification	Not Regulated
DOT Marine Pollutants	
(No Product Ingr	
DOT Severe Marine Po (No Product Ingre	
EPCRA 311/312 Chem	icals and RQs (>.1%):
Nitrous acid, sodi	um salt (100 lb final RQ; 45.4 kg final RQ)
EPCRA 302 Extremely (No Product Ingre	
EPCRA 313 Toxic Che	micals (>.1%) :
Barium	
Nitrous acid, sodi	um salt
Mass RTK Substances	(>1%):
Barium sulfate	
2-Butoxyethanol	
Talc	
Titanium dioxide	
Penn RTK Substances	(>1%):
Barium sulfate	
2-Butoxyethanol	
Talc	
Titanium dioxide	
(No Product Ingr	us Substances (>.01%) : edients Listed)
RCRA Status: (No Product Ingr	edients Listed)
N.J. RTK Substances (
Barium sulfate	
2-Butoxyethanol	
Talc	
Titanium dioxide	
N.J. Special Hazardous	Substances (>.01%):
Barium	
2-Butoxyethanol	
	monomethyl ether
Quartz	
Talc	
N.J. Env. Hazardous S	ubstances (>.1%):
Barium	um colt
Nitrous acid, sodi Proposition 65 - Carcin	
1,4-Dioxane	uyenə (>v /o).
Acetaldehyde	
Benzene, (chloror	netbyl)-
Epichlorohydrin	iong.
Ethylene oxide	
Lead	
Quartz	
Titanium dioxide	
	e Repro Toxins (>0%):

Ethylene oxide Lead Proposition 65 - Male Repro Toxins (>0%): Epichlorohydrin Ethylene oxide Lead Proposition 65 - Developmental Toxins (>0%): Ethylene oxide Lead

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H272 May intensify fire; oxidizer.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document