

Biodegradable Cleaner

PRODUCT DESCRIPTION A waterbased, biodegradable alkaline cleaner.

INTENDED USES To remove oil, grease and other contaminants prior to further surface preparation or for general cleaning purposes. For interior and exterior surfaces.

PRODUCT INFORMATION

Colour	GMA571-Clear
Part B (Curing Agent)	One pack
Mix Ratio	Not applicable
Method of Application	Airless Spray, Brush

Drying Information

Overcoating Data - see limitations

Substrate Temperature

Note Drying and Overcoating Information are not applicable for this product.

REGULATORY DATA **VOC** 0 g/lit as supplied (EPA Method 24)

Note: VOC values are typical and are provided for guidance purposes only. These may be subject to variation depending on factors such as differences in colour and normal manufacturing tolerances.

International 950

Biodegradable Cleaner



SURFACE PREPARATIONS See 'Application' data on page 3.

Marine Coatings

Biodegradable Cleaner

APPLICATION May be used as supplied if contamination is particularly heavy, otherwise follow dilution recommendations specified in "Mixing" section. Apply International 950 to the substrate to be cleaned and allow to soak for 3-5 minutes. Rinse away with copious amounts of fresh water ensuring all deposits are removed and adhesion of the coatings to be applied is not affected.

Mixing International 950 is supplied in concentrated form but is normally diluted with fresh water prior to application. (Dilution ratios may vary depending on severity of the substrate contamination).
Dilution Ratios:
Brush-on/Wipe : 1 part International 950 to 5-10 parts fresh water.
High Pressure Spray : 1 part International 950 to 10-20 parts fresh water.

Work Stoppages and Cleanup Flush all equipment with clean water. Unused, diluted International 950 can be returned to its original container for future use or disposed of immediately in a safe manner recommended for alkaline materials.

SAFETY

All work involving the application and use of this product should be performed in compliance with all relevant national Health, Safety & Environmental standards and regulations.

Prior to use, obtain, consult and follow the Material Safety Data Sheet for this product concerning health and safety information. Read and follow all precautionary notices on the Material Safety Data Sheet and container labels. If you do not fully understand these warnings and instructions or if you can not strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapour concentrations within safe limits and to protect against toxic or oxygen deficient hazards. Take precautions to avoid skin and eye contact (ie. gloves, goggles, face masks, barrier creams etc.) Actual safety measures are dependant on application methods and work environment.

EMERGENCY CONTACT NUMBERS:

USA/Canada - Medical Advisory Number 1-800-854-6813

Europe - Contact (44) 191 4696111. For advice to Doctors & Hospitals only contact (44) 207 6359191

R.O.W. - Contact Regional Office

Biodegradable Cleaner

LIMITATIONS

Apply in good weather when air and surface temperatures are above 2°C. Unmixed material (in closed containers) should be maintained in protected storage between 4-38°C. Keep from freezing and do not apply under freezing conditions. Maximum substrate application temperature is 57°C. This material may cause lifting of some coatings, such as alkyd based coatings due to alkaline (pH approximately 13) nature of International 950.

Only use spray equipment designed for use with highly alkaline products.

Technical and application data herein is for the purpose of establishing a general guideline of the coating and proper coating application guidelines. Test performance results were obtained in a controlled laboratory environment and International Paint makes no claim that the exhibited published test results, or any other tests, accurately represent results actually found in all field environments. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

UNIT SIZE	Unit Size	Part A
		Vol Pack
	5 US gal	5 US gal 5 US gal
For availability of other unit sizes consult International Paint		
UNIT SHIPPING WEIGHT (TYPICAL)	Unit Size	Unit Weight
	5 US gal	46 lb
STORAGE	Shelf Life	24 months minimum from date of manufacture when maintained in protected storage at 4-38°C
		Subject to reinspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.

WORLDWIDE AVAILABILITY Consult International Paint.

IMPORTANT NOTE

The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product. We hereby disclaim any warranties or representations, express or implied, by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose. All products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.

This Technical Data Sheet is available on our website at www.international-marine.com or www.international-pc.com, and should be the same as this document. Should there be any discrepancies between this document and the version of the Technical Data Sheet that appears on the website, then the version on the website will take precedence.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies.

© AkzoNobel, 2015

www.international-marine.com