

## Non-Slip Aggregate

**PRODUCT DESCRIPTION** Anti-skid additive for use in a range of coating schemes.

**INTENDED USES** To be added to the top coat of a coating scheme to give a non slip surface profile.

<b>PRODUCT INFORMATION</b>	<b>Colour</b>	GMA132
	<b>Finish/Sheen</b>	Not applicable
	<b>Volume Solids</b>	100% ±3% (ISO 3233:1998)
	<b>Specific Gravity</b>	2.58
	<b>Typical Film Thickness</b>	Not applicable
	<b>Method of Application</b>	Broadcast over wet paint surface. If necessary, apply an additional coat of paint over the aggregate to embed it into the coating.  Alternatively, pre-mix in the wet paint and apply by brush or roller.  Consult International Paint for scheme recommendations.
	<b>Flash Point (Typical)</b>	Not applicable

**Drying Information**

**Overcoating Data - see limitations**

**Substrate Temperature**

**Note** Drying and Overcoating Information are not applicable for this product.

<b>REGULATORY DATA</b>	<b>VOC</b>	Not Applicable
------------------------	------------	----------------

## Non-Slip Aggregate

### SYSTEMS AND COMPATIBILITY

Consult your International Paint representative for the system best suited for the surfaces to be protected.

---

### SURFACE PREPARATIONS

Not applicable.

---

## Marine Coatings

## Non-Slip Aggregate

### APPLICATION

Mixing	Not applicable
Thinner	Not applicable
Airless Spray	Not applicable
Brush	Not applicable
Roller	Not applicable
Cleaner	Not applicable

### SAFETY

All work involving the application and use of this product should be performed in compliance with all relevant national Health, Safety & Environmental standards and regulations.

Prior to use, obtain, consult and follow the Material Safety Data Sheet for this product concerning health and safety information. Read and follow all precautionary notices on the Material Safety Data Sheet and container labels. If you do not fully understand these warnings and instructions or if you can not strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapour concentrations within safe limits and to protect against toxic or oxygen deficient hazards. Take precautions to avoid skin and eye contact (ie. gloves, goggles, face masks, barrier creams etc.) Actual safety measures are dependant on application methods and work environment.

#### EMERGENCY CONTACT NUMBERS:

USA/Canada - Medical Advisory Number 1-800-854-6813

Europe - Contact (44) 191 4696111. For advice to Doctors & Hospitals only contact (44) 207 6359191

R.O.W. - Contact Regional Office

## Non-Slip Aggregate

**LIMITATIONS** Aggregate must be dry at time of use.

Discard any damaged containers.

---

### UNIT SIZE

25 Kg per Bag

For availability of other unit sizes consult International Paint

### UNIT SHIPPING WEIGHT (TYPICAL)

**WORLDWIDE AVAILABILITY** Consult International Paint.

---

### IMPORTANT NOTE

*This information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product. We hereby disclaim any warranties or representations, express or implied, by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose. All products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.*

*This Technical Data Sheet is available on our website at [www.international-marine.com](http://www.international-marine.com) or [www.international-pc.com](http://www.international-pc.com), and should be the same as this document. Should there be any discrepancies between this document and the version of the Technical Data Sheet that appears on the website, then the version on the website will take precedence.*

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies.

© AkzoNobel, 2015

[www.international-marine.com](http://www.international-marine.com)