

CLY999/M INTERLAC 665 BLACK

4

10/25/14

1.

1.1. INTERLAC 665 BLACK  
CLY999/M

1.2.

1.3.

626-6

( 8-6 )

1.4.

055-632-6286( ),055 586 2310( )  
055 587 6276( )  
055 586 2310( )  
055 586 2310( )

2.

2.1. 3; H226

2;H411

2.2. 11 , 12



H226  
H411

[ ]:  
P210 / / /  
P260 / /

P262 , ,  
P273  
P280 / / /  
[ ]:  
P301+310 : /  
P303+361+353 ( ) :  
/  
P331  
P332+313 : /  
P370 :  
P378 , , ,  
P391  
[ ]:  
P403+233 가  
[ ]:  
P501 ( )

2.3. PBT ( , ) vPvB ( , )

3.

/	%	GHS	
White spirits CAS No: 0064742-82-1	30-40	1;H304 - 2;H411 3; H226	[1]
carbon black CAS No: 0001333-86-4	1-2.5		[1][2]
xylene CAS No: 0001330-20-7	1-2.5	3; H226 - 4;H312 - 4;H332 / 2;H315 / 2AIH319 -1 ;H336 - 1;H372	[1][2]
Amorphous fumed silica CAS No: 0112945-52-5	1-2.5		[1]
Methyl ethyl ketoxime CAS No: 0000096-29-7	<1	2;H351 - 4;H312 / 1;H318 1;H317	[1]
	60-70	---	---

- 1)
- 2) 가
- 3) PBT vPvB  
16

4.

4.1.

가

가

10

4.2. 가 /

4.3.

5. ,

5.1.

; , , , .

Note; 가 .

가

5.2.

가 : , , , .

5.3.

가

가

6.

6.1.

가 가 가 , 가

6.2.

가

6.3.

.8

, , 가 . (13 .)

가

가

,  
가

가

7.

7.1.

가

, 가 (LEL) (OEL)

가

가

, 가 (LEL) (OEL)

7.2.

( )

: , ,

,8

가 , 가  
가 , 1 가

7.3. Specific end use(s)

가

,가 .3

Hot surfaces, Sparks,

가 ( 60% , )

8.

8.1.

(OEL) (ACGIH)

(ACGIH)

ppm mg/m<sup>3</sup> ppm mg/m<sup>3</sup>

Barium Sulphate

2 10

Calcium carbonate

10

carbon black

3.5

xylene

150 655 100 434

(P) (Peak exposure limit)

(R)

(Sk)

(Sen)

(Cat 1)

(Cat 2) 가

(Cat 3)

**DNEL/PNEC**

8.2.

가

가 (visor)

(overall)

가

가

.가

가

9.

pH

/ (°C)

(°C)

65

40

( = 1)

( , )

/

: .8 ( White spirits )

: 6.6 ( xylene )

(Pa)

1.18

n-

/

(Log Kow)

9.2.

10.

10.1.

10.2.

.(Section 7 )

가

10.3.

가

10.4.

.(7 )

10.5.

10.6.

가

11.

(OEL)

가  
가  
가  
2

	LD50, mg/kg	LD50, mg/kg	LD50, mg/L/4hr	/ LD50, mg/L/4hr
Amorphous fumed silica - (112945-52-5)	3,160.00,			
carbon black - (1333-86-4)	8,000.00,			
Methyl ethyl ketoxime - (96-29-7)	930.00,	2,000.00,	20.00,	
White spirits - (64742-82-1)	5,000.00,	3,160.00,		
xylene - (1330-20-7)	4,299.00,	1,548.00,		20.00,

( )		
( )		
( )		
/		
/		
(1 )		
( )		

12.

12.1.

Dangerous Preparations Directive 1999/45/EC

가  
( 3 )

가

	96 hr LC50 mg/l	49 hr EC50 mg/l	ErC50 mg/l
White spirits - (64742-82-1)	100.00, Fish (Piscis)	2.60, Chaetogammarus marinus	
carbon black - (1333-86-4)	1,000.00, Danio rerio	5,600.00, Daphnia magna	10,000.00 (72 hr), Scenedesmus subspicatus
xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Amorphous fumed silica - (112945-52-5)			
Methyl ethyl ketoxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus

12.2.

가 .

12.3.

12.4.

12.5. , 가

PBT ( , ) vPvB ( , ) .

12.6.

13.

13.1.

가

..

14.

14.1. 1263

14.2.

14.3.

1263, , 3, III, 3[Y]

IMDG Class/Div. 3

EmS F-E,S-E

ICAO/IATA 3

14.4. III



14.5.

:

IMDG

: ( Naphtha (petroleum), hydrodesulfurized heavy )

14.6. 가

가

14.7.

MARPOL73/78 Annex II IBC Code .

15.

4 , 2 , III

MSDS 8 .

( )

(CMR):

carbon black (0001333-86-4)

Silica(quartz) (0014808-60-7)

ethanol (0000064-17-5)

:

xylene (0001330-20-7)

:

xylene (0001330-20-7)

가

:

( )

:

( )

:

( )

:

( )

Group I:

( )

Group II:

Barium Sulphate (0007727-43-7)

xylene (0001330-20-7)

:

( )

( )

:

( )

: 10/25/2014

: 4

: 09/28/2010

MSDS KOSHA, NITE, ESIS, NLM, SIDS, IPCS, NCIS

SDS

Section 3 Phrases

H226

H304

H312

H315

H319

H332

H336

H372

H411

**This SDS is valid for 5 years from the revised date on page 1.**



Akzo Nobel

가